



**The Deutsche Bundesbank's technical specifications for
the clearing and settlement of interbank SEPA direct debits
via the RPS SEPA-Clearer (SCL) 2023 Version 1.0
("SDD/SCL technical specifications")**

valid from 19 March 2023

Notes on the English translation

This translation has been prepared with the greatest possible care; however,
in case of doubt, the German text is the authoritative version.

Contents

1	Introduction	5
2	Duplication checks	6
2.1	Duplication checks in the SEPA-Clearer.....	6
2.2	Duplication checks in other CSMs.....	7
3	Cross-referencing checks	8
3.1	Cross-referencing checks in the SEPA-Clearer.....	8
3.2	Cross-referencing checks in other CSMs.....	8
4	Daily reconciliation report for direct debits (DRD)	10
4.1	DRD header.....	10
4.2	DRD (pacs.003) direct debit bulks sent body.....	11
4.3	DRD (pacs.004) return/refund bulks sent body.....	12
4.4	DRD (pacs.007) reversal bulks sent body.....	13
4.5	DRD (pacs.002) reject bulks sent body.....	14
4.6	DRD (camt.056) payment cancellation request bulks sent body.....	15
4.7	DRD (pacs.003) direct debit bulks received body.....	16
4.8	DRD (pacs.004) return bulks received body.....	17
4.9	DRD (pacs.007) reversal bulks received body.....	18
4.10	DRD (pacs.002) reject bulks received body.....	19
4.11	DRD (camt.056) payment cancellation request bulks received body.....	20
4.12	DRD trailer.....	21
5	XML file header	22
5.1	Input debit file (IDF) header (BBkIDFBkDirDeb).....	22
5.2	Debit validation file (DVF) header (BBkDVFBkDirDeb).....	22
5.3	Debit notification file (DNF) header (BBkDNFBkDirDeb).....	22
5.4	Settled debit file (SDF) header (BBkSDFBkDirDeb).....	22
5.5	Unsettled debit file (UDF) header (BBkSDFBkDirDeb).....	22
5.6	Result of settlement file (RSF) header (BBkRSFBkDirDeb).....	22
6	XML interbank messages	23
6.1	SEPA direct debit – interbank direct debit (pacs.003.001.02).....	23
6.2	SEPA direct debit – interbank direct debit reject SCL (pacs.002.001.03SCLSD).....	23
6.3	SEPA direct debit – interbank direct debit reject (pacs.002.001.03SDD).....	23
6.4	SEPA direct debit – interbank payment cancellation request (camt.056.001.01SDD).....	23
6.5	SEPA direct debit – interbank direct debit return/refund (pacs.004.001.02SDD).....	23
6.6	SEPA direct debit – interbank direct debit reversal (pacs.007.001.02).....	23
7	Use of the instructing agent/instructed agent	24
8	Error codes/rejection reason codes	28
9	Character set	37
10	Notes on format/status	38
10.1	Explanatory notes on the format of XML file headers and daily reconciliation reports.....	38
10.2	Completing amount fields in line with the schema.....	38
10.3	Use of filling characters in the amount fields.....	38
10.4	Use of white spaces in XML fields, in this case the “collapsing” procedure.....	39
10.5	Namespace declaration.....	40
11	Compression procedures	40
11.1	FileAct.....	40
11.2	EBICS.....	40
12	General specifications of message elements	40
13	TARGET referencing	42
14	Automated e-mail notification	45

14.1 Repeated settlement attempts	45
14.2 Advance information	46

Changes/additions to the “technical specifications 2021” compared with version 1.0

Section	Location	Changes/additions
12		Effects of TARGET2/T2S consolidation on the reporting of settlement references in credit and debit notifications and in account statements

1 Introduction

All items to be processed between the SEPA-Clearer and direct SEPA-Clearer participants are exchanged in the form of physical files. The formats of the individual files and bulks (logical files contained in files) are specified in the corresponding sections of this document.

If the XML format and syntax rules defined in the XSD schema files are not observed, a file rejection message is generated by the SEPA-Clearer. With regard to outgoing files, the data formats provided meet the specifications of this document.

The SEPA-Clearer's SDD service (comprising the SDD Core service and an SDD B2B service) supports SEPA direct debits in XML format as stipulated in the ISO 20022 standard and the EPC specifications. Checking rules that go beyond schema validations are described in the following sections.

Message types pacs.002.001.03SCL and camt.056.001.01 are not part of the EPC specifications. Message type pacs.002.001.03SCL is a rejection message which the SEPA-Clearer sends to the submitter in the event of an error to inform them about bulks or individual transactions (at the validation or settlement stage). Message type camt.056.001.01 is used by the payee's payment service provider to cancel a previously sent individual payment (direct debit) prior to settlement.

2 Duplication checks

2.1 Duplication checks in the SEPA-Clearer

Participants in the RPS SEPA-Clearer are advised to unambiguously reference each individual transaction every business day. Ensuring that payments are unambiguous helps to avoid duplicate payments and makes it easier to classify and trace specific payments.

The SEPA-Clearer carries out duplication checks at file, bulk and individual transaction level. These cover the following criteria, from which an unambiguous key can be derived.

- Service (“Core” or “B2B”)
- Reference number
- Identification of the party that allocated the reference
- Interbank settlement date or processing day in the SEPA-Clearer

The table below shows the duplication criteria applying at file, bulk and individual transaction levels.

	Origin	Service	Reference number	BIC	Date
Files	IDF file header	CORE or B2B	File reference If a file is rejected, it must always be given a new file reference before it is resubmitted.	Sending institution	-
IDF bulks	IDF group header or assignment	CORE or B2B	Message ID or identification It is necessary to ensure that the <Msgld> remains unambiguous for all pacs types (pacs.002, pacs.003, pacs.004 and pacs.007) and to safeguard the <Id> of camt.056 (see explanatory note on <Msgld> and <Id>).	Instructing agent	Interbank settlement date
Direct debit	pacs.003	CORE or B2B	Transaction ID	Creditor agent	Interbank settlement date
Reject/refusal	pacs.002	CORE or B2B	Status ID	Original debtor agent	Interbank Settlement Date ¹

¹ Submission of pacs.002: in the absence of the interbank settlement date at group header level, the interbank settlement date of the first payment at transaction level is used instead.

Payment cancellation request	camt.056	CORE or B2B	Cancellation ID	Original creditor agent	Interbank Settlement Date ²
Return/refund	pacs.004	CORE or B2B (only returns)	Return ID	Original debtor agent	Interbank settlement date
Reversal	pacs.007	Core or B2B	Reversal ID	Original creditor agent	Interbank settlement date

2.2 Duplication checks in other CSMs

The Bundesbank routes SEPA direct debits which cannot be processed in the SEPA-Clearer via other CSMs. To avoid rejections by other CSMs on account of other duplication checks, the references entered in the following message elements should be kept unambiguous for an extended period of time (at least three months) by, for example, applying a time stamp.

- Message identification (bulk level; pacs.002, pacs.003, pacs.004 and pacs.007)
- Identification (bulk level; camt.056)
- Transaction ID (individual transaction level; pacs.003)
- Return ID (individual transaction level; pacs.004)
- Status ID (individual transaction level; pacs.002)
- Cancellation ID (individual transaction level; camt.056)

The individual participant is responsible for any rejections by other CSMs owing to duplicate submissions arising from that participant's non-compliance with the rules for completing fields. Furthermore, that participant shall be liable for any resulting damages, breaches of return deadlines defined in the rulebooks etc.

² Submission of camt.056: in the absence of the interbank settlement date across the entire message, the interbank settlement date of the transaction level is used for duplication check.

3 Cross-referencing checks

3.1 Cross-referencing checks in the SEPA-Clearer

Rejections (pacs.002) and recalls (camt.056) are booked in the SEPA-Clearer on their interbank settlement date as part of the same settlement procedure used for the original direct debit (pacs.003) in the form of a counteracting booking on the participants' accounts in accordance with the gross coverage principle. To prevent such R-transactions from being booked without an underlying original direct debit, these messages will be rejected using the error code XT75 in cases where the original direct debit was not processed in the SEPA-Clearer or where an R-transaction was already submitted.

Assignment to the original direct debit occurs on the basis of the following fields:

O-Tx pacs.003	pacs.002	camt.056
GrpHdr / IntrBkSttlmDt	TxInfAnstSts / OrgnlTxRef / IntrBkSttlmDt	Undrlyg / TxInf / OrgnlIntrBkSttlmDt
DrctDbtTxInf / PmtTplnf/ LclInstrm / Cd	TxInfAnstSts / OrgnlTxRef / PmtTplnf / LclInstrm / Cd	Undrlyg / TxInf / OrgnlTxRef / PmtTplnf / LclInstrm / Cd
DrctDbtTxInf / CdtrAgt / FinInstnId / BIC or BICFI	TxInfAnstSts / OrgnlTxRef / CdtrAgt / FinInstnId / BIC or BICFI	TxInfAnstSts / OrgnlTxRef / CdtrAgt / FinInstnId / BIC or BICFI
DrctDbtTxInf / PmtId / TxId	TxInfAnstSts / OrgnlTxId	Undrlyg / TxInf / OrgnlTxId

Processing of post-settlement R-transactions (pacs.004 and pacs.007) is effected without any checking of the original transactions referenced in the payment messages.

3.2 Cross-referencing checks in other CSMs

The SEPA-Clearer delivers, among other things, R-transactions arriving from other CSMs to participants. Where applicable, other CSMs may subject these R-transactions to cross-referencing checks on the basis of the references entered in the individual message elements specified under "Duplication checks" and entries contained in other message elements of the original transaction (eg the original interbank settlement date or the original interbank settlement amount), the aim being to establish whether the original transaction was also settled using this other CSM. If it was not, for post-settlement R-transactions (pacs.004 and pacs.007) the <OrgnlMsgId> of the R-transaction is, where necessary, marked with a

“NOMATCH” identifier. The R-transactions are then allocated “UNMATCHED” (or a similar label) and forwarded.

In the case of submitted pre-settlement R-transactions (pacs.002 and camt.056) that are routed via other CSMs, transactions for which the outcome of the cross-referencing check is negative may result in the individual transaction being rejected by the other CSM.

With regard to the cross-referencing check conducted by EBA CLEARING, the latter only permits the submission of R-transactions during a specific period, which may vary depending on the message type and service. EBA CLEARING has published details about this in its “STEP2 Multi Purpose Direct Debits Core Service and B2B Service Functional Description” document (section 4.4.4).

Excerpt from the document (as at 27 November 2017):

Date validation	Data element validated	CORE	B2B
The latest date (number of TARGET days before D) on which a Request for Cancellation Request can be sent	Sending date	0	0
The latest date (number of TARGET days before D) on which a Refusal or Reject can be sent	Sending date	0	0
The latest date (number of TARGET days after D) on which a Reversal can be submitted by the Creditor Agent	Sending date	5	5
The latest date (number of TARGET days after D) on which a Return can be submitted by the Debtor Agent	Sending date	5	3
The latest date (number of TARGET days after D) on which a Request for Refund for an Authorized transaction can be submitted by the Debtor Agent	Sending date	47 ³	N/A
The latest date (number of calendar days after D) on which a Request for Refund for an Unauthorized transaction can be submitted by the Debtor Agent	Sending date	440 ⁴	N/A

Compliance with EBA CLEARING’s above deadlines is not checked by the SEPA-Clearer. Hence, non-compliance may result in these transactions being rejected by EBA CLEARING after R-transactions have been routed to EBA CLEARING.

³ STEP2 M-PEDD Core service will not reject a refund for an authorised transaction if it arrives after the defined timeline.

⁴ STEP2 will reject a refund for an unauthorised transaction if it arrives after the defined timeline.

4 Daily reconciliation report for direct debits (DRD)

Summary of the SDD bulks submitted to and delivered from the SEPA-Clearer, a copy of which is made available to each SEPA-Clearer participant in EBCDIC format every business day at the end of that day's SEPA-Clearer processing schedule. The DRD is not in XML format. A separate DRD (DRD Core or DRD B2B) is made available to the SEPA-Clearer participant for each SDD service (Core and B2B).

The DRD files delivered by the SEPA-Clearer in ASCII format using the EBICS communication infrastructure do not incorporate any special characters for the line feed at the end of the data record.

4.1 DRD header

Status	Field name	Format	Content	Item
M	Record type	4x	HDRD	0
M	Service identifier	3x	Core or B2B	4
M	File type	3x	DRD	7
M	Sending institution	4!a2!a2!c	SEPA-Clearer's BIC (in production mode: MARKDEFF; in test mode: MARKDEF0)	10
M	Sender's file reference	16!x	SEPA-Clearer's reference	18
M	Date and time	6!n6!n	YYMMDDHHMMSS	34
M	Test code	1x	Either "T" (test) or "P" (production), depending on the processing environment	46
M	Receiving institution	4!a2!a2!c3!c	Originator's BIC/clearing institution's BIC (<u>not</u> communication partner)	47
M	Business date clearer	6!n	SEPA-Clearer business day	58

4.2 DRD (pacs.003) direct debit bulks sent body

Submissions of original SEPA direct debits to the SEPA-Clearer by SEPA-Clearer participants

Status	Field name	Format	Content	Item
M	Record type	4x	DDSB	0
M	Bulk reference	35x	<MsgId> in group header	4
M	Number direct debits processed	8n	Number of processed transactions in a bulk	39
M	Number direct debits rejected	8n	Number of records rejected in a bulk	47
M	Value direct debits processed	18d	Total value of processed transactions in a bulk. If an entire bulk is rejected: 0.00	55
M	Value direct debits rejected	18d	Total value of records rejected in a bulk. If an entire bulk is rejected, total value of all transactions contained in the bulk	73
M	Processing cycle number	2n	<p>Processing cycle in SDD Core service</p> <ul style="list-style-type: none"> • A “90” denotes processing after the first submission window • A “91” denotes processing after the second submission window • A “96” denotes processing after the third submission window • A “99” denotes processing after the fourth submission window <p>Processing cycle in SDD B2B service</p> <ul style="list-style-type: none"> • A “90” denotes processing after the first submission window • A “91” denotes processing after the second submission window • A “92” denotes processing after the third submission window • A “95” denotes processing after the fourth submission window • A “99” denotes processing after the fifth submission window 	91

4.3 DRD (pacs.004) return/refund bulks sent body

Submissions of returns/refunds to the SEPA-Clearer by SEPA-Clearer participants

Status	Field name	Format	Content	Item
M	Record type	4x	DFSB	0
M	Bulk reference	35x	<MsgId> in group header	4
M	Number of returns/refunds processed	8n	Number of processed transactions in a bulk	39
M	Number of returns/refunds rejected	8n	Number of records rejected in a bulk	47
M	Value of returns/refunds processed	18d	Total value of processed transactions in a bulk. If an entire bulk is rejected: 0.00	55
M	Value of returns/refunds rejected	18d	Total value of records rejected in a bulk. If an entire bulk is rejected, total value of all transactions contained in the bulk	73
M	Processing cycle number	2n	<p>Processing cycle in SDD Core service</p> <ul style="list-style-type: none"> • A “90” denotes processing after the first submission window • A “91” denotes processing after the second submission window • A “99” denotes processing after the fourth submission window <p>Processing cycle in SDD B2B service</p> <ul style="list-style-type: none"> • A “90” denotes processing after the first submission window • A “91” denotes processing after the second submission window • A “92” denotes processing after the third submission window • A “99” denotes processing after the fifth submission window 	91

4.4 DRD (pacs.007) reversal bulks sent body

Submissions of reversals to the SEPA-Clearer by SEPA-Clearer participants

Status	Field name	Format	Content	Item
M	Record type	4x	DVSB	0
M	Bulk reference	35x	<MsgId> in group header	4
M	Number of reversals processed	8n	Number of processed transactions in a bulk	39
M	Number of reversals rejected	8n	Number of records rejected in a bulk	47
M	Value of reversals processed	18d	Total value of processed transactions in a bulk. If an entire bulk is rejected: 0.00	55
M	Value of reversals rejected	18d	Total value of records rejected in a bulk. If an entire bulk is rejected: total value of the bulk	73
M	Processing cycle number	2n	<p>Processing cycle in SDD Core service</p> <ul style="list-style-type: none"> • A “90” denotes processing after the first submission window • A “91” denotes processing after the second submission window • A “99” denotes processing after the fourth submission window <p>Processing cycle in SDD B2B service</p> <ul style="list-style-type: none"> • A “90” denotes processing after the first submission window • A “91” denotes processing after the second submission window • A “92” denotes processing after the third submission window • A “99” denotes processing after the fifth submission window 	91

4.5 DRD (pacs.002) reject bulks sent body

Submissions of rejections to the SEPA-Clearer by SEPA-Clearer participants

Status	Field name	Format	Content	Item
M	Record type	4x	DJSB	0
M	Bulk reference	35x	<MsgId> in group header	4
M	Number rejects processed	8n	Number of processed transactions in a bulk	39
M	Number rejects rejected	8n	Number of records rejected in a bulk	47
M	Value rejects processed	18d	Total value of processed transactions in a bulk. If an entire bulk is rejected: 0.00	55
M	Value rejects rejected	18d	Total value of records rejected in a bulk. If an entire bulk is rejected: total value of the bulk	73
M	Processing cycle number	2n	<p>Processing cycle in SDD Core service</p> <ul style="list-style-type: none"> • A “90” denotes processing after the first submission window • A “91” denotes processing after the second submission window • A “99” denotes processing after the fourth submission window <p>Processing cycle in SDD B2B service</p> <ul style="list-style-type: none"> • A “90” denotes processing after the first submission window • A “91” denotes processing after the second submission window • A “92” denotes processing after the third submission window • A “99” denotes processing after the fifth submission window 	91

4.6 DRD (camt.056) payment cancellation request bulks sent body

Submissions of payment cancellation requests (PCRs) to the SEPA-Clearer by SEPA-Clearer participants

Status	Field name	Format	Content	Item
M	Record type	4x	DCSB	0
M	Bulk reference	35x	<Id> belonging to assignment	4
M	Number PCRs processed	8n	Number of processed transactions in a bulk	39
M	Number PCRs rejected	8n	Number of records rejected in a bulk	47
M	Value PCRs processed	18d	Total value of processed transactions in a bulk. If an entire bulk is rejected: 0.00	55
M	Value PCRs rejected	18d	Total value of records rejected in a bulk. If an entire bulk is rejected: total value of the bulk	73
M	Processing cycle number	2n	<p>Processing cycle in SDD Core service</p> <ul style="list-style-type: none"> • A “90” denotes processing after the first submission window • A “91” denotes processing after the second submission window • A “99” denotes processing after the fourth submission window <p>Processing cycle in SDD B2B service</p> <ul style="list-style-type: none"> • A “90” denotes processing after the first submission window • A “91” denotes processing after the second submission window • A “92” denotes processing after the third submission window • A “99” denotes processing after the fifth submission window 	91

4.7 DRD (pacs.003) direct debit bulks received body

Deliveries of SEPA direct debits from the SEPA-Clearer to SEPA-Clearer participants

Status	Field name	Format	Content	Item
M	Record type	4x	DDRB	0
M	Bulk reference	35x	<MsgId> in group header	4
M	Number direct debits received	8n	Number of delivered transactions in a bulk	39
M	Value direct debits received	18d	Total value of delivered transactions in a bulk	47
M	Processing cycle number	2n	<p>Processing cycle in SDD Core service</p> <ul style="list-style-type: none"> • A “90” denotes deliveries from the first delivery window • A “91” denotes deliveries from the second delivery window • A “93” denotes deliveries from the third delivery window • A “96” denotes deliveries from the fourth delivery window • A “98” denotes deliveries from the fifth delivery window • A “99” denotes deliveries from the sixth delivery window <p>Processing cycle in SDD B2B service</p> <ul style="list-style-type: none"> • A “90” denotes deliveries from the first delivery window • A “91” denotes deliveries from the second delivery window • A “92” denotes deliveries from the third delivery window • A “93” denotes deliveries from the fourth delivery window • A “95” denotes deliveries from the fifth delivery window • A “97” denotes deliveries from the sixth delivery window • A “99” denotes deliveries from the seventh delivery window 	65

4.8 DRD (pacs.004) return bulks received body

Deliveries of returns from the SEPA-Clearer to SEPA-Clearer participants

Status	Field name	Format	Content	Item
M	Record type	4x	DFDB	0
M	Bulk reference	35x	<MsgId> in group header	4
M	Number returns received	8n	Number of delivered transactions in a bulk	39
M	Value returns received	18d	Total value of delivered transactions in a bulk	47
M	Processing cycle number	2n	<p>Processing cycle in SDD Core service</p> <ul style="list-style-type: none"> • A “90” denotes deliveries from the first delivery window • A “91” denotes deliveries from the second delivery window • A “93” denotes deliveries from the third delivery window • A “98” denotes deliveries from the fifth delivery window • A “99” denotes deliveries from the sixth delivery window <p>Processing cycle in SDD B2B service</p> <ul style="list-style-type: none"> • A “90” denotes deliveries from the first delivery window • A “91” denotes deliveries from the second delivery window • A “92” denotes deliveries from the third delivery window • A “93” denotes deliveries from the fourth delivery window • A “97” denotes deliveries from the sixth delivery window • A “99” denotes deliveries from the seventh delivery window 	65

4.9 DRD (pacs.007) reversal bulks received body

Deliveries of reversals from the SEPA-Clearer to SEPA-Clearer participants

Status	Field name	Format	Content	Item
M	Record type	4x	DVDB	0
M	Bulk reference	35x	<MsgId> in group header	4
M	Number of reversals received	8n	Number of delivered transactions in a bulk	39
M	Value of reversals received	18d	Total value of delivered transactions in a bulk	47
M	Processing cycle number	2n	<p>Processing cycle in SDD Core service</p> <ul style="list-style-type: none"> • A “90” denotes deliveries from the first delivery window • A “91” denotes deliveries from the second delivery window • A “93” denotes deliveries from the third delivery window • A “98” denotes deliveries from the fifth delivery window • A “99” denotes deliveries from the sixth delivery window <p>Processing cycle in SDD B2B service</p> <ul style="list-style-type: none"> • A “90” denotes deliveries from the first delivery window • A “91” denotes deliveries from the second delivery window • A “92” denotes deliveries from the third delivery window • A “93” denotes deliveries from the fourth delivery window • A “97” denotes deliveries from the sixth delivery window • A “99” denotes deliveries from the seventh delivery window 	65

4.10 DRD (pacs.002) reject bulks received body

Deliveries of rejections from the SEPA-Clearer to SEPA-Clearer participants

Status	Field name	Format	Content	Item
M	Record type	4x	"DJRB"	0
M	Bulk reference	35x	<MsgId> in group header	4
M	Number rejections received	8n	Number of delivered transactions in a bulk	39
M	Value rejects received	18d	Total value of delivered transactions in a bulk	47
M	Processing cycle number	2n	<p>Processing cycle in SDD Core service</p> <ul style="list-style-type: none"> • A "90" denotes deliveries from the first delivery window • A "91" denotes deliveries from the second delivery window • A "93" denotes deliveries from the third delivery window • A "98" denotes deliveries from the fifth delivery window • A "99" denotes deliveries from the sixth delivery window <p>Processing cycle in SDD B2B service</p> <ul style="list-style-type: none"> • A "90" denotes deliveries from the first delivery window • A "91" denotes deliveries from the second delivery window • A "92" denotes deliveries from the third delivery window • A "93" denotes deliveries from the fourth delivery window • A "97" denotes deliveries from the sixth delivery window • A "99" denotes deliveries from the seventh delivery window 	65

4.11 DRD (camt.056) payment cancellation request bulks received body

Deliveries of payment cancellation requests (PCRs) from the SEPA-Clearer to SEPA-Clearer participants

Status	Field name	Format	Content	Item
M	Record type	4x	DCRB	0
M	Bulk reference	35x	<Id> belonging to assignment	4
M	Number PCRs received	8n	Number of delivered transactions in a bulk	39
M	Value PCRs received	18d	Total value of delivered transactions in a bulk	47
M	Processing cycle number	2n	<p>Processing cycle in SDD Core service</p> <ul style="list-style-type: none"> • A “90” denotes deliveries from the first delivery window • A “91” denotes deliveries from the second delivery window • A “93” denotes deliveries from the third delivery window • A “98” denotes deliveries from the fifth delivery window • A “99” denotes deliveries from the sixth delivery window <p>Processing cycle in SDD B2B service</p> <ul style="list-style-type: none"> • A “90” denotes deliveries from the first delivery window • A “91” denotes deliveries from the second delivery window • A “92” denotes deliveries from the third delivery window • A “93” denotes deliveries from the fourth delivery window • A “97” denotes deliveries from the sixth delivery window • A “99” denotes deliveries from the seventh delivery window 	65

4.12 DRD trailer

Status	Field name	Format	Content	Item
M	Record type	4x	TDRD	0
M	Total number of records	6n	Number of DRD bodies	4

5 XML file header

5.1 Input debit file (IDF) header (BBkIDFBikDirDeb)

see annex 1

5.2 Debit validation file (DVF) header (BBkDVFBikDirDeb)

see annex 2

5.3 Debit notification file (DNF) header (BBkDNFBikDirDeb)

see annex 3

5.4 Settled debit file (SDF) header (BBkSDFBikDirDeb)

see annex 4

5.5 Unsettled debit file (UDF) header (BBkSDFBikDirDeb)

see annex 5

5.6 Result of settlement file (RSF) header (BBkRSFBikDirDeb)

see annex 6

6 XML interbank messages

6.1 SEPA direct debit – interbank direct debit

(pacs.003.001.02)

see annex 7

6.2 SEPA direct debit – interbank direct debit reject SCL

(pacs.002.001.03SCLSDD)

see annex 8

6.3 SEPA direct debit – interbank direct debit reject

(pacs.002.001.03SDD)

see annex 9

6.4 SEPA direct debit – interbank payment cancellation request

(camt.056.001.01SDD)

see annex 10

6.5 SEPA direct debit – interbank direct debit return/refund

(pacs.004.001.02SDD)

see annex 11

6.6 SEPA direct debit – interbank direct debit reversal

(pacs.007.001.02)

see annex 12

7 Use of the instructing agent/instructed agent

The following section provides an overview of how the *instructing agent*, the *instructed agent* and the *receiving institution* and *sending institution* are to be specified at the different message levels (file, bulk or individual transaction level). The “InstructedAgentRule” and the “InstructingAgentRule” must be observed in accordance with the ISO 20022 standard. The latter rule encompasses an exclusion principle, which clearly states that the *instructing agent* may be specified only in the group header or at individual transaction level. This principle also applies to the *instructed agent*.

The following information is **not** intended to depict all the data elements that can or must contain a BIC in a SEPA direct debit message but rather to identify the key actors involved in payment processing using the SEPA-Clearer.

Brief overview of key individual actors

Sending institution <SndgInst> in the file header: should contain the BIC of the file sender (communication partner).

A file delivered to the SEPA-Clearer may contain bulks from one or more *instructing agents*. The BIC of the *sending institution* can deviate from that of the *instructing agent* and need not be listed in the SCL Directory. This is, for example, the case for technical service providers who themselves are not participants in the SEPA-Clearer.

A file sent by the SEPA-Clearer contains exactly one bulk. “MARKDEFF” (in the test: “MARKDEF0”) is entered as the *sending institution*.

Receiving institution <RcvgInst> in the file header: should contain the BIC of the file recipient (communication partner).

A file sent by the SEPA-Clearer contains exactly one bulk for an *instructed agent*. The BIC of the *receiving institution* can deviate from that of the *instructed agent* and need not be listed in the SCL Directory. This is, for example, the case for technical service providers who themselves are not participants in the SEPA-Clearer.

In a file delivered to the SEPA-Clearer “MARKDEFF” (in the test: “MARKDEF0”) must be specified as the *receiving institution*.

Instructing agent <InstgAgt> in the group header:⁵ should contain the BIC of the submitter of a bulk submitted to the SEPA-Clearer. This BIC can, but need not necessarily, be listed in the SCL Directory. The countervalue of the submitted bulk is settled using the technical sub-account in TARGET specified by the submitter for the purpose of effecting financial settlement via the SEPA-Clearer during the corresponding SDD/SCC settlement cycle. The BIC of the *instructing agent* in the group header can deviate from that of the payment service provider at the individual transaction level.

⁵ In the case of submissions, this applies equally to the assigner behind the assignment of the message type camt.056.

In the files delivered by the SEPA-Clearer, the field *instructing agent* in the group header is left blank.

Instructed agent <InstdAgt> in the group header:⁶ In the files delivered by the SEPA-Clearer, the field *instructed agent* contains the BIC of the SEPA-Clearer participant whose technical sub-account in TARGET is used for the purpose of effecting financial settlement during the corresponding SDD/SCC settlement cycle. This BIC can, but need not necessarily, be listed in the SCL Directory. The BIC of the *instructed agent* can deviate from that of the *debtor/creditor agent* at the individual transaction level.

In the case of submissions to the SEPA-Clearer, this field must be left blank.

Instructing agent <InstgAgt> at the individual transaction level:⁷ should contain the BIC of the original submitter to the SEPA-Clearer of the bulk in which the transaction was contained. Upon delivery of the transaction, this BIC is entered at individual transaction level by the SEPA-Clearer and can, but need not necessarily, be listed in the SCL Directory. The BIC of the *instructing agent* can deviate from that of the *debtor/creditor agent* at the individual transaction level.

In the case of submissions to the SEPA-Clearer, this field must be left blank.

Instructed agent <InstdAgt> at the individual transaction level:⁸ this field is **not** supported at the individual transaction level, nor is it a component of the SEPA-Clearer schema files.

Debtor agent BIC <DbtrAgt> at the individual transaction level: should contain the BIC of the payer's payment service provider (debtor bank). It is essential that this BIC is listed in the SCL Directory as it is the key criterion for routing the payment in the SDD service.

Creditor agent BIC <CdtrAgt> at the individual transaction level: should contain the BIC of the payee's payment service provider (creditor bank). This BIC must be listed in the SCL Directory.

⁶ In the case of deliveries, this applies equally to the assignee in the assignment of the message type camt.056.

⁷ In the case of deliveries, this applies equally to the assigner at the individual transaction level of the message type camt.056.

⁸ In the case of deliveries, this applies equally to the assignee at the individual transaction level of the message type camt.056.

Sample entry for the maximum number of different BICs in an input debit file:

File header:

```
<?xml version="1.0" encoding="UTF-8"?>
<SCLSDD:BBkIDFBkDirDeb xmlns:SCLSDD="urn:BBkIDF:xsd:BBkIDFBkDirDeb"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="urn:BBkIDF:xsd:BBkIDFBkDirDeb BBkIDFBkDirDeb.xsd">
```

```
<SCLSDD:Sndglnst>AAAAD E A A X X X </SCLSDD:Sndglnst>
<SCLSDD:Rcvglnst>MARKDEF0</SCLSDD:Rcvglnst>
<SCLSDD:FileRef>2018062801020202</SCLSDD:FileRef>
<SCLSDD:Srcld>COR</SCLSDD:Srcld>
<SCLSDD:TstCode>T</SCLSDD:TstCode>
<SCLSDD:FType>IDF</SCLSDD:FType>
<SCLSDD:FDtTm>2018-06-28T09:14:24</SCLSDD:FDtTm>
<SCLSDD:NumDDBIk>1</SCLSDD:NumDDBIk>
<SCLSDD:NumPCRBk>0</SCLSDD:NumPCRBk>
<SCLSDD:NumREJBk>0</SCLSDD:NumREJBk>
<SCLSDD:NumRVSBk>0</SCLSDD:NumRVSBk>
<SCLSDD:NumRFRBk>0</SCLSDD:NumRFRBk>
```

BIC of a technical service provider who is not a participant in the SEPA-Clearer itself, but has been authorised to submit by an SCL participant.

Group header:

```
<SCLSDD:FIToFICstmrDrctDbt xmlns="urn:iso:std:iso:20022:tech:xsd:sdd:pacs.003.001.02">
  <GrpHdr>
    <Msgld>BBBBDEBBXX2018062801020202001</Msgld>
    <CreDtTm>2018-06-28T09:14:24</CreDtTm>
    <NbOfTx>00003</NbOfTx>
    <TtlIntrBkSttlmAmt Ccy="EUR">6.00</TtlIntrBkSttlmAmt>
    <IntrBkSttlmDt>2018-07-05</IntrBkSttlmDt>
    <SttlmInf>
      <SttlmMtd>CLRG</SttlmMtd>
      <ClrSys>
        <Prtry>SCL</Prtry>
      </ClrSys>
    </SttlmInf>
    <InstgAgt>
      <FinInstnId>
        <BIC>BBBBDEBBXX</BIC>
      </FinInstnId>
    </InstgAgt>
  </GrpHdr>
```

BIC of the SCL participant whose account will be used for settlement. This BIC can, but need not necessarily, be listed in the SCL Directory.

Individual transaction level:

```

<DrctDbtTxInf>
  <PmtId> ... </PmtId>
  <PmtTplnf> ... </PmtTplnf>
  <IntrBkSttlmAmt Ccy="EUR">1.00</IntrBkSttlmAmt>
  <ChrgBr>SLEV</ChrgBr>
  <ReqdColltnDt>2018-07-05</ReqdColltnDt>
  <DrctDbtTx> ... </DrctDbtTx>
  <Cdtr> ... </Cdtr>
  <CdtrAcct> ... </CdtrAcct>
  <CdtrAgt>
    <FinInstnld>
      | <BIC>CCCCDECCXX</BIC>
      </FinInstnld>
    </CdtrAgt>
  <Dbtr> ... </Dbtr>
  <DbtrAcct> ... </DbtrAcct>
  <DbtrAgt>
    <FinInstnld>
      | <BIC>DDDDDEDD</BIC>
      </FinInstnld>
    </DbtrAgt>
  </DrctDbtTxInf>

```

BIC of the payee's payment service provider (creditor bank). This BIC must be listed in the SCL Directory.

BIC of the payer's payment service provider (debtor bank). This BIC must be listed in the SCL Directory.

8 Error codes/rejection reason codes

Error codes used in connection with the structural check of an input debit file (IDF) by the SEPA-Clearer

The errors described below result in the entire file being rejected by means of DVF (exception: A01)

Error code	Nature of error
A01	IDF was partially rejected.
R02	The file name designation does not conform with the rules (code currently not in use).
R04	The sender's BIC in the file name does not conform with the rules (code currently not in use).
R07	SWIFTNet FileAct request type does not conform with the rules.
R09	IDF was completely rejected as it does not conform with the rules for other reasons (eg character set data deviate from UTF-8).
R10	IDF does not correspond to the schema and therefore cannot be processed.
R11	Sender's BIC (<SndgInst>) is incorrect.
R12	Recipient's BIC (<RcvgInst>) is incorrect.
R13	IDF is a duplicate.
R14	Error in test code (<TstCode>).
R18	Number of direct debit bulks contained in the IDF does not match the figure given in the file header.
R19	Number of PCR bulks contained in the IDF does not match the figure given in the file header.
R20	Number of return/refund bulks contained in the IDF does not match the figure given in the file header.
R21	Number of reject bulks contained in the IDF does not match the figure given in the file header.
R22	Number of reversal bulks contained in the IDF does not match the figure given in the file header.
S01	IDF rejected as maximum permissible number of bulks in a file was exceeded.

Error codes used in connection with the structural check of a bulk by the SEPA-Clearer

The errors described below result in the entire bulk being rejected by means of DVF (exception: B01).

Error code	Nature of error	Type	pac.002SCL
B01	Bulk was partially rejected.	PRTRY	X
B02	Maximum permissible number of transactions contained in a bulk was exceeded.	PRTRY	X
B03	Number of transactions contained in a bulk does not match the figure given in the group header.	PRTRY	X
B05	Total amount in the field <TtlIntrBkSttlmAmt>, <TtlRtrdIntrBkSttlmAmt> or <TtlRvsdIntrBkSttlmAmt> does not match the sum of the transactions in the bulk.	PRTRY	X
B09	Entire bulk was rejected as all transactions contained in it were rejected. The specific reasons for rejecting each transaction are stated accordingly.	PRTRY	X
B10	Entire bulk was rejected either because the instructing agent has to be included in the IDF group header or the specified instructing agent is not authorised to make submissions for the submitted payment type, or the sending institution specified in the file header is not authorised to make submissions for the instructing agent specified in the group header.	PRTRY	X
B11	Entire bulk was rejected as the instructed agent must not be included in the IDF group header.	PRTRY	X
B12	Entire bulk was rejected as the assigner was not authorised to make submissions or the assignee data were incorrect or the institution specified in the file header is not authorised to make submissions for the instructing agent specified in the group header.	PRTRY	X
B14	Entire bulk was rejected as the <Msgld> or <Id> appears in duplicate.	PRTRY	X
B15	Entire bulk was rejected as the date in the field <IntrBkSttlmDt> or <OrgnlIntrBkSttlmDt> falls outside the permitted time period.	PRTRY	X
B30	Entire bulk was rejected as submission with a message type for R-transactions took place between 10.00 and 15.00 (SDD Core service) and/or between 11.00 and 14.00 (SDD B2B service).	PRTRY	X
B40	Entire bulk was rejected as it contains more than 999 erroneous transactions. Specific reasons for rejection are only stated for the validated, erroneous individual transactions.	PRTRY	X
B97	Entire bulk (pac.002 or camt.056) was rejected as no clear <IntrBkSttlmDt> or <OrgnlIntrBkSttlmDt> could be identified.	PRTRY	X
B98	Entire bulk was rejected as the <Msgld> (GrpHdr) or <Id> (Assgnmt) does not conform with the	PRTRY	X

Error code	Nature of error	Type	pacs.002SCL
	format rules.		
B99	Bulk was rejected for other reasons.	PRTRY	X

Individual transaction-related error codes (SEPA-Clearer/SCL and other CSMs) or rejection codes (payment service providers/PSPs) specific to the individual transaction:

The message types for which the relevant error code can be used as a reason for an R-transaction or rejection are specified in the five columns furthest to the right.

Code	ISO 20022 designation	SEPA Core reason (pursuant to EPC Implementation Guidelines)	Nature of error	Initiator	Type	camt.056	pacs.002	pacs.007	pacs.004	pacs.002SCL
AC01	IncorrectAccountNumber	Account identifier incorrect (ie invalid IBAN or account number does not exist)	See description on left	PSPs/SCL	ISO		X		X	
AC04	ClosedAccountNumber	Account closed	See description on left	PSPs	ISO		X		X	
AC06	BlockedAccount	Account blocked Account blocked for direct debit by the debtor	See description on left	PSPs	ISO		X		X	
AC13	InvalidDebtorAccount Type	Debtor account is a consumer account	See description on left	PSPs	ISO		X		X	
AGNT	IncorrectAgent	Agent in the payment workflow is incorrect	See description on left	PSPs	ISO	X				
AG01	TransactionForbidden	Direct debit forbidden on this account for regulatory reason	See description on left	PSPs	ISO		X		X	
AG02	InvalidBankOperation Code	Operation code/transaction code/sequence type incorrect, invalid file format. Usage rule: To be used to indicate an incorrect 'operation code / transaction code / sequence type'.	See description on left	PSPs/SCL	ISO		X		X	
AM04	InsufficientFunds	Insufficient funds	See description on left	PSPs	ISO		X		X	X
AM05	Duplication	Duplicate collection/entry	See description on left	PSPs/SCL	ISO		X	X	X	X

Code	ISO 20022 designation	SEPA Core reason (pursuant to EPC Implementation Guidelines)	Nature of error	Initiator	Type	camt.056	pacs.002	pacs.007	pacs.004	pacs.002SCL
				/other CSMs						
BE05	UnrecognisedInitiating Party	Identifier of the creditor incorrect	Originator not known – creditor ID incorrect	PSPs	ISO		X		X	
CNOR	Creditor bank is not registered	Creditor bank is not registered under this BIC in the CSM	Payee's payment service provider is not registered under this BIC in the CSM	PSPs	ISO		X			
CURR	IncorrectCurrency	Currency of the payment is incorrect	Currency used for payment (= EUR) is incorrect	PSPs	ISO	X				
CUST	RequestedByCustomer	---	Recall by customer	PSPs	ISO	X				
CUTA	CancelUponUnableTo Apply	---	Recall owing to find request	PSPs	ISO	X				
DNOR	Debtor bank is not registered	Debtor bank is not registered under this BIC in the CSM	Payer's payment service provider is not registered under this BIC in the CSM	PSPs	ISO		X			
DUPL	DuplicatePayment	Payment is a duplicate of another payment	See description on left	PSPs	ISO	X				
DT01	InvalidDate		Date falls outside the time period permitted by other CSMs (see also item 2(2) on cross-referencing by other CSMs) or the SEPA-Clearer's time corridor.	SCL/other CSMs	ISO					X
ED05	SettlementFailed		Unsuccessful settlement (rejected by means of RSF)	PSPs/SCL /other CSMs	ISO		X			X

Code	ISO 20022 designation	SEPA Core reason (pursuant to EPC Implementation Guidelines)	Nature of error	Initiator	Type	camt.056	pacs.002	pacs.007	pacs.004	pacs.002SCL
FRAD	---	---	Payment effected fraudulently	PSPs	PRTRY	X				
MD01	NoMandate	No valid mandate	See description on left	PSPs	ISO		X		X	X
MD02	MissingMandatory InformationInMandate	Mandate missing or incorrect	See description on left	PSPs	ISO		X			X
MD06	RefundRequestedByEnd Customer	<u>Refund</u> : disputed authorised transaction	<u>Refund</u> : direct debit transaction disputed by the debtor	PSPs	ISO				X	
MD07	EndCustomerDeceased	Debtor deceased	See description on left	PSPs	ISO		X		X	
MS02	NotSpecifiedReason CustomerGenerated	Refusal by the debtor	Debtor initiates a rejection	PSPs	ISO		X	X	X	
MS03	NotSpecifiedReason AgentGenerated	Reason not specified	Reason for return not specified by payment service provider	PSPs/other CSMs	ISO		X	X	X	X
PY01	---	---	The transaction cannot be processed as the payer's and/or the payee's payment service provider is/are not registered as a direct or indirect participant in the STEP2 SDD service	SCL	PRTRY					X
RC01	BankIdentifierIncorrect	Bank identifier incorrect (ie invalid BIC)	See description on left	PSPs	ISO		X		X	
RR01	MissingDebtorAccount OrIdentification	Regulatory reason	See description on left	PSPs	ISO		X		X	
RR02	MissingDebtorNameOr Address	Regulatory reason	See description on left	PSPs	ISO		X		X	

Code	ISO 20022 designation	SEPA Core reason (pursuant to EPC Implementation Guidelines)	Nature of error	Initiator	Type	camt.056	pacs.002	pacs.007	pacs.004	pacs.002SCL
RR03	MissingCreditorNameOr Address	Regulatory reason	See description on left	PSPs	ISO		X		X	
RR04	Regulatory reason	Regulatory reason	See description on left	PSPs	ISO		X		X	
SL01	DueToSpecificServices OfferedByDebtorAgent	Specific service offered by the debtor bank	Reason for return: designated service offered by the debtor bank whereby all direct debits that are not expressly authorised by customers are returned	PSPs	ISO		X		X	
TECH	---	---	Payment effected erroneously due to technical problems	PSPs	PRTRY	X				
UPAY	UnduePayment	---	Unauthorised payment	PSPs	ISO	X				
XD19	---	---	Issued if the country code is a valid ISO or SEPA country code but the (country-specific) structure of the IBAN or the check digits is incorrect. The field with the invalid IBAN is specified in the field "StsRsn".	SCL	PRTRY					X
XT13	---	---	The transaction contains at least one field which is not supported. At least one mandatory field is missing from the transaction. The invalid XML field is indicated by the error code (if a code exists).	SCL	PRTRY					X

Code	ISO 20022 designation	SEPA Core reason (pursuant to EPC Implementation Guidelines)	Nature of error	Initiator	Type	camt.056	pacs.002	pacs.007	pacs.004	pacs.002SCL
XT27	---	---	The transaction contains at least one element with a BIC not listed in the SCL Directory	SCL	PRTRY					X
XT33	---	---	The content of at least one XML element is not in the format required. The invalid XML field is indicated by the error code.	SCL	PRTRY					X
XT43	---	---	Type of direct debit (Core/B2B) differs from the entry in the <SrvclId> in the file header	SCL	PRTRY					X
XT53	---	---	Verification of the creditor identifier (<CdtrSchmld><Id>) regarding structure/check digits failed	SCL	PRTRY					X
XT73	---	---	The two characters forming the country code do not constitute a valid ISO or SEPA country code	SCL	PRTRY					X
XT74	---	---	Invalid underlying original transaction Further check required	Other CSMs	PRTRY					X
XT75	---	---	Invalid status of underlying original transaction from R-message No further action required	SCL/other CSMs	PRTRY					X
XT76	---	---	Invalid error code (in return/refund)	SCL	PRTRY					X

Code	ISO 20022 designation	SEPA Core reason (pursuant to EPC Implementation Guidelines)	Nature of error	Initiator	Type	camt.056	pacs.002	pacs.007	pacs.004	pacs.002SCL
XT77	---	---	The originally instructed amount <OrgnlIntrBkSttlmAmt> was not found or does not match the original transaction amount	Other CSMs	PRTRY					X
XT78	---	---	pacs.004.001.01: The amount entered in <OrgnlIntrBkSttlmAmt> plus <CompstnAmt> plus <ChrgsInf> <Amt> must add up to <RtrdIntrBkSttlmAmt> if <CompstnAmt> and/or <ChrgsInf><Amt> exist(s).	SCL/other CSMsr	PRTRY					X
XT79	---	---	The <DbtrAgt> is not permitted to receive direct debits. A direct participant must be permitted to receive direct debits from the clearing system.	Other CSMs	PRTRY					X
XT80	---	---	The <CdrAgt> is not permitted to send direct debits. An indirect participant must be enabled to send direct debits to the clearing system.	Other CSMs	PRTRY					X
XT99	---	---	Direct debit rejected for other reasons (code currently not in use)	SCL	PRTRY					X

9 Character set

The SEPA-Clearer supports the full UTF-8 character set.

Pursuant to the SEPA rulebooks, PSPs must be able to support the following Latin character set commonly used in international communication.

a b c d e f g h i j k l m n o p q r s t u v w x y z
A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
0 1 2 3 4 5 6 7 8 9
/ - ? : () . ' ' +
Space

However, it can be agreed on a bilateral or multilateral basis to support one or more UTF-8 character sets in addition to the Latin character set (eg the Greek character set). This applies above all to message elements containing the purpose of payment, name and address of the payer (creditor) and payee (debtor). Unless prevented by the schema parameters, the SEPA-Clearer therefore delivers data records featuring UTF-8 characters not contained in the Latin character set to the recipient in unchanged format.

Checks by the SEPA-Clearer

(1) When files are submitted (IDFs), the SEPA-Clearer checks whether their prologue contains the following information in line with the usage rules applying to the UTF-8 character set.

```
<?xml version="1.0" encoding="UTF-8"?>
```

If any other character set is entered, the entire file is rejected using the error code R09.

(2) No character set checks beyond those covering compliance with the UTF-8 character set are carried out by the SEPA-Clearer.

10 Notes on format/status

10.1 Explanatory notes on the format of XML file headers and daily reconciliation reports

Format	Description
a	Alpha, capital letters
c	Alphanumeric, letters: capital letters
d	Decimal including decimal point and two decimal places
n	Numeric
x	Characters in accordance with Latin character set, in some cases restricted by XSD schema file (see also section entitled "Character set")
3!a	Precisely three alphanumeric characters
ISODate	YYYY-MM-DD
ISODateTime	YYYY-MM-DDThh:mm:ss
Status	
M	Mandatory field
O	Optional field

10.2 Completing amount fields in line with the schema

Sample entry		Processing in the SEPA-Clearer
996.5	One decimal place	996.50
997.	No decimal places	997.00
998	No decimal point and no decimal places	998.00

Submitted files containing amounts with a comma and/or more than two decimal places do not conform to the schema and are therefore rejected using error code R10. Amounts at the individual transaction level may not be smaller than €0.01 and must not exceed €999999999.99.

10.3 Use of filling characters in the amount fields

The XML parser accepts characters that function as "fillers" in an XML context. These may be entered in the amount fields in an XML environment, however their use may result in processing problems for the receiving/processing institution. We therefore advise against using such filling characters.

The fillers listed below are recognised by the XML parser and routed/processed as follows by the SCL.

1. Leading zeros before the decimal point⁹

The SEPA-Clearer ignores the redundant zeros and delivers the amount with the first and the last significant characters to the SCL participant.

Example:

Submission to the SCL:

```
<IntrBkSttlmAmt Ccy="EUR">0000000000000001.01</IntrBkSttlmAmt>
```

Delivery by the SCL:

```
<IntrBkSttlmAmt Ccy="EUR">1.01</IntrBkSttlmAmt>
```

2. Spaces in the amount field

The SEPA-Clearer ignores the redundant spaces and delivers the amount with the first and the last significant characters to the SCL participant.

Example:

Submission to the SCL:

```
<IntrBkSttlmAmt Ccy="EUR">                2.02                </IntrBkSttlmAmt>
```

Delivery by the SCL:

```
<IntrBkSttlmAmt Ccy="EUR">2.02</IntrBkSttlmAmt>
```

10.4 Use of white spaces in XML fields, in this case the “collapsing” procedure

“White spaces” form part of the standard XML environment. They are also permitted for the decimal data type, which is set as standard for the amount field.

Neither the ISO 20022 standard nor the EPC’s Implementation Guidelines make provisions for any restrictions to this arrangement. As a rule, white spaces can be processed by XML parsers. However, problems can occur, eg when customised solutions have been programmed or the XML data records have been converted to different formats for further processing.

We therefore advise against using spaces in the tags as this may result in processing problems for the receiving/processing institution.

CSMs have stipulated the following format rules for a variety of “string”-derived fields in their schema files. In the description, the white spaces facet was set to “collapse” in the schema files. Detailed information on the procedure used in XML parsing can be found in the document “W3C Recommendation 28 October 2004, XML Schema Part 2: Datatypes Second Edition”, the contents of which can be called up using the internet link provided below.

<http://www.w3.org/TR/xmlschema-2/#rf-whiteSpace>

⁹ The schema validation excludes zeros after the second decimal place.

For reasons of interoperability, this “collapsing” procedure was integrated into the SEPA-Clearer’s schema files with the same level of effect, meaning that, overall, and wherever necessary both submissions to and deliveries from the SEPA-Clearer undergo the above procedure as part of the XML parsing process.

10.5 Namespace declaration

Message instances (ie messages exchanged between PSPs and the SEPA-Clearer) must contain the name space declaration at bulk level. This declaration thereafter applies to all tags contained in the message; individual tags therefore need not be identified with the prefix “sw”. SCL participants must take care to adhere to the stipulated entries/declaration.

SCL delivery messages to PSPs are likewise sent without a prefix at “tag level”.

Sample message instance:

```
<SCLSDD:pacs.003.001.02 xmlns="urn:iso:std:iso:20022:tech:xsd:sdd:pacs.003.001.02">  
  <GrpHdr>  
    <MsgId>BBBBBBBB20080104-123456</MsgId>
```

11 Compression procedures

11.1 FileAct¹⁰

Files may be transmitted in either direction in compressed or uncompressed format as desired by the customer. To this end, the following compression procedures may be used.

- FLAM¹¹ (which uses the ADC compression mode as it offers the highest compression factor)
- ZIP
- GZIP

11.2 EBICS¹²

In EBICS, the ZIP compression procedure must be supported when transmitting files in either direction.

12 General specifications of message elements

Creditor identifier (AT-02/AT-18)

The SEPA direct debit mandate features a creditor identifier which clearly identifies the creditor without making any reference to an account. This information must be specified in the SEPA data record when collecting a SEPA direct debit.

¹⁰ See the procedural rules on communication via SWIFTNet FileAct for the Deutsche Bundesbank’s Retail Payment System (RPS) and the RPS SEPA-Clearer (SCL).

¹¹ FLAM (Frankenstein-Limes-Access-Method) is a registered trademark of limes datentechnik gmbh, Bad Homburg, Germany.

¹² See the Deutsche Bundesbank’s procedural rules on communication via EBICS with deposit-taking credit institutions and other account holders with a bank sort code.

Together with the mandate reference number assigned by the direct debit creditor, this creditor identifier is forwarded in the SEPA data record all the way along the chain of payment processes to the payer. This identification must remain unambiguous and consistent over time in order to allow the payer and the payer's PSP to check a mandate when direct debit collection occurs. In Germany, creditor identifiers are allocated by the Deutsche Bundesbank at www.bundesbank.de.

The creditor identifier is structured as specified in the EPC Implementation Guidelines under AT-02. The creditor identifier is case and space insensitive.

Format rules

- Positions 1 and 2 contain the ISO country code.
- Positions 3 and 4 contain the check digits.
- Positions 5 to 7 contain the creditor business code which the creditor can complete with any characters it sees fit. Spaces are prohibited, however. The default characters entered for the creditor business code are "ZZZ".
- Positions 8 to 35 contain the country-specific element.
- **Note:** the following preparatory steps are required in order to calculate the check digits:
 - Preceding spaces are not taken into account.
 - Positions 1 to 7 may not contain any spaces.

Hence, the following entries are prohibited and would result in the transactions being rejected using the error code XT53.

```
<Id> DE98Zz Z09999999999 </Id>
<Id> DE98Z zZ099999999999 </Id>
<Id> DE98 ZzZ0999999999999 </Id>
<Id> DE9 8ZzZ0999999999999 </Id>
<Id> DE 98ZzZ0999999999999 </Id>
<Id> D E98ZzZ0999999999999 </Id>
```

The following entry would be permissible, however.

```
<Id> DE98ZzZ 099999999999 </Id>
```

Positions 5 to 7 are not included.

- All non-alphanumeric characters must be deleted from the country-specific element (positions 8 to 35).
- The ISO country code and "00" must be added at the right-hand end.
- Letters should be converted into figures as shown in the table below.

A = 10	G = 16	M = 22	S = 28	Y = 34
B = 11	H = 17	N = 23	T = 29	Z = 35
C = 12	I = 18	O = 24	U = 30	
D = 13	J = 19	P = 25	V = 31	
E = 14	K = 20	Q = 26	W = 32	
F = 15	L = 21	R = 27	X = 33	

- The check digit procedure MOD 97-10 should be used to calculate the check digit (see also ISO 7064).

13 TARGET referencing

TARGET issues settlement information (camt.054) and electronic account statements (camt.053) for all accounts held under its auspices. The aforementioned message types contain settlement references which serve to identify the SEPA direct debits that are exchanged with the SEPA-Clearer. The BIC of the SEPA Clearer "MARKDEFFSCL" is shown in the element <DbtrAgt> under <TxDtIs> <RltdAgt>.

1 Liquidity transfer automatically generated by the SEPA-Clearer from the RTGS DCA to the relevant sub-account in the amount of the settlement sum total of submitted or delivered SEPA direct debit and SCC collections resulting in debit entries

Structure of the reference in the <EndtoEndId> of the camt-message under <TxDtIs><Refs>:

SCL	Format	Content
System	1-character, alphanumeric	"S" (SCL)
AS action	2-character, alphanumeric	"C" + No of cycles
Date	2-character, numeric	"TT" (processing day)
Constant	2-character, numeric	"00"
Serial number	9-character, numeric	Unambiguous serial number within the preceding reference information

In addition, the following information is provided in the unstructured remittance information (element <RmtInf><Ustrd> under <TxDtIs>) of the camt.054:

SCL	Format	Content
<u>Liquidity transfer</u>	3-character, constant	"CUO"
Processing cycle	2-character, numeric	Phase 90 to 99
Settlement cycle	2-character, alphabetical	First character: "I", "O" or "X" I = Input (settlement of bulks submitted to the SCL) O = Output (settlement of bulks delivered from the SCL) X = Error (settlement of rejected transactions) Second character: A, B or C ¹³ A = SCT service B = SDD service C = SCC service

Furthermore, the code "LIAS" (Immediate LT – intra-service AS on behalf) in the element <LclInstrm><Prtry> indicates that this is a liquidity transfer initiated by the ancillary system.

¹³ If a Liquidity transfer Order refers to settlements from multiple services, only one character is given (depending on the order in which bulks that are to be settled are processed).

2 Settlement of submitted and delivered SDD bulks on the sub-account during the relevant SDD/SCC settlement cycles of a settlement procedure

Structure of the reference in the <EndtoEndId> of the camt-message under <TxDtIs><Refs>:

SCL	Format	Content
System	1-character, alphanumeric	"S" (SEPA-Clearer)
AS action	2-character, alphabetical	<p>First character: "I", "O" or "X"</p> <p>I = Input (settlement of bulks submitted to the SCL)</p> <p>O = Output (settlement of bulks delivered from the SCL)</p> <p>X = Error (settlement of rejected transactions)</p> <p>Second character: A, B or C</p> <p>A = SCT service</p> <p>B = SDD service</p> <p>C = SCC service</p>
Current date	2-character, numeric	Day of the current month
File ID	6-character, numeric	Internal file ID
Bulk ID	3-character, numeric	Bulk within the file
Serial number	2-character, numeric	Serial number

In addition, the following information is provided in the unstructured remittance information (element <RmtInf><Ustrd> under <TxDtIs>) of the camt.054:

SCL	Format	Content
Bulk ID	35-character, alphanumeric	Message identification (<MsgID>) in group header or identification (<Id>) belonging to the assignment of the settled SDD bulk
Settlement date	6-character, numeric	DDMMYY
Instructing or instructed agent	11-character, alphanumeric	<p>From the group header or assignment of the booked SDD bulk</p> <p>Submitted bulks: instructing agent or assigner</p> <p>Delivered bulks: instructed agent or assignee</p>
Indicates a partial settlement within a bulk	1-character, alphabetical	<p>F (= Full)</p> <p>P (= partial settlement)</p>

Furthermore, the code "ASTI" (AS Transfer) in the element <LclInstrm><Prtry> indicates that this is a settlement initiated by the ancillary system.

3 Return transfer of entire funds from the sub-account to the corresponding RTGS DCA after completion of all settlements in a settlement procedure (SCT and SDD/SCC settlement cycles) automatically initiated by the SEPA-Clearer

When retransferring the (entire amount of) liquidity from the sub-account to the RTGS DCA, references are likewise assigned (provided in the <EndtoEndId> of the camt-messages under <TxDtIs><Refs>). This is an internal reference that always starts with the constant "SCP". Together with the BIC of the SEPA Clearer and the entry "LIIA" in the element <LclInstrm><Prtry>, the debits on the sub-account or the credits on the RTGS DCA can be unambiguously assigned to this business case.

14 Automated e-mail notification

14.1 Repeated settlement attempts

The account holders involved will be informed via automated e-mail notification about repeated settlement attempts. The account holder on the debit side will be asked to promptly arrange for sufficient funds on its account, while the account holder on the credit side will be alerted to the delayed settlement.

It is mandatory for direct participants to register the relevant contact details. These will be used in both instances.

Up to five different sets of contact details can be provided. To prevent instances where contact persons are absent or out of the office, or have left your institution altogether, we advise participants to register functional e-mail addresses.

14.1.1 Debit side

Notifications will be sent from the e-mail address “EMZ-Disposition@bundesbank.de”.

The subject line of these e-mails clearly identifies the service or scheme in question and the matter in hand.

“SCL Fehlende Deckung / Insufficient funds [BIC]”

The notification comprises a standardised e-mail message.

“Sehr geehrte Damen und Herren, /Dear Sir or Madam

auf Ihrem PM-Konto konnten SEPA-Clearer-Zahlungen in Höhe von EUR [...] nicht belastet werden. Bitte sorgen Sie bis [...] Uhr für ausreichende Liquidität.

SCL payments amounting to EUR [...] could not be debited to your PM account. Please ensure that sufficient liquidity is available by [...] Central European Time.

Mit freundlichen Grüßen / Yours sincerely

DEUTSCHE BUNDESBANK”

14.1.2 Credit side

Notifications will be sent from the e-mail address “EMZ-Disposition@bundesbank.de”.

The subject line of these e-mails clearly identifies the service or scheme in question and the matter in hand: “SCL Settlement Verzögerung / Delay [BIC]”

The information comprises a standardised message.

“Sehr geehrte Damen und Herren, /Dear Sir or Madam

Bitte beachten Sie, dass einzelne Gutschriften aus dem SEPA-Clearer nicht durchgeführt werden konnten. Eine Wiederholung des Buchungsversuchs erfolgt in Kürze.

Please note that a number of credit positions from the SEPA-Clearer could not be settled. The booking attempt will be repeated shortly.

Mit freundlichen Grüßen / Yours sincerely

DEUTSCHE BUNDESBANK”

14.2 Advance information

Advance information will automatically be sent out roughly 20 minutes before operations are booked. It is mandatory for direct participants to register the relevant contact details. Up to five different sets of contact details can be provided.

The advance information states the total funds needed to cover upcoming debit bookings on the delivery side, ie for original direct debits (pacs.003) and R-transactions (pacs.002, pacs.004) to be delivered. Any incoming liquidity or debit amounts on the submission side will not be shown in the advance information.

Notifications will be sent from the e-mail address “EMZ-Disposition@bundesbank.de”.

The subject line of these mails clearly identifies the service or scheme in question and the matter in hand.

“SCL Vorabinformation/Settlement notification [BIC]”

The advance information comprises a standardised e-mail message and a PDF attachment.

Message

“Sehr geehrte Damen und Herren, /Dear Sir or Madam

anbei senden wir Ihnen die Vorabinformation zu dem um ca. [...] Uhr anstehenden Buchungsgeschäft des SEPA-Clearers.

Please find attached advance information on the upcoming booking operations of the SEPA-Clearer at around [...] Central European Time.

Mit freundlichen Grüßen / Yours sincerely

DEUTSCHE BUNDESBANK”

The following pages show the structure of the attachment.

The file name of the attachment is structured as follows:

“SCL_Vorabinfo_Settlement_notice_[BIC].PDF”

Vorabinformation aus dem SEPA-Clearer der Deutschen Bundesbank - EMZ-Betrieb
Advance information from the SEPA-Clearer of the Deutsche Bundesbank - RPS Operations
Nächster Buchungszeitpunkt / Next booking time: 08:30

Instrd Agt	MsgId	BulkId int.	SVC	PACS	Amount Bulk in EUR	
AAADEAAXXX	12345678901234567890123456789012345	12345678901234567	COR	003	111,11	
AAADEAAXXX	12345678901234567890123456789012345	12345678901234567	B2B	002	111,11	
AAADEAAXXX	12345678901234567890123456789012345	12345678901234567	SCC	004	111,11	
						333,33
DEBIT SUBACC	DEMARKSAAADEAAXXXEMZD10123456789	TOTAL AMOUNT EUR				333,33
BBBDEAAXXX	12345678901234567890123456789012345	12345678901234567	COR	002	222,22	
BBBDEAAXXX	12345678901234567890123456789012345	12345678901234567	B2B	004	222,22	
BBBDEAAXXX	12345678901234567890123456789012345	12345678901234567	SCC	003	222,22	
						666,66
CCCCDEAAXXX	12345678901234567890123456789012345	12345678901234567	COR	002	444,44	
CCCCDEAAXXX	12345678901234567890123456789012345	12345678901234567	B2B	004	444,44	
CCCCDEAAXXX	12345678901234567890123456789012345	12345678901234567	SCC	003	444,44	
						1.333,32
DEBIT SUBACC	DEMARKSAAADEAAXXXEMZD201234567890	TOTAL AMOUNT EUR				1.999,98
BIC SETTLEMENT AGENT	ZAHLSTELLE AAADEAAXXX	PM ACCOUNT	TOTAL AMOUNT EUR			2.333,31

F o r t s e t z u n g nächste Seite oder E N D E D E R A U S G A B E
C o n t i n u e d on next page or E N D O F O U T P U T

XML-File-Header

Input Debit File (IDF) Header

Verwendung

- Einlieferung von pacs.003-, pacs.002-, pacs.004-, pacs.007- und camt.056-Bulks in den SEPA-Clearer
- Parsing-Fehler führen zur File-Rückweisung mit dem Fehlercode R10
- Die Schemadatei „BBkIDFBkDirDeb“ spezifiziert den IDF

Use

- File header for the submission of pacs.003, pacs.002, pacs.007, pacs.004 and camt.056 bulks to the SEPA-Clearer.
- Parsing errors result in the file being rejected with the error code R10.
- The schema file BBkIDFBkDirDeb specifies the IDF.

Nachrichtenstruktur / Message structure

Status	Element/Attribute	Format	Inhalte und Prüfung	Contents and Checks
	BBkIDFBikDirDeb			
	BBkIDFBikDirDeb			
1..1	Sndglnst BBkIDFBikDirDeb +Sndglnst	Name Typ Pattern Sending Institution sw6:BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}	11-stelliger BIC des Senders (Kommunikationspartner) Prüfung, ob der BIC im Feld Sending Institution dem BIC entspricht, der bei der Übertragung des Files genutzt wurde: R11 Bestandteil der Doppelseinreichungsprüfung Fehlercode: R13	Sender's 11-digit BIC (communication partner) Check as to whether this element is equal to the BIC used for submission.: R11 Part of the duplication check error code: R13
1..1	Rcvglnst BBkIDFBikDirDeb +Rcvglnst	Name Typ Receiving Institution BBkIDF:RcvgBICIdentifier	BIC des SEPA-Clearers (Produktion MARKDEFF; Test MARKDEF0) Prüfung, ob das Element mit dem BIC des SEPA-Clearers belegt ist. Fehlercode: R12	SEPA-Clearer's BIC (production: MARKDEFF; test: MARKDEF0) Check as to whether this element is allocated with the BIC of the SEPA-Clearer error code: R12
Anwendbare Codes / Acceptable Codes				
MARKDEF0 MARKDEFF				
1..1	FileRef BBkIDFBikDirDeb +FileRef	Name Typ Pattern File Reference BBkIDF:Max16Text [0-9A-Z]{16,16}	Referenz des Senders muss geschäftstägig eindeutig sein Bestandteil der Doppelseinreichungsprüfung Fehlercode: R13	Sender's reference, must be unique on operating day Part of the duplication check error code: R13
1..1	SrvclD BBkIDFBikDirDeb +SrvclD	Name Typ Service Identifier BBkIDF:SrvclD	COR oder B2B Nur die Verwendung von "COR" oder "B2B" ist zulässig. (Schemavalidierung)	COR or B2B Only COR or B2B can be used (schema validation)
Anwendbare Codes / Acceptable Codes				
B2B COR				
1..1	TstCode BBkIDFBikDirDeb +TstCode	Name Typ Test Code BBkIDF:TestCodeType	Entweder Wert "T" (Test) oder Wert "P" (Produktion), abhängig von der Verarbeitungsumgebung Fehlercode: R14	Either "T" (test) or "P" (production), depending on the processing environment error code: R14

Status	Element/Attribute	Format	Inhalte und Prüfung	Contents and Checks
		Anwendbare Codes / Acceptable Codes		
		P		
		T		
1..1	FType BBkIDFBkDirDeb +FType	Name File Type Typ BBkIDF:FType	IDF	IDF
		Anwendbare Codes / Acceptable Codes		
		IDF		
1..1	FDtTm BBkIDFBkDirDeb +FDtTm	Name File Date and Time Typ sw3:ISODatetime Pattern [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}[T][0-9]{2,2}: [0-9]{2,2};[0-9]{2,2}[S]*	Erstellungsdatum und –zeit	File creation date and time
1..1	NumDDBIk BBkIDFBkDirDeb +NumDDBIk	Name Total Number of pacs.003 Bulks Typ BBkIDF:Max8NumericText Pattern [0-9]{1,8}	Gesamtanzahl der Direct Debit Bulks im IDF Number of bulks contained in the file is not consistent with the number given. error code: R18 Maximum of 999 bulks per file is permitted error code: S01	Total number of direct debit bulks in IDF Number of bulks contained in the file is not consistent with the number given. error code: R18 Maximum of 999 bulks per file is permitted error code: S01
1..1	NumPCRBk BBkIDFBkDirDeb +NumPCRBk	Name Total Number of camt.056 Payment Cancellation Request-Bulks Typ BBkIDF:Max8NumericText Pattern [0-9]{1,8}	Gesamtanzahl der Direct Debit Bulks im IDF Anzahl der Bulks innerhalb des Files stimmt nicht mit angegebenem Wert überein. Fehlercode: R19 Max. 999 Bulks im File zulässig Fehlercode: S01	Total number of payment cancellation request bulks in IDF Number of bulks contained in the file is not consistent with the number given. error code: R19 Maximum of 999 bulks per file is permitted error code: S01
1..1	NumREJBk BBkIDFBkDirDeb +NumREJBk	Name Total Number of pacs.002 Rejects Bulks Typ BBkIDF:Max8NumericText Pattern [0-9]{1,8}	Gesamtanzahl der Reject Bulks (einschl. Refusal) im IDF Anzahl der Bulks innerhalb des Files stimmt nicht mit angegebenem Wert überein. Fehlercode: R21	Total number of reject bulks (including refusals) in IDF Number of bulks contained in the file is not consistent with the number given. error code: R21

Status	Element/Attribute	Format	Inhalte und Prüfung	Contents and Checks	
1..1	NumRVSBIk BBkIDFBkDirDeb +NumRVSBIk	Name	Total Number of pacs.007 Reversals Bulks	Max. 999 Bulks im File zulässig Fehlercode: S01 Gesamtanzahl der Reversal Bulks im IDF	Maximum of 999 bulks per file is permitted error code: S01 Total number of reversal bulks in IDF.
		Typ Pattern	BBkIDF:Max8NumericText [0-9]{1,8}	Anzahl der Bulks innerhalb des Files stimmt nicht mit angegebenem Wert überein. Fehlercode: R22	Number of bulks contained in the file is not consistent with the number given. error code: R22
1..1	NumRFRBIk BBkIDFBkDirDeb +NumRFRBIk	Name	Total Number of pacs.004 Returns/Refunds Bulks	Max. 999 Bulks im File zulässig Fehlercode: S01 Gesamtanzahl der Return / Refund Bulks im IDF	Maximum of 999 bulks per file is permitted error code: R22 Total number of return/refund bulks in IDF.
		Typ Pattern	BBkIDF:Max8NumericText [0-9]{1,8}	Anzahl der Bulks innerhalb des Files stimmt nicht mit angegebenem Wert überein. Fehlercode: R20 Max. 999 Bulks im File zulässig Fehlercode: S01	Number of bulks contained in the file is not consistent with the number given. Error code: R20 Maximum of 999 bulks per file is permitted error code: S01

XML-File-Header

Debit Validation File (DVF) Header

Verwendung

- File-, Bulk- und Einzeltransaktionsrückweisungen von SDD-Files durch den SEPA-Clearer
 - Parsing-Fehler führen zur kompletten Rückweisung des eingereichten IDF (File-Rückweisung) mit dem Fehlercode R10, dieser wird im Element *IDF Error Code* (<IdfErrCd>) des DVF Headers eingestellt
 - Bei Bulk- und Einzeltransaktionsrückweisungen wird der pacs.002.001.03SCLSDD zusätzlich dem DVF Header beigefügt
- Der DVF Header wird sowohl für technische und fachliche Fehler als auch für fehlende Deckung verwendet
- Die Schemadatei „BBkDVFBkDirDeb“ spezifiziert den DVF

Use

- File header for file, bulk and individual transaction rejections of SDD files by the SEPA-Clearer.
 - Parsing errors result in a complete reject of the submitted IDF with the error code R10; this is entered into the element IDF error code (<IdfErrCd>) of the DVF header.
 - For individual transaction and bulk rejects, the pacs.002.001.03SCLSDD is added to the DVF header.
- The DVF header is used for both technical and functional errors.
- The schema file BBkIDFBkDirDeb specifies the DVF.

Nachrichtenstruktur / Message structure

Status	Element/Attribute	Format	Inhalte und Prüfung	Contents and Checks
	BBkDVFBkDirDeb			
	BBkDVFBkDirDeb			
1..1	Sndglnst BBkDVFBkDirDeb +Sndglnst	Name Sending Institution Typ BBkDVF:BIcIdentifierBBK	BIC des SEPA-Clearers (Produktion: MARKDEFF; Test: MARKDEF0)	SEPA-Clearer's BIC (production: MARKDEFF; test: MARKDEF0)
		Anwendbare Codes / Acceptable Codes		
		MARKDEF0 MARKDEFF		
1..1	Rcvglnst BBkDVFBkDirDeb +Rcvglnst	Name Receiving Institution Typ sw5:BIcIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}	11-stelliger BIC des Empfängers (Kommunikationspartner)	Recipient's 11-digit BIC (communication partner)
1..1	SrvclD BBkDVFBkDirDeb +SrvclD	Name Service Identifier Typ BBkDVF:SrvclD	COR oder B2B	COR or B2B
		Anwendbare Codes / Acceptable Codes		
		B2B COR		
1..1	TstCode BBkDVFBkDirDeb +TstCode	Name Test Code Typ BBkDVF:TestCodeType	Entweder Wert "T" (Test) oder Wert "P" (Produktion), abhängig von der Verarbeitungsumgebung	Either "T" (test) or "P" (production), depending on the processing environment
		Anwendbare Codes / Acceptable Codes		
		P T		
1..1	FType BBkDVFBkDirDeb +FType	Name File Type Typ BBkDVF:FTpType	DVF	DVF
		Anwendbare Codes / Acceptable Codes		
		DVF		
1..1	FileRef BBkDVFBkDirDeb +FileRef	Name File Reference Typ BBkDVF:Max16Text Pattern [0-9A-Z]{16,16}	Referenz des SEPA-Clearers	SEPA-Clearer's reference
1..1	FileDtTm BBkDVFBkDirDeb +FileDtTm	Name File Date and Time Typ sw5:ISODateTime	Erstellungsdatum und -zeit	File creation date and time

BBkDVFBkDirDeb

Status	Element/Attribute	Format	Inhalte und Prüfung	Contents and Checks
0..1	OrigFRef BBkDVFBkDirDeb +OrigFRef	Name Typ Pattern Original File Reference BBkDVF:Max16Text [0-9A-Z]{16,16}	Nur gefüllt wenn aus Ursprungsdatei ermittelbar	Given only when ascertainable from original file
1..1	OrigFName BBkDVFBkDirDeb +OrigFName	Name Typ Length Original File Name BBkDVF:Max32Text 1 .. 32	SWIFTNet FileAct: Original IDF Dateiname. Ohne Konstante „SCL_“ EBICS: Interne, vom SEPA-Clearer generierte Referenz, welche dem Einreicher keine Rückschlüsse auf die eingereichte Datei ermöglicht	SWIFTNet FileAct: original IDF file name; without the constant “SCL_” EBICS: Internal by the SEPA-Clearer generated reference. Allows no conclusion about the submitted file
0..1	OrigDtTm BBkDVFBkDirDeb +OrigDtTm	Name Typ Original Date And Time sw5:ISODateTime	Nur wenn ermittelbar	Only when ascertainable
1..1	IdfErrCd BBkDVFBkDirDeb +IdfErrCd	Name Typ IDF Error Code BBkDVF:Text3	Grund für Rückweisung / Teilrückweisung des Files	Reason for rejection/partial rejection of file
1..1	FileBusDt BBkDVFBkDirDeb +FileBusDt	Name Typ File Business Date sw5:ISODate	Geschäftstag der Erstellung des Files durch den SEPA-Clearer	Business day on which the file was created by the SEPA-Clearer
1..1	FileCycleNo BBkDVFBkDirDeb +FileCycleNo	Name Typ Pattern File Cycle Number BBkDVF:Max2NumericText [0-9]{2,2}	Verarbeitungsphase in der das File vom SEPA-Clearer erstellt wurde	Processing phase during which the file was created by the SEPA-Clearer

XML-File-Header

Debit Notification File (DNF) Header

Verwendung

- Auslieferung von pacs.003-, pacs.002- und camt.056-Bulks vor Settlement durch den SEPA-Clearer an einen SEPA-Clearer-Teilnehmer
- Ein File enthält genau ein Bulk
- Die Schemadatei „BBkDNFBkDirDeb“ spezifiziert den DNF

Use

- Delivery of pacs.003, pacs.002 and camt.056 bulks to a SEPA-Clearer participant via the SEPA-Clearer prior to settlement.
- Each file contains exactly one bulk.
- The schema file BBkDNFBkDirDeb specifies the DNF.

Nachrichtenstruktur / Message structure

Status	Element/Attribute	Format	Inhalte und Prüfung	Contents and Checks
	BBkDNFBkDirDeb			
1..1	FType BBkDNFBkDirDeb +FType	Name File Type Typ BBkDNF:FTpType	DNF	DNF
		Anwendbare Codes / Acceptable Codes		
		DNF		
1..1	SndgInst BBkDNFBkDirDeb +SndgInst	Name Sending Institution Typ BBkDNF:BIcIdentifierBBk	BIC des SEPA-Clearers (Produktion: MARKDEFF; Test: MARKDEF0)	SEPA-Clearer's BIC (production: MARKDEFF; test: MARKDEF0)
		Anwendbare Codes / Acceptable Codes		
		MARKDEF0 MARKDEFF		
1..1	RcvgInst BBkDNFBkDirDeb +RcvgInst	Name Receiving Institution Typ sw3:BIcIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}	11-stelliger BIC des Empfängers (Kommunikationspartner)	Recipient's 11-digit BIC (communication partner)
1..1	SrvclD BBkDNFBkDirDeb +SrvclD	Name Service Identifier Typ BBkDNF:SrvclD	COR oder B2B	COR or B2B
		Anwendbare Codes / Acceptable Codes		
		B2B COR		
1..1	TstCode BBkDNFBkDirDeb +TstCode	Name Test Code Typ BBkDNF:TestCodeType	Entweder Wert "T" (Test) oder Wert "P" (Produktion), abhängig von der Verarbeitungsumgebung	Either "T" (test) or "P" (production), depending on the processing environment
		Anwendbare Codes / Acceptable Codes		
		P T		
1..1	FileRef BBkDNFBkDirDeb +FileRef	Name File Reference Typ BBkDNF:Max16Text Pattern [0-9A-Z]{16,16}	Referenz des SEPA-Clearers	SEPA-Clearer's reference
1..1	FileBusDt BBkDNFBkDirDeb +FileBusDt	Name File Business Date Typ sw2:ISODate Pattern [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}	Geschäftstag der Erstellung des Files durch den SEPA-Clearer	Business day on which the file was created by the SEPA-Clearer

BBkDNFBikDirDeb

Status	Element/Attribute	Format	Inhalte und Prüfung	Contents and Checks
1..1	RoutingInd BBkDNFBikDirDeb +RoutingInd	Name Routing Indicator Typ BBkDNF:RoutingInd	ALL	ALL
Anwendbare Codes / Acceptable Codes				
		ALL DIR IND		
1..1	FileCycleNo BBkDNFBikDirDeb +FileCycleNo	Name File Cycle Number Typ BBkDNF:Max2NumericText Pattern [0-9]{2,2}	Verarbeitungsphase in der das File vom SEPA-Clearer erstellt wurde	Processing phase during which the file was created by the SEPA-Clearer
1..1	NumDDBik BBkDNFBikDirDeb +NumDDBik	Name Number of pacs.003 Typ BBkDNF:Max8NumericText Pattern [0-9]{1,8}	Anzahl der enthaltenen Bulks des Typs pacs.003	Number of bulks of type pacs.003 received
1..1	NumPCRBik BBkDNFBikDirDeb +NumPCRBik	Name Number of camt.056 Typ BBkDNF:Max8NumericText Pattern [0-9]{1,8}	Anzahl der enthaltenen Bulks des Typs camt.056	Number of bulks of type camt.056 received
1..1	NumREJBik BBkDNFBikDirDeb +NumREJBik	Name Number of pacs.002 Typ BBkDNF:Max8NumericText Pattern [0-9]{1,8}	Anzahl der enthaltenen Bulks des Typs pacs.002	Number of bulks of type pacs.002 received

XML-File-Header

Settled Debit File (SDF) Header

Verwendung

- Auslieferung von pacs.004- und pacs.007-Bulks nach Settlement durch den SEPA-Clearer an einen SEPA-Clearer-Teilnehmer
- Ein File enthält genau ein Bulk
- Die Schemadatei „BBkSDFBlkDirDeb“ spezifiziert den SDF

Use

- Delivery of pacs.004 and pacs.007 bulks after settlement to SEPA-Clearer participants via the SEPA-Clearer.
- Each file contains exactly one bulk.
- The schema file BBkSDFBlkDirDeb specifies the SDF.

Nachrichtenstruktur / Message structure					
Status	Element/Attribute	Format	Inhalte und Prüfung	Contents and Checks	
	BBkSDFBlkDirDeb				
1..1	Sndglnst BBkSDFBlkDirDeb +Sndglnst	Name Sending Institution Typ BBkSDF:BIcIdentifierBBk	BIC des SEPA-Clearers (Produktion: MARKDEFF; Test: MARKDEF0)	SEPA-Clearer's BIC (production: MARKDEFF; test: MARKDEF0)	
		Anwendbare Codes / Acceptable Codes			
		MARKDEF0 MARKDEFF			
1..1	Rcvglnst BBkSDFBlkDirDeb +Rcvglnst	Name Receiving Institution Typ sw7:BIcIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}	11-stelliger BIC des Empfängers (Kommunikationspartner)	Recipient's 11-digit BIC (communication partner)	
1..1	SrvclD BBkSDFBlkDirDeb +SrvclD	Name Service Identifier Typ BBkSDF:SrvclD	COR oder B2B	COR or B2B	
		Anwendbare Codes / Acceptable Codes			
		B2B COR			
1..1	TstCode BBkSDFBlkDirDeb +TstCode	Name Test Code Typ BBkSDF:TestCodeType	Entweder Wert "T" (Test) oder Wert "P" (Produktion), abhängig von der Verarbeitungsumgebung	Either "T" (test) or "P" (production), depending on the processing environment	
		Anwendbare Codes / Acceptable Codes			
		P T			
1..1	FType BBkSDFBlkDirDeb +FType	Name File Type Typ BBkSDF:FTpType	SDF	SDF	
		Anwendbare Codes / Acceptable Codes			
		SDF			
1..1	FileRef BBkSDFBlkDirDeb +FileRef	Name File Reference Typ BBkSDF:Max16Text Pattern [0-9A-Z]{16,16}	Referenz des SEPA-Clearers	SEPA-Clearer's reference	
1..1	RoutingInd BBkSDFBlkDirDeb +RoutingInd	Name Routing Indicator Typ BBkSDF:RoutingInd	ALL	ALL	

BBkSDFBlkDirDeb

Status	Element/Attribute	Format	Inhalte und Prüfung	Contents and Checks
		Anwendbare Codes / Acceptable Codes		
		ALL		
		DIR		
		IND		
1..1	FileBusDt BBkSDFBlkDirDeb +FileBusDt	Name File Business Date Typ sw7:ISODate Pattern [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}	Geschäftstag der Erstellung des Files durch den SEPA-Clearer	Business day on which the file was created by the SEPA-Clearer
1..1	FileCycleNo BBkSDFBlkDirDeb +FileCycleNo	Name File Cycle Number Typ BBkSDF:Max2NumericText Pattern [0-9]{2,2}	Verarbeitungsphase in der das File vom SEPA-Clearer erstellt wurde	Processing phase during which the file was created by the SEPA-Clearer

XML-File-Header

Unsettled Debit File (UDF) Header

Verwendung

- Information der Zahlstelle über das fehlgeschlagene Settlement von SDD-Zahlungen im SEPA-Clearer
 - Settlement-Fehler führen zur Nichtausführung von SDD-Zahlungen
 - Transaktionen, die wegen mangelnder Deckung nicht ausgeführt werden können, werden dem UDF beigefügt
 - Ein UDF enthält immer genau ein Bulk
- Die Schemadatei „BBkUDFBikDirDeb“ spezifiziert den UDF

Use

- Information of the participant on the debit side of the SDD transactions from the SEPA-Clearer that could not be settled
 - Settlement errors result in the non-execution of SDD transactions
 - Transactions that could not be settled due to insufficient funds are attached to the UDF
 - Each UDF contains always exactly one bulk
- The schema file BBkUDFBikDirDeb specifies the UDF

Nachrichtenstruktur / Message structure

Status	Element/Attribute	Format	Inhalte und Prüfung	Contents and Checks
	BBkUDFBkDirDeb			
1..1	Sndglnst BBkUDFBkDirDeb +Sndglnst	Name Sending Institution Typ BBkUDF:BIcIdentifierBBk	BIC des SEPA-Clearers (Produktion: MARKDEFF; Test: MARKDEF0)	SEPA-Clearer's BIC (production: MARKDEFF; test: MARKDEF0)
		Anwendbare Codes / Acceptable Codes		
		MARKDEF0 MARKDEFF		
1..1	Rcvglnst BBkUDFBkDirDeb +Rcvglnst	Name Receiving Institution Typ sw3:BIcIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}	11-stelliger BIC des Empfängers (Kommunikationspartner)	Recipient's 11-digit BIC (communication partner)
1..1	SrvclD BBkUDFBkDirDeb +SrvclD	Name Service Identifier Typ BBkUDF:SrvclD	COR oder B2B	COR or B2B
		Anwendbare Codes / Acceptable Codes		
		B2B COR		
1..1	TstCode BBkUDFBkDirDeb +TstCode	Name Test Code Typ BBkUDF:TestCodeType	Entweder Wert "T" (Test) oder Wert "P" (Produktion), abhängig von der Verarbeitungsumgebung	Either "T" (test) or "P" (production), depending on the processing environment
		Anwendbare Codes / Acceptable Codes		
		P T		
1..1	FType BBkUDFBkDirDeb +FType	Name File Type Typ BBkUDF:FTpType	UDF	UDF
		Anwendbare Codes / Acceptable Codes		
		UDF		
1..1	FileRef BBkUDFBkDirDeb +FileRef	Name File Reference Typ BBkUDF:Max16Text Pattern [0-9A-Z]{16,16}	Referenz des SEPA-Clearers	SEPA-Clearer's reference
1..1	RoutingInd BBkUDFBkDirDeb +RoutingInd	Name Routing Indicator Typ BBkUDF:RoutingInd	ALL	ALL

BBkUDFBkDirDeb

Status	Element/Attribute	Format	Inhalte und Prüfung	Contents and Checks
		Anwendbare Codes / Acceptable Codes		
		ALL		
		DIR		
		IND		
1..1	FileBusDt BBkUDFBkDirDeb +FileBusDt	Name File Business Date Typ sw3:ISODate Pattern [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}	Geschäftstag der Erstellung des Files durch den SEPA-Clearer	Business day on which the file was created by the SEPA-Clearer
1..1	FileCycleNo BBkUDFBkDirDeb +FileCycleNo	Name File Cycle Number Typ BBkUDF:Max2NumericText Pattern [0-9]{2,2}	Verarbeitungsphase in der das File vom SEPA-Clearer erstellt wurde	Processing phase during which the file was created by the SEPA-Clearer

XML-File-Header

Result of Settlement File (RSF) Header

Verwendung

- Einzeltransaktionsrückweisungen von SDD-Zahlungen durch den SEPA-Clearer an den Einreicher
 - Settlement-Fehler im SEPA-Clearer oder bei anderen Clearinghäusern führen zur Rückweisung von SDD-Zahlungen mit dem Fehlercode ED05, dieser wird im beigefügten pacs.002.001.03SCLSDD im Feld TxInfAndSts/StsRsnInf/Prtry angegeben.
 - Jeder RSF enthält immer genau ein Bulk.
 - Der RSF wird am Interbank Settlement Date erzeugt
- Die Schemadatei „BBkRSFBkDirDeb“ spezifiziert den RSF

Use

- Individual transaction rejection of SDD payments to the submitter from the SEPA-Clearer
 - Settlement errors in the SEPA-Clearer or with other CSMs result in the rejection of SDD payments with the error code ED05, which is indicated in the field TxInfAndSts/StsRsnInf/Prtry in the attached pacs.002.001.03SCLSDD
 - Each RSF contains always exactly one bulk
 - The RSF is generated at the Interbank Settlement Date
- The schema file BBkRSFBkDirDeb specifies the RSF

Nachrichtenstruktur / Message structure					
Status	Element/Attribute	Format	Inhalte und Prüfung	Contents and Checks	
	BBkRSFBkDirDeb				
	BBkRSFBkDirDeb				
1..1	Sndglnst BBkRSFBkDirDeb +Sndglnst	Name Sending Institution Typ BBkRSF:BIcIdentifierBBk	BIC des SEPA-Clearers (Produktion: MARKDEFF; Test: MARKDEF0)	SEPA-Clearer's BIC (production: MARKDEFF; test: MARKDEF0)	
		Anwendbare Codes / Acceptable Codes			
		MARKDEF0 MARKDEFF			
1..1	Rcvglnst BBkRSFBkDirDeb +Rcvglnst	Name Receiving Institution Typ sw5:BIcIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}	11-stelliger BIC des Empfängers (Kommunikationspartner)	Recipient's 11-digit BIC (communication partner)	
1..1	SrvclD BBkRSFBkDirDeb +SrvclD	Name Service Identifier Typ BBkRSF:SrvclD	COR oder B2B	COR oder B2B	
		Anwendbare Codes / Acceptable Codes			
		B2B COR			
1..1	TstCode BBkRSFBkDirDeb +TstCode	Name Test Code Typ BBkRSF:TestCodeType	Entweder Wert "T" (Test) oder Wert "P" (Produktion), abhängig von der Verarbeitungsumgebung	Either "T" (test) or "P" (production), depending on the processing environment	
		Anwendbare Codes / Acceptable Codes			
		P T			
1..1	FType BBkRSFBkDirDeb +FType	Name File Type Typ BBkRSF:FTpType	RSF	RSF	
		Anwendbare Codes / Acceptable Codes			
		RSF			
1..1	FileRef BBkRSFBkDirDeb +FileRef	Name File Reference Typ BBkRSF:Max16Text Length 1 .. 16	Referenz des SEPA-Clearers	SEPA-Clearer's reference	
1..1	RoutingInd BBkRSFBkDirDeb +RoutingInd	Name Routing Indicator Typ BBkRSF:RoutingInd	ALL	ALL	

BBkRSFBkDirDeb

Status	Element/Attribute	Format	Inhalte und Prüfung	Contents and Checks
Anwendbare Codes / Acceptable Codes				
ALL				
1..1	FileBusDt BBkRSFBkDirDeb +FileBusDt	Name File Business Date Typ sw5:ISODate	Geschäftstag der Erstellung des Files durch den SEPA-Clearer	Business day on which the file was created by the SEPA-Clearer
1..1	FileCycleNo BBkRSFBkDirDeb +FileCycleNo	Name File Cycle Number Typ BBkRSF:Max2NumericText Pattern [0-9]{2,2}	Verarbeitungsphase in der das File vom SEPA-Clearer erstellt wurde	Processing phase during which the file was created by the SEPA-Clearer

Nachricht / Message

SEPA Direct Debit – Interbank Collection (DS-04)

Verwendung der Interbank Customer Direct Debit Collection (pacs.003.001.02)

Diese Nachricht wird verwendet, um eine Lastschrift vom Zahlungsdienstleister des Zahlungsempfängers zum Zahlungsdienstleister des Zahlers zu transportieren.

Die Nachricht berücksichtigt sowohl Sammelaufträge als auch einzelne Zahlungsaufträge.

ISO Nachrichtenstruktur

Eine Direct Debit Interbank Collection beinhaltet:

- einen einzelnen Group Header.
- eine oder mehrere “Direct Debit Transaction Information“-Sequenzen, von denen jede einen Lastschrifteinzug enthält, wie in DS-04 definiert.

Group Header

Der Group Header enthält Informationen, die für die Verarbeitung der gesamten Nachricht benötigt werden.

Use of the Interbank Customer Direct Debit (pacs.003.001.02)

This message is used to transport the Direct Debit Collection instruction from the Creditor Bank to the Debtor Bank.

The message caters for bulk and single direct debit instructions.

ISO message structure

A Direct Debit Interbank Collection contains:

- a single group header
- one or more “direct debit transaction information” sequences, each containing a direct debit instruction as defined in DS-04.

Group header

- The group header contains information required to process the entire message.

Nachrichtenstruktur / Message structure

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document Document	Typ Document			
1..1	FIToFICstmrDrctDbt Document +FIToFICstmrDrctDbt	Typ FIToFICustomerDirectDebitV02			
1..1	GrpHdr Document +FIToFICstmrDrctDbt ++GrpHdr	Name Typ Group Header SCLSDDGroupHeader3		Der Group Header enthält Informationen, die für die Verarbeitung der gesamten Nachricht benötigt werden	Group Header contains processing informations which applies to the whole payment.
1..1	MsgId Document +FIToFICstmrDrctDbt ++GrpHdr +++MsgId	Name Typ Pattern Message Identification SCLSDDId7 ([A-Za-z0-9][+ \? / \- :\(\) \.\, ']){1,35}		Referenz-Nr. des Bulks. MsgId ist Bestandteil der Doppeleinreichungskontrolle auf Dateiebene (über 15 Kalendertage eindeutige Referenz). Fehlercode: B14 Die ersten 8 bzw. 11 Stellen der MsgId müssen im IDF mit dem BIC des Instructing Agent übereinstimmen. Der Rest des Feldes ist frei verfügbar. Fehlercode: B98	Bulk reference number. <MsgId> is part of duplication check at bulk level (unique reference over 15 calendar days). Error code: B14 The first 8 or 11 characters of <MsgId> must match the BIC of the instructing agent in IDF. The rest of the field can be freely defined. Error code: B98
1..1	CreDtTm Document +FIToFICstmrDrctDbt ++GrpHdr +++CreDtTm	Name Typ Pattern Creation Date Time ISODateTime [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}[T][0-9]{2,2}: [0-9]{2,2}:[0-9]{2,2}\S*		Erstellungsdatum und -zeit des Bulks.	Bulk creation date and time.
1..1	NbOfTxs Document +FIToFICstmrDrctDbt ++GrpHdr +++NbOfTxs	Name Typ Pattern Number Of Transactions Max15NumericText [0-9]{1,15}		Gesamtanzahl der Einzeltransaktionen im Bulk. Darf nicht größer sein als 100.000 (maximaler Parameter der Datensätze im Bulk) Fehlercode: B02 Gesamtanzahl der Datensätze	Total number of single transactions in the bulk Must not exceed 100,000 (maximum parameter of data records in the bulk). Error code: B02 Total number of data records

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	TtlIntrBkSttlmAmt Document +FIToFICstmrDrctDbt ++GrpHdr +++TtlIntrBkSttlmAmt	Name Total Interbank Settlement Amount Typ SCLSDDCurrencyAndAmount_Total FractionDigits 2 TotalDigits 18 Inclusive 0.01 .. 99999999999999.99 Pattern [0-9]{0,15}(\.([0-9]{0,2}))?{0,1}	Mandatory Usage Rule: Only 'EUR' is allowed. Usage Rule: Amount must be 0.01 or more and 99999999999999.99 or less. Format Rule: The fractional part has a maximum of two digits.	muss der tatsächlichen Anzahl der Einzeldatensätze in der Datei entsprechen. Fehlercode: B03 Gesamtsumme der Einzeltransaktionen im Bulk. Bis zu 15 Zeichen sind im ganzzahligen Wertebereich erlaubt. Weiterhin maximal bis zwei Nachkommastellen erlaubt. (Schema-Validierung) Währungskennzeichen ist immer "EUR". (Schema-Validierung) Die angegebene Gesamtsumme muss der addierten Summe aus den Einzeltransaktionen des Bulks entsprechen. Fehlercode: B05 Betragsangabe muss mindestens den Wert 0.01 oder mehr enthalten und darf den Wert 99999999999999.99 nicht übersteigen. (Schema-Validierung)	must be equal to the actual number of individual data records in the bulk Error code: B03 Total number of single transactions in the bulk. Integer value of up to 15 characters is allowed. Maximum number of decimal places allowed is two. (Schema validation) Currency symbol is always 'EUR'. (Schema validation) The total amount given must equal the sum of the single transactions in the bulk. Error code: B05 Amount must be at least 0.01 and no more than 99999999999999.99. (Schema validation)
1..1	IntrBkSttlmDt Document +FIToFICstmrDrctDbt ++GrpHdr +++IntrBkSttlmDt	Name Interbank Settlement Date Typ ISODate Pattern [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}	Mandatory AT-26 Settlement Date of the Collection	Abrechnungsdatum (Buchungsdatum) des Einzugs. 1. Datum darf nicht in der Vergangenheit liegen. 2. Muss mindestens einen Geschäftstag in der Zukunft liegen. 3. Darf maximal 14 Kalendertage in der Zukunft liegen. 4. Muss ein T2-Geschäftstag sein. Fehlercode: B15	Settlement date of the collection. 1. The date may not be in the past. 2. The date must be at least one business day in the future. 3. The date may not be more than 14 calendar days in the future. 4. Must be a T2 business Day Error code: B15

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
				<IntrBkSttlmDt> ist Bestandteil der Doppeleinreichungskontrolle auf Datei- (über 15 Kalendertage eindeutige Referenz) und Einzelsatzebene.	<IntrBkSttlmDt> is part of the duplication check at bulk level (unique reference over 15 calendar days) and single record level.
1..1	SttlmInf Document +FIToFICstmrDrctDbt ++GrpHdr +++SttlmInf	Typ SCLSDDSettlementInformation2			
1..1	SttlmMtd Document +FIToFICstmrDrctDbt ++GrpHdr +++SttlmInf ++++SttlmMtd	Name SettlementMethod Typ SCLSDDSettlementMethod2Code		Information über den Settlement Mechanismus. Nur der Code "CLRG" ist zulässig. (Schema-Validierung)	Information on the settlement mechanism. Only the code 'CLRG' is allowed. (Schema validation)
Anwendbare Codes / Acceptable Codes					
CLRG					
1..1	ClrSys Document +FIToFICstmrDrctDbt ++GrpHdr +++SttlmInf ++++ClrSys	Typ SCLSDDClearingSystemIdentification1Choice			
1..1	Prtry Document +FIToFICstmrDrctDbt ++GrpHdr +++SttlmInf ++++ClrSys +++++Prtry	Name Proprietary Typ Max35Text_Prtry Length 1 .. 35 Pattern \S+.* WhiteSpace collapse		Kennzeichen für das Clearing System. Für den SEPA-Clearer ist nur der Wert "SCL" zu verwenden. (Schema-Validierung)	Code for the clearing system. For the SEPA-Clearer, only the value 'SCL' may be used. (Schema validation)
Anwendbare Codes / Acceptable Codes					
SCL					
0..1	InstgAgt Document +FIToFICstmrDrctDbt ++GrpHdr +++InstgAgt	Name Instructing Agent Typ SCLSDDBranchAndFinancialInstitutionIdentification3	Usage Rule: Only BIC is allowed.	Nur bei Einlieferungen in den SEPA-Clearer zu belegen. Hier ist der BIC des SCL-Teilnehmers einzustellen, der zu dem technischen Unterkonto/Sub-Account in T2 gehören, dass für die	Only to be used for submissions to the SEPA-Clearer. Allocation of the BIC of the SCL participant which is linked with the T2 sub-account assigned for settlement with the SEPA-

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
				geldlichen Verrechnung herangezogen wird.	Clearer.
				Bestandteil der Doppeleinreichungskontrolle (geschäftstaglich eindeutige Referenz).	Part of duplication check at bulk level (daily unique reference).
1..1	FinInstnId Document +FIToFICstmrDrctDbt ++GrpHdr +++InstgAgt ++++FinInstnId	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Choice			
1..1	BIC Document +FIToFICstmrDrctDbt ++GrpHdr +++InstgAgt ++++FinInstnId +++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}		BIC muss im Input Debit File (IDF) enthalten und einreichungsberechtigt sein. Fehlercode: B10 Prufung gegen den BIC im File Header (Sending Institution) auf Einreichungsberechtigung des Kommunikationspartners. Fehlercode: B10	BIC must be included in the Input Debit File (IDF) and authorised to submit files Fehlercode: B10 Communication partner's authorisation to submit verified against the BIC in the file header (Sending Institution). Error code: B10
0..1	InstdAgt Document +FIToFICstmrDrctDbt ++GrpHdr +++InstdAgt	Name Typ Instructed Agent SCLSDDBranchAndFinancialInstitutionIdentification3	Usage Rule: Only BIC is allowed.	Nur bei Auslieferungen aus dem SEPA-Clearer belegt. Hier ist der BIC des SCL-Teilnehmers angegeben, der zu dem technischen Unterkonto/Sub-Account in T2 gehort, das fur die Durchfuhrung der geldlichen Verrechnung herangezogen wird.	Only to be used for deliveries from the SEPA-Clearer. Allocation of the BIC of the SCL participant which is linked with the T2 sub-account assigned for settlement with the SEPA-Clearer.
1..1	FinInstnId Document +FIToFICstmrDrctDbt ++GrpHdr +++InstdAgt ++++FinInstnId	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Choice			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	BIC Document +FIToFICstmrDrctDbt ++GrpHdr +++InstdAgt ++++FinInstnId +++++BIC	Name BIC Typ BICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}		BIC darf nur im Debit Notification File (DNF) enthalten sein. Fehlercode: B11	BIC may only be contained in the debit notification file (DNF). Error code: B11
1..n	DrctDbtTxInf Document +FIToFICstmrDrctDbt ++DrctDbtTxInf	Name Direct Debit Transaction Information Typ SCLSDDDirectDebitTransactionInformation2		maximal 100.000 Datensätze im Bulk	Maximum of 100,000 data records in the bulk
1..1	PmtId Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++PmtId	Name Payment Identification Typ SCLSDDPaymentIdentification2			
0..1	InstrId Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++PmtId ++++InstrId	Name Instruction Identification Typ SCLSDDId7 Pattern ([A-Za-z0-9][+ \? / \- : \(\) \. , ']){1,35}		Referenznummer des Instructing Agent ("eigene Ref."). Punkt-zu-Punkt-Referenz.	Reference number of the instructing agent ('own ref'). End-to-end reference.
1..1	EndToEndId Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++PmtId ++++EndToEndId	Name End to End Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse	AT-10 Creditor's reference of the Direct Debit Transaction Usage Rule: A customer reference that must be passed on in the end-to-end payment chain. In the event that no reference was given, NOTPROVIDED must be used.	Referenz des Zahlungsempfängers der Lastschrift. Falls die End-to-End-ID nicht belegt ist, muss der Wert "NOTPROVIDED" vergeben werden. Eine Überprüfung durch den SEPA-Clearer ist nicht vorgesehen.	Creditor's reference of the direct debit transaction. If the end-to-end Id is not given, 'NOTPROVIDED' must be entered. Not checked by the SEPA-Clearer.
1..1	TxId	Name Transaction Identification Typ SCLSDDId7	AT-43 Creditor's bank's reference of the	Referenz der Ersten Inkassostelle.	Reference of the Creditor Bank..

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++PmtId ++++TxId	Pattern ([A-Za-z0-9][+ ? / - : (\\) \., '])(1,35)	collection Usage Rule: Must contain a reference that is meaningful to the Creditor's Bank and is unique over time.	Transaction ID ist Bestandteil der Doppeleinreichungskontrolle auf Einzelsatzebene. Fehlercode: AM05	Transaction Id is part of the duplication check at single record level. Error code: AM05
1..1	PmtTpInf Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++PmtTpInf	Name Typ Payment Type Information SCLSDDPaymentTypeInfo4	Usage Rule: 'Payment Type Information' must be present in either 'Group Header' or in 'Direct Debit Transaction Information'.		
1..1	SvcLvl Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++PmtTpInf ++++SvcLvl	Name Typ Service Level SCLSDDServiceLevel3Choice	Mandatory		
1..1	Cd Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++PmtTpInf ++++SvcLvl +++++Cd	Name Typ Code SCLSDDServiceLevel2Code	AT-20 Identification code of the Scheme Usage Rule: Only 'SEPA' is allowed.	Im SEPA-Clearer ist nur der Code "SEPA" erlaubt. (Schema- Validierung)	In the SEPA-Clearer, only the code 'SEPA' is allowed. (Schema validation)
Anwendbare Codes / Acceptable Codes					
SEPA					
1..1	LclInstrm Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++PmtTpInf ++++LclInstrm	Name Typ Local Instrument SCLSDDLocalInstrument1Choice	Mandatory		
1..1	Cd Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++PmtTpInf ++++LclInstrm +++++Cd	Name Typ Length Code ExternalLocalInstrument1Code 1 .. 35	AT-20 The identification code of the Scheme Usage Rule: Only 'CORE' is allowed. Usage Rule: The mixing of different Local Instrument values is not allowed in the same	Es dürfen nur die Werte "CORE" oder "B2B" enthalten sein (Schema-Validierung). In einem COR-File dürfen nur CORE-Bulks und in einem B2B-File nur B2B-Bulks enthalten sein. Fehlercode: XT43	Only the codes 'CORE' or 'B2B' are allowed (Schema validation). In a COR-file are only CORE and in a B2B-file are only B2B-Bulks allowed. Error code: XT43

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
			message. AT-20 The identification code of the B2B scheme Usage Rule: Only 'B2B' is allowed. Usage Rule: The mixing of different Local Instrument values is not allowed in the same message.	Eine gemischte Einreichung von B2B- und CORE-Lastschriften in einem Bulk ist nicht zulässig. Fehlercode: XT43	Mixed submission of B2B and CORE Direct Debits in one file is not allowed. Error code: XT43
Anwendbare Codes / Acceptable Codes					
B2B CORE					
1..1	SeqTp Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++PmtTpInf ++++SeqTp	Name Sequence Type Typ SCLSDDSequenceType1Code	Mandatory AT-21 Transaction / Sequence Type Usage Rule: If 'Amendment Indicator' is 'true', and 'Original Debtor Account' is set to 'SMNDA' (Same Mandate with a New Debtor Account) , this message element indicates either 'FRST' (First), 'RCUR' (Recurring), 'FNAL' (Final) or 'OOFF' (One-off) (all four codes allowed, no restrictions).	Lastschrift-Typ: FNAL: letztmalig FRST: erstmalig OOFF: einmalig RCUR: wiederholend (Schema-Validierung)	Direct debit type FNAL: final FRST: first OOFF: one-off RCUR: recurring (Schema validation)
Anwendbare Codes / Acceptable Codes					
FNAL FRST OOFF RCUR					
0..1	CtgyPurp Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++PmtTpInf ++++CtgyPurp	Name Category Purpose Typ CategoryPurpose1Choice	AT-59 Categorypurpose of the Collection Usage Rule: Depending on the agreement between the Creditor and the Creditor Bank,	Plausibilisierung bei gleichzeitiger Belegung von <Purpose> und <Category Purpose> erfolgt nicht, d.h. widersprüchliche Belegungen werden vom SCL ignoriert.	No plausibility check if <Purpose> and <Category purpose> fields both contain conflicting entries, ie SCL ignores conflicting entries.

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Cd Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++PmtTplnf ++++CtgyPurp +++++Cd	Name Code Typ ExternalCategoryPurpose1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse	'Category Purpose' may be forwarded to the Debtor Bank.	Category Purpose. Cd und Prtry (s.u.) können nicht gleichzeitig verwendet werden. Zweck der Transaktion. Belegung max. vierstellig. Bei Einlieferung in den SCL ist Belegung nicht erforderlich, bei Auslieferung kann das Feld belegt sein. Belegung gem. externer Code-Liste (ISO 20022) möglich; eine Validierung durch den SCL findet nicht statt.	Category purpose. <Cd> and <Prtry> (see below) cannot be used simultaneously. Purpose of transaction. Field may be completed in accordance with the external codelist (ISO 20022). A maximum of four characters may be entered. No entry is required for submissions to the SCL, whereas for deliveries from the SLC an entry may be made in the field. There is no validation by the SCL.
1..1	Prtry Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++PmtTplnf ++++CtgyPurp +++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse		Category Purpose. Cd (s.o.) und Prtry können nicht gleichzeitig verwendet werden. Bei Einlieferung in den SCL ist Belegung nicht erforderlich, bei Auslieferung kann das Feld belegt sein; eine Validierung durch den SCL findet nicht statt.	Category purpose. <Cd> (see above) and <Prtry> cannot be used simultaneously. No entry is required for submissions to the SCL, whereas for deliveries from the SLC an entry may be made in the field. There is no validation by the SCL.
1..1	IntrBkSttlmAmt Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++IntrBkSttlmAmt	Name Interbank Settlement Amount Typ SCLSDDCurrencyAndAmount_Tx FractionDigits 2 TotalDigits 18 Inclusive 0.01 .. 999999999.99 Pattern [0-9]{0,15}(\. [0-9]{0,2}){0,1}	AT-06 Amount of the Collection in Euro Usage Rule: Only 'EUR' is allowed. Usage Rule: Amount must be 0.01 or more and 999999999.99 or less. Format Rule: The fractional part has a maximum of two digits.	Betrag der jeweiligen Lastschrift. Das Währungskennzeichen muss "EUR" lauten (Schema-Validierung); Maximal zwei Nachkommastellen dürfen aufgrund des Währungskennzeichens "EUR" angegeben werden. (Schema-Validierung)	The amount of the relevant direct debit. The currency designation must be 'EUR'. (Schema validation) A maximum of two decimal places may be used. (Schema validation)
				Betrag darf den vorgesehenen	Amount must not exceed

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
				Maximalbetrag (999999999.99) nicht übersteigen und muss größer als "0" sein. (Schema-Validierung)	permitted maximum amount (999999999.99) and must be greater than '0'. (Schema validation)
1..1	ChrgBr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++ChrgBr	Name Charge Bearer Typ SCLSDDChargeBearerType1Code	Usage Rule: Only 'SLEV' is allowed.	Nur SLEV ist erlaubt. (Schema-Validierung)	Only SLEV is allowed. (Schema validation)
Anwendbare Codes / Acceptable Codes					
SLEV					
1..1	ReqdColltnDt Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++ReqdColltnDt	Name Requested Collection Date Typ ISODate Pattern [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}	Mandatory AT-11 Due Date of the Collection	Fälligkeitsdatum des Einzugs. Unterscheidung nach Einlieferungsphase: Einlieferung in ein morgendliches Fenster: Immer D-1 T2-Geschäftstag (keine Abhängigkeit zum SeqTp). Einlieferung in ein abendliches Fenster oder nach Annahmeschluss: Immer D-2 T2-Geschäftstage (keine Abhängigkeit zum SeqTp). Datum darf nicht größer als D-14 Kalendertage sein. Datum muss gleich bzw. darf nur einen Geschäftstag geringer ausfallen, als das "IntrBkSttlmDt". Fehlercode: DT01 (D = Fälligkeitstag des Einzugs / Due Date) Bei der Berechnung der Fristen wird der Einlieferungstag in den SCL mitgezählt.	Due date of the collection. Differentiation according to submission windows: Submission until 15.00 (Core) or 13.00 (B2B): D-1 T2 business day (not dependent on SeqTp). Submission after 15.00 (Core) or 13.00 (B2B): D-2 T2 business days (not dependent on SeqTp) Date may not be more than D-14 calendar Days.Date must be equal to or only one business day less than the 'IntrBk SttlmDt'. Error code: DT01 D = due date (for collection) The day of submission to the SCL is included in the calculation of deadlines.

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	DrctDbtTx Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx	Name Typ Direct Debit Transaction SCLSDDDirectDebitTransaction1	Mandatory		
1..1	MndtRltdInf Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf	Name Typ Mandate Related Information SCLSDDMandateRelatedInformation1	Mandatory		
1..1	MndtId Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++MndtId	Name Typ Pattern Mandate Identification SCLSDDId8 ([A-Za-z0-9][+ \/ \/- \/()\ \. ' \"}]1,35)	Mandatory AT-01 Unique Mandate Reference	Eindeutige Mandatsreferenz. (Nur Schema-Validierung)	Unique mandate reference. (schema validation only)
1..1	DtOfSgntr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++DtOfSgntr	Name Typ Pattern Date Of Signature ISODate [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}	Mandatory AT-25 Date of Signing of the Mandate	Datum der Unterzeichnung des Mandats.	Date mandate was signed.
0..1	AmdmntInd Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++AmdmntInd	Name Typ Amendment Indicator TrueFalseIndicator		Grund für Änderung des Mandats. Falls Belegung mit "true", muss mindestens eines der folgenden Felder belegt sein. Fehlercode: XT13 Falls Belegung mit "false", darf keines der folgenden Felder belegt sein. Fehlercode: XT13 Falls Feld nicht belegt ist, wird von der Standardeinstellung "false" ausgegangen.	Amendment Indicator of the mandate. If completed with 'TRUE', at least one of the following fields must be completed. Error code: XT13 If completed with 'FALSE', none of the following fields may be completed. Error code: XT13 If the field is not completed, 'FALSE' is assumed to be the default setting.

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	AmdmntInfDtls Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++AmdmntInfDtls	Name Typ Amendment Information Details SCLSDDAmdmentInformationDetails1	AT-24 Reason for Amendment of the Mandate Usage Rule: Mandatory if 'Amendment Indicator' is 'true'. The reason code from the Rulebook is indicated using one of the following message sub-elements:		
0..1	OrgnlMndtld Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++AmdmntInfDtls +++++OrgnlMndtld	Name Typ Pattern Original Mandate Identification SCLSDdId8 ([A-Za-z0-9][+ / \- : \(\) \., ' \s]){1,35}	AT-19 Unique Mandate reference as given by the original Creditor who issued the Mandate Usage Rule: Mandatory if changes occur in 'Mandate Identification', otherwise not to be used.	Eindeutige Referenz des Mandats, die vom Zahlungsempfänger (Gläubiger) bei der Ausstellung des Mandats vergeben wurde. Prüfung in Abhängigkeit von der Belegung in <AmdmntInd>. Fehlercode: XT13	Unique mandate reference as given by the creditor when the mandate was issued. Check depending on entry in <AmdmntInd>. Error code: XT13
0..1	OrgnlCdtrSchmeld Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++AmdmntInfDtls +++++OrgnlCdtrSchmeld	Name Typ Original Creditor Scheme Identification SCLSDdCdrSchmeld1	Usage Rule: Mandatory if changes occur in 'Creditor Scheme Identification', otherwise not to be used.	Identifikator des ursprünglichen Zahlungsempfängers, der das Mandat herausgegeben hat.	Identifier of the original creditor who issued the mandate.
0..1	Nm Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++AmdmntInfDtls +++++OrgnlCdtrSchmeld +++++Nm	Name Typ Length Pattern WhiteSpace Name Max70Text 1 .. 70 \\S+.* collapse	Original AT-03 Name of the Creditor Usage Rule: If present, the new name must be specified under 'Creditor'. Usage Rule: 'Name' is limited to 70 characters in length	Name des Zahlungsempfängers. Prüfung in Abhängigkeit von der Belegung in <AmdmntInd>. Fehlercode: XT13	Name of creditor. Check depending on entry in <AmdmntInd>. Error code: XT13
0..1	Id Document +FIToFICstmrDrctDbt	Name Typ Identification SCLSDdPrivateIdentification	AT-18 Identifier of the Original Creditor who issued the Mandate		

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnCdtrSchmeld ++++++Id				
1..1	PrvtId Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnCdtrSchmeld ++++++Id ++++++PrvtId	Name Typ Private Identification SCLSDDPrty1	Usage Rule: Private Identification is used to identify either an organisation or a private person.		
1..1	Othr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnCdtrSchmeld ++++++Id ++++++PrvtId ++++++Othr	Name Typ Other SCLSDDId4	Usage Rule: Only one occurrence of 'Other' is allowed, and no other sub-elements are allowed. 'Identification' must be used with an identifier described in General Message Element Specifications, Chapter 1.5.2. 'Proprietary' under 'Scheme Name' must specify 'SEPA'.		
1..1	Id Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnCdtrSchmeld ++++++Id	Name Typ Pattern Identification SCLSDDId8 ([A-Za-z0-9][+ ? / - : \(\) \. ' \\s]){1,35}		Identifikator des ursprünglichen Zahlungsempfängers der das Mandat herausgegeben hat. Prüfung in Abhängigkeit von der Belegung in <AmdmntInd> Fehlercode: XT13	Unique mandate reference as given by the creditor when the mandate was issued. Check depending on entry in <AmdmntInd>. Error code: XT13

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	<p>+++++PrvtId +++++Othr +++++Id</p> <p>SchmeNm</p> <p>Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++AmdmntInfDtIs +++++OrgnCctrSchmeld +++++Id +++++PrvtId +++++Othr +++++SchmeNm</p>	<p>Name Typ</p> <p>Scheme Name FinancialIdentificationSchemeName2</p>			
1..1	<p>Prtry</p> <p>Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++AmdmntInfDtIs +++++OrgnCctrSchmeld +++++Id +++++PrvtId +++++Othr +++++SchmeNm +++++Prtry</p>	<p>Name Typ</p> <p>Proprietary SCLSDDId9</p>		Nur "SEPA" zulässig.	Only "SEPA" allowed.
Anwendbare Codes / Acceptable Codes					
SEPA					
0..1	<p>OrgnIDbtrAcct</p> <p>Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++AmdmntInfDtIs +++++OrgnIDbtrAcct</p>	<p>Name Typ</p> <p>Original Debtor Account SCLSDDCashAccount8</p>	To use 'Identification' under 'Other' under 'Identification' with code 'SMNDA' (Same Mandate with a New Debtor Account) to indicate same mandate with new Debtor Account. Or In case of an account change within the same bank, IBAN is allowed.		

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Id Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnIDbtrAcct +++++++Id	Name Identification Typ SCLSDDAccountIdentification4Choice			
1..1	IBAN Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnIDbtrAcct +++++++Id +++++++IBAN	Name IBAN Typ IBANIdentifier Pattern [a-zA-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}		Prüfung in Abhängigkeit von der Belegung in <AmdmntInd>. Fehlercode: XT13	Check depending on entry in <AmdmntInd>. Error code: XT13
1..1	Othr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnIDbtrAcct +++++++Id +++++++Othr	Name Other Typ SCLSDDOrgnIDbtrAcctOther2			
1..1	Id Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnIDbtrAcct +++++++Id +++++++Othr +++++++Id	Name Identification Typ Max34Text_SMNDA Length 1 .. 34 Pattern \S+.* WhiteSpace collapse		Nur die Belegung mit "SMNDA" ist erlaubt. (Schemavalidierung)	Only "SMNDA" is allowed (schema validation)

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
Anwendbare Codes / Acceptable Codes					
SMNDA					
0..1	OrgnIDbtrAgt Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnIDbtrAgt	Name Original Debtor Agent Typ SCLSDDOrgnIDbtrAgt	Not to be used if element 'Original Debtor Account' is populated with 'SMNDA' (Same Mandate with a New Debtor Account)	Prüfung in Abhängigkeit von der Belegung in <AmdmntInd>. Fehlercode: XT13 Darf nicht belegt sein, wenn Id unter <OrgnIDbtrAcct>/<Id>/<Othr>/<Id> mit "SMNDA" belegt ist. Fehlercode: XT13	Check depending on entry in <AmdmntInd>. Error code: XT13 Not to be used if <OrgnIDbtrAcct>/<Id>/<Othr>/<Id> is populated with 'SMNDA' Error code: XT13
1..1	FinInstnId Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnIDbtrAgt +++++++FinInstnId	Name Financial Institution Identification Typ SCLSDDOrgnIDbtrAgt1			
1..1	BIC Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnIDbtrAgt +++++++FinInstnId +++++++BIC	Name BIC Typ BICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}			
0..1	ElectrcSgntr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++MndtRltdInf +++++ElectrcSgntr	Name Electronic Signature Typ Max1025Text Length 1 .. 1025	AT-16 Placeholder for the electronic signature data, if applicable AT-17 The type of Mandate (paper or e-mandate) AT-60 Reference of the validation made by the Debtor Bank (if present in DS-03) Usage Rule: If the direct	Platzhalter Elektronische Unterschrift.	Placeholder for electronic signature

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
				debit is based on an EPC electronic mandate, this data element must contain AT-60 which is the reference to the Mandate Acceptance Report made by the Debtor Bank. This data element is not to be used if the mandate is a paper mandate.	
1..1	CdtrSchmeld Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++CdtrSchmeld	Name Typ Creditor Scheme Identification SCLSDDCdtrSchmeld	Mandatory	Identifikator des Zahlungsempfängers.	Creditor identifier
1..1	Id Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++CdtrSchmeld +++++Id	Name Typ Identification SCLSDDPrivatIdentification2	Mandatory AT-02 Identifier of the Creditor	Prüfung des im Rulebook beschriebenen Aufbaus der Id. Stellen 3-4 (Prüfziffer) werden analog der IBAN-Prüfziffer berechnet (ISO13616). Fehlercode: XT53	Check of the structure of <Id> described in the rulebook. Digits 3-4 (check digits) are calculated in compliance with the IBAN check digits (ISO13616). Error code: XT53
1..1	PrvtId Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++CdtrSchmeld +++++Id ++++++PrvtId	Name Typ Private Identification SCLSDDPrty2	Usage Rule: Private Identification is used to identify either an organisation or a private person.		
1..1	Othr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++CdtrSchmeld	Name Typ Other SCLSDDId10	Usage Rule: Only one occurrence of 'Other' is allowed, and no other sub-elements are allowed. Identification must be		

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+++++Id +++++PrvtId +++++Othr		used with an identifier described in General Message Element Specifications, Chapter 1.5.2. 'Proprietary' under 'Scheme Name' must specify 'SEPA'.		
1..1	Id Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++CdtrSchmeld +++++Id +++++PrvtId +++++Othr +++++Id	Name Typ Pattern Identification SCLSDDId8 ([A-Za-z0-9][+ \/ \\- \\(\\) \\. ' \\s]){1,35}		Prüfungen gemäß den Formatvorgaben der EPC-Implementation Guidelines (s. "Gläubiger-Identifikationsnummer" in Kap. "Allgemeine Spezifikationen von Nachrichtenelementen"). Die Stellen 1-7 dürfen keine Leerzeichen beinhalten. Führende Leerzeichen werden dabei jedoch nicht berücksichtigt. Fehlercode: XT53	Checks according to the format rules of the EPC Implementation Guidelines (see "creditor identification number" under general specifications of message elements). Error code: XT53 The digits 1-7 must not contain any spaces. However leading spaces are not taken into account. Error code: XT53
1..1	SchmeNm Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++CdtrSchmeld +++++Id +++++PrvtId +++++Othr +++++SchmeNm	Name Typ Scheme Name FinancialIdentificationSchemeName2			
1..1	Prtry Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DrctDbtTx ++++CdtrSchmeld +++++Id +++++PrvtId +++++Othr +++++SchmeNm +++++Prtry	Name Typ Proprietary SCLSDDId9		Nur "SEPA" zulässig.	Only 'SEPA' allowed

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
		Anwendbare Codes / Acceptable Codes			
		SEPA			
1..1	Cdtr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Cdtr	Name Creditor Typ SCLSDDId2			
1..1	Nm Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Cdtr ++++Nm	Name Name Typ Max70Text Length 1 .. 70 Pattern \S+* WhiteSpace collapse	Mandatory AT-03 Name of the Creditor Usage Rule: "Name" is limited to 70characters in length.	Name des Zahlungsempfängers.	Name of creditor.
0..1	PstlAdr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Cdtr ++++PstlAdr	Name Postal Address Typ SCLSDDPostalAddress1	AT-05 Address of the Creditor Usage Rule: 'Postal Address' is optional but is mandatory if provided by the Creditor.	Adresse des Zahlungsempfängers.	Address of creditor.
0..1	Ctry Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Cdtr ++++PstlAdr +++++Ctry	Name Country Typ CountryCode Pattern [A-Z]{2,2}		Prüfung des Ländercodes gemäß ISO3166. Fehlercode: XT73	Check of country code in accordance with ISO 3166. Error code: XT73
0..2	AdrLine Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Cdtr ++++PstlAdr +++++AdrLine	Name Adress Line Typ Max70Text Length 1 .. 70 Pattern \S+* WhiteSpace collapse	Usage Rule: Only two occurrences are allowed.	"Address Line" darf nur zweimal vorkommen. (Schema-Validierung)	Maximum of two occurrences of 'address line' allowed. (Schema validation)
1..1	CdtrAcct Document +FIToFICstmrDrctDbt	Name Creditor Account Typ SCLSDDCashAccount7	Mandatory AT-04 Account Number of the Creditor	IBAN des Zahlungsempfängers.	IBAN of creditor.

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Id Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++CdtrAcct ++++Id	Name Typ Identification SCLSDDAccountIdentification3Choice	Usage Rule: Only IBAN is allowed.		
1..1	IBAN Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++CdtrAcct ++++Id +++++IBAN	Name Typ Pattern IBAN IBANIdentifier [a-zA-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}		Überprüfung gemäß ISO 13616. Fehlercode: XD19 Überprüfung der ersten beiden Zeichen auf Übereinstimmung mit einem gültigen ISO-oder SEPA-Ländercode. Fehlercode: XT73	Ckeck in accordance with ISO 13616. Error code: XD19 Check as to whether the first two characters match a valid ISO code or SEPA country code. Error code XT73
1..1	CdtrAgt Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++CdtrAgt	Name Typ Creditor Agent SCLSDDBranchAndFinancialInstitutionIdentification3	AT-12 BIC of the Creditor bank Usage Rule: Only BIC is allowed.	BIC der ersten Inkassostelle.	BIC of the creditor agent.
1..1	FinInstnId Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++CdtrAgt ++++FinInstnId	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Choice			
1..1	BIC Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++CdtrAgt ++++FinInstnId +++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}		Gültigkeit des BIC anhand des SCL-Directorys. Fehlercode: XT27 Generelle Prüfung auf Erreichbarkeit: BIC muss innerhalb des SEPA-Clearers erreichbar sein. Fehlercode: PY01	Validity of BIC using SEPA BIC directory. Error code: XT27 General addressability check: BIC must be addressable within the SEPA-Clearer (The CSM identification in the scl-directory must be „MARKDEFF“ in production or „MARKDEF0“ in test) Fehlercode: PY01

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
				<p>Prüfung nur bei Weiterleitung der Zahlung vom SEPA-Clearer an STEP2: BIC muss ein über die Bundesbank registrierter Reachable BIC des entsprechenden SDD Services der EBA CLEARING sein. Fehlercode: PY01</p> <p>Nur bei Weiterleitung an andere CSM: Creditor Agent muss berechtigt sein, Lastschriften einzureichen. Fehlercode: XT80</p> <p>Creditor Agent BIC ist Bestandteil der Doppeleinreichungskontrolle auf Einzelsatzebene. Fehlercode: AM05</p>	<p>Check only if the direct debit is forwarded from the SEPA-Clearer to STEP2: BIC must belong to a registered reachable BIC of the respective STEP2 SDD Service via the Deutsche Bundesbank. Error code: PY01</p> <p>Check only if the direct debit is forwarded from the SEPA-Clearer to another CSM: Creditor agent must be authorised to submit direct debits. Error code: XT80</p> <p>Creditor agent BIC is part of the duplication check at single record level. Error code: AM05</p>
0..1	UltmtCdtr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr	Name Typ Ultimate Creditor SCLSDDPartyIdentification10	Usage Rule: Mandatory if given by the Creditor in 'pain.008.001.02' and must be forwarded through the payment chain up to the Debtor.	Abweichender Zahlungsempfänger	Ultimate creditor
0..1	Nm Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++Nm	Name Typ Length Pattern WhiteSpace Name Max70Text 1 .. 70 \\S+.* collapse	AT-38 Name of the Creditor Reference Party Usage Rule: "Name" is limited to 70 characters in length.	Name des abweichenden Zahlungsempfängers	Name of the ultimate creditor
0..1	Id Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++Id	Name Typ Identification SCLSDDParty3Choice	AT-39 Identification code of the Creditor Reference Party	Identifikation des abweichenden Zahlungsempfängers	Identifiier of ultimate creditor
1..1	OrgId	Name Organisation Identification	Usage Rule: Either "BIC		

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++Id +++++Orgld	Typ SCLSDDOrganisationIdentification4		or BEI" or one occurrence of "Other" is allowed.	
1..1	BICOrBEI Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++Id +++++Orgld ++++++BICOrBEI	Name Typ Pattern BIC or BEI SCLSDDAnyBICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}			
1..1	Othr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++Id +++++Orgld ++++++Othr	Name Typ Other SCLSDDGenericOrganisationIdentification1			
1..1	Id Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++Id +++++Orgld ++++++Othr +++++++Id	Name Typ Length Pattern WhiteSpace Identification Max35Text 1 .. 35 \\S+.* collapse			
0..1	SchmeNm Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++Id +++++Orgld ++++++Othr +++++++SchmeNm	Name Typ Scheme Name SCLSDDOrganisationIdentificationSchemeName1Choice			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Cd Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++ld +++++Orgld +++++Othr +++++SchmeNm +++++Cd	Name Code Typ SCLSDDExternalOrganisationIdentification1 Code Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++ld +++++Orgld +++++Othr +++++SchmeNm +++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++ld +++++Orgld +++++Othr +++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	Prvtld Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++ld +++++Prvtld	Name Private Identification Typ SCLSDDPersonIdentification5	Usage Rule: Either "Date and Place of Birth" or one occurrence of "Other" is allowed.		
1..1	DtAndPicOfBirth	Name Date and Place of Birth Typ DateAndPlaceOfBirth			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++ld +++++PrvtId ++++++DtAndPlcOfBirth				
1..1	BirthDt Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++ld +++++PrvtId ++++++DtAndPlcOfBirth +++++++BirthDt	Name Birth Date Typ ISODate Pattern [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}			
0..1	PrvcOfBirth Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++ld +++++PrvtId ++++++DtAndPlcOfBirth +++++++PrvcOfBirth	Name Province of Birth Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	CityOfBirth Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++ld +++++PrvtId ++++++DtAndPlcOfBirth +++++++CityOfBirth	Name City of Birth Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	CtryOfBirth Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr	Name Country of Birth Typ CountryCode Pattern [A-Z]{2,2}			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++++Id +++++PrvtId +++++DtAndPlcOfBirth +++++CtryOfBirth				
1..1	Othr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++Id +++++PrvtId +++++Othr	Name Other Typ SCLSDDGenericPersonIdentification1			
1..1	Id Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++Id +++++PrvtId +++++Othr +++++Id	Name Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	SchmeNm Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++Id +++++PrvtId +++++Othr +++++SchmeNm	Name Scheme Name Typ SCLSDDPersonIdentificationSchemeName1 Choice			
1..1	Cd Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++Id +++++PrvtId +++++Othr +++++SchmeNm	Name Code Typ SCLSDDExternalPersonIdentification1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	+++++++Cd Prtry Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++Id +++++PrvtId +++++Othr +++++SchmeNm +++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtCdtr ++++Id +++++PrvtId +++++Othr +++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	InstgAgt Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++InstgAgt	Name InstructingAgent Typ SCLSDDBranchAndFinancialInstitutionIdentification3	Usage Rule: Only BIC is allowed.	Ursprünglicher Einreicher der Lastschrift. Belegung nur im Debit Notification File (DNF) erlaubt. Nur bei Auslieferung der BBK an den SCL-Teilnehmer (Bank) zu belegen. Hier steht bei Zahlungen, die über STEP2 geleitet werden, der BIC des direkten STEP2-Teilnehmers bzw. bei Zahlungen, die innerhalb des SEPA-Clearers abgewickelt werden, der BIC des SCL- Teilnehmers, der die Lastschrift im SCL eingereicht hat.	Original submitter of the bulk in which the direct debit was included. Only used in the debit notification file (DNF) in deliveries from the Bundesbank to the SCL participant. If payments are routed via STEP2, this element contains the BIC of the direct STEP2 participant. If routed within the SEPA-Clearer, this element contains the BIC of the SCL participant that has submitted the direct debit into the SEPA-Clearer.
1..1	FinInstnId Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++InstgAgt ++++FinInstnId	Name Financial Institution Identification Typ SCLSDDFinancialInstitutionIdentification5Character			

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	BIC Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++InstgAgt ++++FinInstnId +++++BIC	Name BIC Typ BICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}		Belegung nur im Settled Debit File (DNF) erlaubt, darf im Input Debit File (IDF) des Teilnehmers an den SCL nicht enthalten sein. Fehlercode: XT13	Only allowed in the Delivery Notification File (DNF), not to be included in the Input Debit File (IDF) submitted to the SEPA-Clearer Error code: XT13
1..1	Dbtr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr	Name Debtor Typ SCLSDDPartyIdentification9			
1..1	Nm Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++Nm	Name Name Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse	Mandatory AT-14 Name of the Debtor Usage Rule: "Name" is limited to 70 characters in length. <u>CORE:</u> In case of a mandate generated using data from a payment card at the point of sale which results in a direct debit to and from a payment account, and where the name of the Debtor is not available, the attribute "Name of the Debtor" must be filled in with "/CDGM" (note: Card Data Generated Mandate), followed by "/" card number", "/" sequence number" and "/expiry date of the card" (note: this means that the information parts are delimited by "/") or, if these data elements are not available, by any	Name des Zahlungspflichtigen oder Ersatzinformationen, beginnend mit dem Wert „/CDGM“, falls ein Lastschriftzug im SEPA-Core-Lastschriftverfahren auf Grundlage eines mit einer Zahlungskarte an der Verkaufsstelle erteilten Mandates erfolgt.	Name of debtor or an alternative information starting with the attribute "/CDGM" in case of mandate generated using data from a payment card at the point of sale which results in a direct debit

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
			other data element(s) that would uniquely identify the Debtor to the Debtor Bank.		
0..1	PstlAdr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++PstlAdr	Name Typ Postal Address SCLSDDPostalAddress1	AT-09 Address of the Debtor Usage Rule: 'Postal Address' is optional but mandatory if present in DS-02 or when the Creditor Bank or the Debtor Bank is located in a non-EEA SEPA country or territory..	Adresse des Zahlungspflichtigen.	Address of debtor.
0..1	Ctry Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++PstlAdr +++++Ctry	Name Typ Pattern Country CountryCode [A-Z]{2,2}		Prüfung des Ländercodes gem. ISO3166. Fehlercode: XT73	Check of country code in accordance with ISO3166. Error code: XT73
0..2	AdrLine Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++PstlAdr +++++AdrLine	Name Typ Length Pattern WhiteSpace Address Line Max70Text 1 .. 70 \S+.* collapse	Usage Rule: Only two occurrences are allowed.	"Address Line" darf nur zweimal vorkommen (Schema-Validierung).	Maximum of two occurrences of 'address line' allowed. (Schema validation).
0..1	Id Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++Id	Name Typ Identification SCLSDDParty3Choice	AT-27 Debtor identification code	Identifikation des Zahlungspflichtigen.	Identifier of debtor.
1..1	OrgId Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++Id +++++OrgId	Name Typ Organisation Identification SCLSDDOrganisationIdentification4	Usage Rule: Either "BIC or BEI" or one occurrence of "Other" is allowed.	Entweder "Organisation Identification" oder "Private Identification" ist vorhanden (Schema-Validierung). Alle ISO 20022 Optionen sind erlaubt.	Either 'organisation identification' or 'private identification' is available (schema validation). All ISO 20022 options are allowed
		Name BIC or BEI			

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	BICOrBEI Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++ld +++++Orgld ++++++BICOrBEI	Name BIC or BEI Typ SCLSDDDAnyBICIdentifier Pattern [A-Z]{6,6}[A-Z-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}			
1..1	Othr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++ld +++++Orgld ++++++Othr	Name Other Typ SCLSDDDGenericOrganisationIdentification1			
1..1	ld Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++ld +++++Orgld ++++++Othr +++++++ld	Name Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	SchmeNm Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++ld +++++Orgld ++++++Othr +++++++SchmeNm	Name Scheme Name Typ SCLSDDOrganisationIdentificationSchemeName1Choice			
1..1	Cd Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr	Name Code Typ SCLSDDExternalOrganisationIdentification1 Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++++Id +++++Orgld +++++Othr +++++SchmeNm +++++Cd				
1..1	Prtry Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++Id +++++Orgld +++++Othr +++++SchmeNm +++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++Id +++++Orgld +++++Othr +++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	Prvtld Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++Id +++++Prvtld	Name Private Identification Typ SCLSDDPersonIdentification5	Usage Rule: Either "Date and Place of Birth" or one occurrence of "Other" is allowed.	Entweder "Organisation Identification" oder "Private Identification" ist vorhanden. (Schema-Validierung) Alle ISO 20022 Optionen sind erlaubt.	Either 'organisation identification' or 'private identification' is available (schema validation). All ISO 20022 options are allowed.
1..1	DtAndPlcOfBirth Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++Id +++++Prvtld +++++DtAndPlcOfBirth	Name Date and Place of Birth Typ DateAndPlaceOfBirth			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	BirthDt Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++ld +++++PrvtId +++++DtAndPlcOfBirth +++++BirthDt	Name Birth Date Typ ISODate Pattern [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}			
0..1	PrvcOfBirth Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++ld +++++PrvtId +++++DtAndPlcOfBirth +++++PrvcOfBirth	Name Province of Birth Typ Max35Text Length 1 .. 35 Pattern \S+* WhiteSpace collapse			
1..1	CityOfBirth Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++ld +++++PrvtId +++++DtAndPlcOfBirth +++++CityOfBirth	Name City of Birth Typ Max35Text Length 1 .. 35 Pattern \S+* WhiteSpace collapse			
1..1	CtryOfBirth Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++ld +++++PrvtId +++++DtAndPlcOfBirth +++++CtryOfBirth	Name Country of Birth Typ CountryCode Pattern [A-Z]{2,2}			
1..1	Othr Document	Name Other Typ SCLSDDGenericPersonIdentification1			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++Id +++++PrvtId ++++++Othr				
1..1	Id Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++Id +++++PrvtId ++++++Othr +++++++Id	Name Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	SchmeNm Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++Id +++++PrvtId ++++++Othr +++++++SchmeNm	Name Scheme Name Typ SCLSDDPersonIdentificationSchemeName1 Choice			
1..1	Cd Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++Id +++++PrvtId ++++++Othr +++++++SchmeNm +++++++Cd	Name Code Typ SCLSDDExternalPersonIdentification1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++++Id +++++PrvtId +++++Othr +++++SchmeNm +++++Prtry				
0..1	Issr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Dbtr ++++Id +++++PrvtId +++++Othr +++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	DbtrAcct Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DbtrAcct	Name DebtorAccount Typ SCLSDDCashAccount7	AT -07 Account number of the Debtor Usage Rule: Only IBAN is allowed.	IBAN des Zahlungspflichtigen.	IBAN of the Debtor
1..1	Id Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DbtrAcct ++++Id	Name Identification Typ SCLSDDAccountIdentification3Choice			
1..1	IBAN Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DbtrAcct ++++Id +++++IBAN	Name IBAN Typ IBANIdentifier Pattern [a-zA-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}		Überprüfung gemäß ISO 13616. Fehlercode: XD19 und Überprüfung der ersten beiden Zeichen auf Übereinstimmung mit einem gültigen ISO-oder SEPA-Ländercode. Fehlercode: XT73	Check in accordance with ISO 13616. Error code: XD19 Check of the first two characters that they correspond to a valid ISO or SEPA country code. Error code: XT73
1..1	DbtrAgt Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DbtrAgt	Name Debtor Agent Typ SCLSDDBranchAndFinancialInstitutionIdentification3	AT-13 BIC of Debtor's Bank Usage Rule: Only BIC is allowed.	BIC der Zahlstelle.	BIC of debtor agent.
1..1	FinInstnId	Name Financial Institution Identification			

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DbtrAgt ++++FinInstnId	Typ SCLSDDFinancialInstitutionIdentification5Choice			
1..1	BIC Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++DbtrAgt ++++FinInstnId +++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}		Gültigkeit des BIC anhand des SCL-Directorys. Fehlercode: XT27 Prüfung nur bei Weiterleitung der Zahlung vom SEPA-Clearer an STEP2: BIC muss ein über die Bundesbank registrierter Reachable BIC des entsprechenden SDD Services der EBA CLEARING sein. Fehlercode: PY01 Prüfung nur bei Weiterleitung an andere CSM: Debtor Agent muss berechtigt sein, Lastschriften aufzunehmen. Fehlercode: XT79	Validity of BIC using SEPA BIC directory. Error code: XT27 Check only if payment is forwarded from the SEPA-Clearer to STEP2: BIC must belong to a registered direct participant or reachable BIC of the STEP2 SDD Service Error code: PY01 Check only if the payment is forwarded from the SEPA-Clearer to another CSM: Debtor agent must be authorised to receive direct debits. Error code: XT79
0..1	UltmtDbtr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr	Name Typ Ultimate Debtor SCLSDDPartyIdentification10	Usage Rule: Mandatory if given by the Creditor in 'pain.008.001.02' and must be forwarded through the payment chain up to the Debtor.	Zwingend, falls durch den Gläubiger in pain.008 angegeben. Muss dann durch die Zahlungskette bis zum Schuldner weitergeleitet werden.	Mandatory if given by creditor in pain.008. Must then be forwarded through the payment chain to the debtor.
0..1	Nm Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr ++++Nm	Name Typ Length Pattern WhiteSpace Name Max70Text 1 .. 70 \\S+.* collapse	AT-15 Name of the Debtor Reference Party Usage Rule: "Name" is limited to 70 characters in length.	Name des abweichenden Zahlungspflichtigen.	Name of ultimate debtor
0..1	Id Document +FIToFICstmrDrctDbt ++DrctDbtTxInf	Name Typ Identification SCLSDDParty3Choice	AT-37 Identification code of the Debtor Reference Party	Identifikation des abweichenden Zahlungspflichtigen.	Identifier of ultimate debtor

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	+++UltmtDbtr ++++Id OrgId Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr ++++Id +++++OrgId	Name Typ Organisation Identification SCLSDDOrganisationIdentification4	Usage Rule: Either "BIC or BEI" or one occurrence of "Other" is allowed.		
1..1	BICorBEI Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr ++++Id +++++OrgId +++++BICorBEI	Name Typ Pattern BIC or BEI SCLSDDAnyBICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}			
1..1	Othr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr ++++Id +++++OrgId +++++Othr	Name Typ Other SCLSDDGenericOrganisationIdentification1			
1..1	Id Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr ++++Id +++++OrgId +++++Othr +++++Id	Name Typ Length Pattern WhiteSpace Identification Max35Text 1 .. 35 \\S+.* collapse			
0..1	SchmeNm Document +FIToFICstmrDrctDbt ++DrctDbtTxInf	Name Typ Scheme Name SCLSDDOrganisationIdentificationSchemeName1Choice			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+++UltmtDbtr ++++Id +++++Orgld +++++Othr +++++SchmeNm				
1..1	Cd Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr ++++Id +++++Orgld +++++Othr +++++SchmeNm +++++Cd	Name Code Typ SCLSDDExternalOrganisationIdentification1 Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr ++++Id +++++Orgld +++++Othr +++++SchmeNm +++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr ++++Id +++++Orgld +++++Othr +++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	Prvtld Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr	Name Private Identification Typ SCLSDDPersonIdentification5	Usage Rule: Either "Date and Place of Birth" or one occurrence of "Other" is allowed.		

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	++++Id +++++PrvtId DtAndPlcOfBirth Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr ++++Id +++++PrvtId +++++DtAndPlcOfBirth	Name Typ Date and Place of Birth DateAndPlaceOfBirth			
1..1	BirthDt Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr ++++Id +++++PrvtId +++++DtAndPlcOfBirth +++++BirthDt	Name Typ Pattern Birth Date ISODate [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}			
0..1	PrvcOfBirth Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr ++++Id +++++PrvtId +++++DtAndPlcOfBirth +++++PrvcOfBirth	Name Typ Length Pattern WhiteSpace Province of Birth Max35Text 1 .. 35 \S+.* collapse			
1..1	CityOfBirth Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr ++++Id +++++PrvtId +++++DtAndPlcOfBirth +++++CityOfBirth	Name Typ Length Pattern WhiteSpace City of Birth Max35Text 1 .. 35 \S+.* collapse			
1..1	CtryOfBirth	Name Typ Country of Birth CountryCode			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr ++++ld +++++Prvtld +++++DtAndPlcOfBirth +++++CtryOfBirth	Pattern [A-Z]{2,2}			
1..1	Othr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr ++++ld +++++Prvtld +++++Othr	Name Other Typ SCLSDDGenericPersonIdentification1			
1..1	Id Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr ++++ld +++++Prvtld +++++Othr +++++ld	Name Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	SchmeNm Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr ++++ld +++++Prvtld +++++Othr +++++SchmeNm	Name Scheme Name Typ SCLSDDPersonIdentificationSchemeName1 Choice			
1..1	Cd Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr	Name Code Typ SCLSDDExternalPersonIdentification1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++++Id +++++PrvtId +++++Othr +++++SchmeNm +++++Cd				
1..1	Prtry Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr ++++Id +++++PrvtId +++++Othr +++++SchmeNm +++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++UltmtDbtr ++++Id +++++PrvtId +++++Othr +++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	Purp Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Purp	Name Purpose Typ SCLSDDPurpose1Choice	AT-58 Purpose of the Collection	"verschlüsselter/ detaillierter Verwendungszweck". Plausibilisierung bei gleichzeitiger Belegung von <Purpose> und <Category Purpose> erfolgt nicht, d.h. widersprüchliche Belegungen werden vom SCL ignoriert.	Purpose of the Collection No plausibility check if <Purpose> and <Category purpose> fields both contain entries, ie SCL ignores conflicting entries.
1..1	Cd Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++Purp +++Cd	Name Code Typ ExternalPurpose1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse		Zweck der Transaktion. Belegung max.vierstellig. Bei Einlieferung in den SCL ist Belegung nicht erforderlich, bei Auslieferung kann das Feld belegt	Purpose of the Collection in accordance with the external code list (ISO 20022). Must not exceed 4 characters. No entry is required for submissions to the SCL, whereas for deliveries from the

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
				sein. Belegung gem. externer Code-Liste (ISO 20022) möglich; eine Validierung durch den SCL findet nicht statt.	SLC an entry may be made in the field. There is no validation by the SCL.
0..1	RmtInf Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++RmtInf	Name Typ Remittance Information SCLSDDRemittanceInformation1	AT-22 Remittance information from the Creditor Usage Rule: Either 'Structured' or 'Unstructured' may be present.	Verwendungszweckangaben des Zahlungsempfängers in strukturierter oder unstrukturierter Form. (Schema-Validierung)	Structured or unstructured remittance information from the creditor. (Schema validation)
1..1	Ustrd Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++RmtInf ++++Ustrd	Name Typ Length Pattern WhiteSpace Unstructured Max140Text 1 .. 140 \S+* collapse	Usage Rule: 'Unstructured' may carry structured remittance information, as agreed between the Creditor and the Debtor. Format Rule: Only one occurrence of 'Unstructured' is allowed.		
1..1	Strd Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++RmtInf ++++Strd	Name Typ Structured SCLSDDStructuredRemittanceInformation6	Usage Rule: Only one occurrence of 'Structured' is allowed. Format Rule: 'Structured' can be used, provided the tags and the data within the 'Structured' element do not exceed 140 characters in length.	Im strukturierten Verwendungszweck dürfen max. 140x vorkommen. Es zählen nur die Informationen innerhalb des Elements <Strd>. Die Elemente inklusive Inhalte innerhalb des XML-Tags <Strd> werden mitgezählt. Fehlercode: XT33 Alle ISO 20022 Feldoptionen sind erlaubt	Structured remittance information must not exceed 140 characters. Only information within the <Strd> element is counted. The elements including the contents within the tag <Strd> are also counted. Error code: XT33 All ISO 20022 field options are allowed.
0..1	CdtrRefInf Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++RmtInf ++++Strd +++++CdtrRefInf	Name Typ Creditor Reference Information SCLSDDCreditorReferenceInformation2	Usage Rule: When present, the Debtor Bank is not obliged to validate the reference information. When used both "Type" and "Reference" must be present.		
1..1		Name Typ Name Type			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Tp Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++RmtInf ++++Strd +++++CdtrRefInf +++++Tp	Typ SCLSDDCreditorReferenceType2	Usage Rule: Mandatory if 'Creditor Reference Information' is used.		
1..1	CdOrPrtry Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++RmtInf ++++Strd +++++CdtrRefInf +++++Tp +++++CdOrPrtry	Name Typ Code or Proprietary SCLSDDCreditorReferenceType1Choice			
1..1	Cd Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++RmtInf ++++Strd +++++CdtrRefInf +++++Tp +++++CdOrPrtry +++++Cd	Name Typ Code SCLSDDDocumentType3Code	Usage Rule: Only "SCOR" is allowed.		
Anwendbare Codes / Acceptable Codes					
SCOR					
0..1	Issr Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++RmtInf ++++Strd +++++CdtrRefInf +++++Tp +++++Issr	Name Typ Length Pattern WhiteSpace Issuer Max35Text 1 .. 35 \\S+.* collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Ref Document +FIToFICstmrDrctDbt ++DrctDbtTxInf +++RmtInf ++++Strd +++++CdtrRefInf ++++++Ref	Name Reference Typ Max35Text Length 1 .. 35 Pattern \S+* WhiteSpace collapse	Usage Rule: Mandatory if 'Creditor Reference Information' is used. If "Reference" contains a check digit, the receiving bank is not required to validate this. If the receiving bank validates the check digit and if this validation fails, the bank may continue its processing and send the transactions to the next party in the chain. RF Creditor Reference may be used(ISO 11649)	Referenz des Zahlungsempfängers. Wenn CdtrRefInf genutzt wird, müssen <Tp> und <Ref> belegt werden. Möglichkeit der Mitgabe einer strukturierten Gläubiger-Referenz. Aufbau dieser Referenz gemäß ISO 11649 (RFnnaaaaaaaaaaaaaaaaaaaaa); maximale Länge 25 Zeichen. Eine Validierung durch den SCL findet nicht statt.	Creditor's reference. If CdtrRefInf is used, "Tp" and "Ref" must be completed. Option of also specifying a structured creditor reference, structured according to ISO 11649 (RFnnaaaaaaaaaaaaaaaaaaaaa); maximum length of 25 characters. There is no validation by the SCL.

Nachricht

SEPA Direct Debit – Interbank Direct Debit Reject Dataset

Verwendung des Interbank Direct Debit Reject Dataset (pacs.002.001.03SCLSDD)

Diese proprietäre Nachricht ist eine Rückweisungsnachricht vom SEPA-Clearer im Fehlerfall, um den SCL-Teilnehmer über zurückgewiesene Lastschriften oder R-Nachrichten (auf Validierungs- oder Buchungsebene) zu informieren.

Die Nachricht unterstützt sowohl Sammel- also auch einzelne Rückweisungen.

Hauptunterschied der pacs.002SCL-Nachricht im Vergleich zur pacs.002-Nachricht (DS-05) gemäß SDD Interbank Implementation Guidelines:

1. Neben den ISO- bzw. SEPA- relevanten Fehlercodes werden im Feld StatusReason/Proprietary SEPA-Clearer (SCL) spezifische Fehlercodes (siehe gesonderte Aufstellung der Fehlercodes) vom SCL zurückgegeben.
2. Die Felder Instructing Agent und Instructed Agent sind im Group Header **nicht** vorgesehen.
3. Innerhalb der Datenstruktur Original Transaction Reference wird **keine** exakte Kopie zurückgegeben, sondern lediglich folgende Informationen:
 - <IntrBkSttlmAmt>: The amount of the original transaction
 - <IntrBkSttlmDt>: The original Interbank Settlement Date
 - <CdtrAgt><FinInstnId><BIC>: The original creditor agent
 - <DbtrAgt>FinInstnId><BIC>: The original debtor agent
4. Mitgabe der Information “Number of Transactions per Status” der vom SEPA-Clearer zurückgewiesenen Zahlungen in der Datenstruktur “Original Group Information and Status” (nur Negativquittung).

Group Header

Der Group Header enthält Informationen, die für die Verarbeitung der gesamten Nachricht benötigt werden.

Use of the interbank direct debit reject dataset (pacs.002.001.03SCLSDD)

This proprietary message is a rejection message from the SEPA-Clearer in the event of an error to notify the SCL participant about rejected direct debits or return ("R") messages (at the validation or settlement stage).

The message caters for bulk and single reject instructions.

Main difference between the pacs.002SCL and the 'Implementation Guideline'–compliant pacs.002 message (DS-05):

1. Along with the relevant ISO and SEPA error codes, in the status reason/proprietary field, error codes specific to the SEPA-Clearer (SCL) (see separate list of error codes) are also used by the SCL.
2. The group header does **not** contain instructing agent or instructed agent.
3. Within the original transaction reference, **no** exact copy is returned; only the following information is given.

<IntrBkSttlmAmt> the amount of the original transaction

<IntrBkSttlmDt> the original interbank settlement date

<CdtrAgt><FinInstnId><BIC> the original creditor agent

4. The 'number of transactions per status' for the payments rejected by the SEPA-Clearer is provided in the 'original group information and status' sequence (only negative acknowledgement).

Group header

The group header contains information required to process the entire message.

Nachrichtenstruktur / Message structure

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document Document	Typ Document			
1..1	FIToFIPmtStsRptSCL Document +FIToFIPmtStsRptSCL	Typ FIToFIPmtStsRptSCL			
1..1	GrpHdr Document +FIToFIPmtStsRptSCL ++GrpHdr	Name Typ Group Header SCLSDDGroupHeader5		Enthält allgemeine Informationen der Verarbeitung, die auf jede einzelne Zahlung zutreffen.	The group header contains general processing information which are needed for the processing of the whole message.
1..1	MsgId Document +FIToFIPmtStsRptSCL ++GrpHdr +++MsgId	Name Typ Pattern Message Identification SCLSDDId7 ([A-Za-z0-9][+ \? / - \(\) \.\, !]){1,35}		Referenz des SEPA-Clearers	SEPA-Clearer file reference.
1..1	CreDtTm Document +FIToFIPmtStsRptSCL ++GrpHdr +++CreDtTm	Name Typ Creation Date Time ISODateTime		Erstellungsdatum und -zeit des Bulk durch den SEPA-Clearer.	File creation date and time in the SEPA-Clearer.
0..1	InstgAgt Document +FIToFIPmtStsRptSCL ++GrpHdr +++InstgAgt	Name Typ Instructing Agent SCLSDDBranchAndFinancialInstitutionIdentification3			
1..1	FinInstnId Document +FIToFIPmtStsRptSCL ++GrpHdr +++InstgAgt ++++FinInstnId	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Choice			
1..1	BIC Document +FIToFIPmtStsRptSCL ++GrpHdr	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}			

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	+++InstgAgt +++FinInstnId +++++BIC InstdAgt Document +FIToFIPmtStsRptSCL ++GrpHdr +++InstdAgt	Name Typ Instructed Agent SCLSDDBranchAndFinancialInstitutionIdentification3			
1..1	FinInstnId Document +FIToFIPmtStsRptSCL ++GrpHdr +++InstdAgt +++++FinInstnId	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Choice			
1..1	BIC Document +FIToFIPmtStsRptSCL ++GrpHdr +++InstdAgt +++++FinInstnId +++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}			
1..1	OrgnlGrpInfAndSts Document +FIToFIPmtStsRptSCL ++OrgnlGrpInfAndSts	Name Typ Original Group Information And Status SCLSDDOriginalGroupInformation1S2		Enthält allgemeine Informationen des Original Group Headers, die auf alle Zahlungen zutreffen.	Contains general information from the original group header which is relevant for all payments.
1..1	OrgnlMsgId Document +FIToFIPmtStsRptSCL ++OrgnlGrpInfAndSts +++OrgnlMsgId	Name Typ Pattern Original Message Identification SCLSDDId7 ([A-Za-z0-9][+ ? / - : (\\) \., '])(1,35}		Die <MsgId>/<Id> des Original Bulk.	<MsgId> of the original bulk..
1..1	OrgnlMsgNmId Document +FIToFIPmtStsRptSCL ++OrgnlGrpInfAndSts +++OrgnlMsgNmId	Name Typ Length Original Message Name Identification Max35Text_Codes 1 .. 35		Nachrichtentyp des zurückgewiesenen Original Bulk.	Message name of the rejected original bulk
Anwendbare Codes / Acceptable Codes camt.056					

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
		Anwendbare Codes / Acceptable Codes			
		pac.002			
		pac.003			
		pac.004			
		pac.007			
1..1	OrgnlNbOfTx Document +FIToFIPmtStsRptSCL ++OrgnlGrpInfAndSts +++OrgnlNbOfTx	Name Original Number of Transactions Typ Max15NumericText Pattern [0-9]{1,15}		Anzahl der empfangenen Einzelzahlungen aus dem Original Bulk.	Total number of received single payments from the original bulk.
1..1	OrgnlCtrlSum Document +FIToFIPmtStsRptSCL ++OrgnlGrpInfAndSts +++OrgnlCtrlSum	Name Original Control Sum Typ DecimalNumber FractionDigits 2 TotalDigits 18 Pattern [0-9]{0,15}(\. [0-9]{0,2}){0,1}		Der Gesamtbetrag des Original Bulk in Euro.	Total amount from the original bulk in euro.
1..1	GrpSts Document +FIToFIPmtStsRptSCL ++OrgnlGrpInfAndSts +++GrpSts	Name Group Status Typ SCLSDDDTransactionGroupStatus1Code		RJCT: wird vom SEPA-Clearer vergeben, wenn es sich um eine Gesamtrückweisung eines Bulks handelt. PART: wird vom SEPA-Clearer vergeben, wenn es sich um eine Teilrückweisung eines Bulks handelt.	RJCT: displayed by SEPA-Clearer if the bulk is completely rejected. PART: displayed by SEPA-Clearer if the bulk is partially rejected.
		Anwendbare Codes / Acceptable Codes			
		PART			
		RJCT			
1..1	StsRsnInf Document +FIToFIPmtStsRptSCL ++OrgnlGrpInfAndSts +++StsRsnInf	Name Status Reason Information Typ SCLSDDDStatusReasonInformation1			
1..1	Orgtr Document +FIToFIPmtStsRptSCL ++OrgnlGrpInfAndSts +++StsRsnInf ++++Orgtr	Name Originator Typ SCLSDDDId5		Initiator der Rückweisung	Initiator of the R-transaction.
1..1	Id	Name Identification			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFIPmtStsRptSCL ++OrgnlGrpInfAndSts +++StsRsnInf ++++Orgtr +++++Id	Typ SCLSDDDParty3Choice			
1..1	Orgld Document +FIToFIPmtStsRptSCL ++OrgnlGrpInfAndSts +++StsRsnInf ++++Orgtr +++++Id ++++++Orgld	Name Typ Organisation Identification SCLSDDDOrganisationIdentification2			
1..1	BICorBEI Document +FIToFIPmtStsRptSCL ++OrgnlGrpInfAndSts +++StsRsnInf ++++Orgtr +++++Id ++++++Orgld +++++++BICorBEI	Name Typ Pattern BIC or BEI BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}		Der BIC des SEPA-Clearers (in der Produktion MARKDEFF, im Test MARKDEF0).	SEPA-Clearer's BIC (production MARKDEFF; test MARKDEF0)
1..1	Rsn Document +FIToFIPmtStsRptSCL ++OrgnlGrpInfAndSts +++StsRsnInf +++Rsn	Name Typ Reason SCLSDDDStatusReason1Choice			
1..1	Cd Document +FIToFIPmtStsRptSCL ++OrgnlGrpInfAndSts +++StsRsnInf ++++Rsn +++++Cd	Name Typ Code SCLSDDDTransactionRejectReason4Code		Wird vom SCL nicht belegt.	Left blank by SCL
Anwendbare Codes / Acceptable Codes					
ED05					

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Prtry Document +FIToFIPmtStsRptSCL ++OrgnlGrpInfAndSts +++StsRsnInf ++++Rsn +++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35		Proprietärer Fehlercode des SEPA-Clearers gemäß Liste der Bulk-Fehlercodes in den technischen Spezifikationen.	Proprietary error code of the SEPA-Clearer according to the list of error code in the technical specifications
0..1	NbOfTxPerSts Document +FIToFIPmtStsRptSCL ++OrgnlGrpInfAndSts +++NbOfTxPerSts	Name Number of Transactions Per Status Typ SCLSDDDNumberOfTransactionsPerStatus1		Angaben zu Transaktionen die vom SEPA-Clearer zurückgewiesen wurden. (Nur bei Teilrückweisungen eines Bulks belegt).	Information on transactions rejected by the SEPA-Clearer. (Only completed in the case of a partial rejection)
1..1	DtldNbOfTx Document +FIToFIPmtStsRptSCL ++OrgnlGrpInfAndSts +++NbOfTxPerSts ++++DtldNbOfTx	Name Detailed Number Of Transactions Typ Max15NumericText Pattern [0-9]{1,15}		Anzahl der Transaktionen die zurückgewiesen wurden. Nur gefüllt wenn der Group Status den Code "PART" enthält.	Number of rejected transactions. Only completed if <GrpSts> contains the code 'PART'.
1..1	DtldSts Document +FIToFIPmtStsRptSCL ++OrgnlGrpInfAndSts +++NbOfTxPerSts ++++DtldSts	Name Detailed Status Typ SCLSDDDTransactionIndividualStatus1Code		Der Status der Transaktionen. Nur gefüllt wenn der Group Status den Code "PART" enthält. Hier ist nur der Code RJCT möglich.	Status of transactions. Only completed if <GrpSts> contains the code 'PART'. Here, only the code RJCT is possible.
Anwendbare Codes / Acceptable Codes					
ACCP					
ACSC					
RJCT					
1..1	DtldCtrlSum Document +FIToFIPmtStsRptSCL ++OrgnlGrpInfAndSts +++NbOfTxPerSts ++++DtldCtrlSum	Name Detailed Control Sum Typ DecimalNumber FractionDigits 2 TotalDigits 18 Pattern [0-9]{0,15}(\. [0-9]{0,2}){0,1}		Gesamtbetrag der zurückgewiesenen Transaktionen. Nur gefüllt wenn der Group Status den Code "PART" enthält.	Total amount of the rejected transactions. Only completed if <GrpSts> contains the code 'PART'.
0..n	TxInfAndSts Document +FIToFIPmtStsRptSCL	Name Transaction Information And Status Typ SCLSDDDPaymentTransactionInformation1		Nur belegt, wenn Rückweisungen aufgrund fehlerhafter Einzeltransaktionen erfolgen.	Only completed in the case of a partial rejection

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	++TxInfAndSts StsId Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++StsId	Name Typ Pattern Status Identification SCLSDDId7 ([A-Za-z0-9][+ ? / - : (\\) \.\ , '])(1,35)		Referenznummer der Transaktion, die vom SEPA-Clearer vergeben wird.	Reference number of the transaction issued by the SEPA-Clearer.
0..1	OrgnlInstrId Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++OrgnlInstrId	Name Typ Pattern Original Instruction Identification SCLSDDId7 ([A-Za-z0-9][+ ? / - : (\\) \.\ , '])(1,35)		Die "Original Instruction Id" der zugrundeliegenden Lastschrift. Wird hier nur angegeben, wenn diese bereits in der ursprünglichen Lastschrift vorhanden war.	The "original instruction ID" of the underlying direct debit. Is only given here if it already existed in the original direct debit.
1..1	OrgnlEndToEndId Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++OrgnlEndToEndId	Name Typ Length Original End To End Identification Max35Text 1 .. 35		Die Referenz des Zahlungsempfängers (End-to-End-Id) der ursprünglichen Lastschrift.	The creditor reference (End to End ID) of the original direct debit.
1..1	OrgnlTxId Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++OrgnlTxId	Name Typ Pattern Original Transaction Identification SCLSDDId7 ([A-Za-z0-9][+ ? / - : (\\) \.\ , '])(1,35)		Die Referenz der ersten Inkassostelle der ursprünglichen Lastschrift. Bei pacs.003 = TxId Bei pacs.002 = RtrId Bei pacs.004 = StsId Bei camt.056 = CxId Bei pacs.007 = RvslId	Reference of the payment service provider of the the original direct debit. For pacs.003 = TxId For pacs.002 = StsId For pacs.004 = RtrId For camt.056 = CxId For pacs.007 = RvslId
1..1	TxSts Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++TxSts	Name Typ Transaction Status SCLSDDTransactionIndividualStatus1Code Anwendbare Codes / Acceptable Codes ACCP ACSC RJCT		Der Status der einzelnen Transaktion. Nur der Wert "RJCT" ist hier zulässig.	Status of the individual transaction. Only the code "RJCT" is allowed.
1..1	StsRsnInf Document +FIToFIPmtStsRptSCL ++TxInfAndSts	Name Typ Status Reason Information SCLSDDStatusReasonInformation2			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	+++StsRsnInf Orgtr Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++StsRsnInf ++++Orgtr	Name Typ Originator SCLSDDid5			
1..1	Id Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++StsRsnInf ++++Orgtr ++++Id	Name Typ Identification SCLSDDParty3Choice			
1..1	Orgld Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++StsRsnInf ++++Orgtr ++++Id +++++Orgld	Name Typ Organisation Identification SCLSDDOrganisationIdentification2			
1..1	BICOrBEI Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++StsRsnInf ++++Orgtr ++++Id +++++Orgld ++++++BICOrBEI	Name Typ Pattern BICOrBEI BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}		Der BIC des SEPA-Clearers, (in der Produktion MARKDEFF, im Test MARKDEF0).	SEPA-Clearer's BIC (production MARKDEFF; test MARKDEF0)
1..1	Rsn Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++StsRsnInf ++++Rsn	Name Typ Reason SCLSDDStatusReason2Choice			
		Name Code			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Cd Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++StsRsnInf ++++Rsn +++++Cd	Name Code Typ SCLSDDTransactionRejectReason3Code		Wird vom SCL nicht belegt.	Left blank by the SCL.
Anwendbare Codes / Acceptable Codes					
		AM01 AM02 AM05 DT01 ED05 MD01 MD02			
1..1	Prtry Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++StsRsnInf ++++Rsn +++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35		Fehlercode des SEPA-Clearers der Zurückgewiesenen Einzeltransaktion; Belegung mit in ISO 20022 definierten sowie proprietären Codes möglich. Feld wird bei bestimmten Fehlern wie folgt formatiert: [Code] [Leerzeichen][Fehlerhaftes XML tag]	Error code of the SEPA-Clearer if the individual transaction is rejected; may be completed using codes defined in ISO 20022 as well as proprietary codes. Field is formatted as follows in the event of certain errors: [Code] [space] [erroneous XML tag]
0..1	InstgAgt Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++InstgAgt	Name Instructing Agent Typ SCLSDDBranchAndFinancialInstitutionIdentification3			
1..1	FinInstnId Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++InstgAgt ++++FinInstnId	Name Financial Institution Identification Typ SCLSDDFinancialInstitutionIdentification5Choice			
1..1	BIC Document +FIToFIPmtStsRptSCL ++TxInfAndSts	Name BIC Typ BICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}			

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	+++InstgAgt +++FinInstnId +++++BIC InstdAgt Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++InstdAgt	Name Typ Instructed Agent SCLSDDBranchAndFinancialInstitutionIdentification3			
1..1	FinInstnId Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++InstdAgt +++++FinInstnId	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Choice			
1..1	BIC Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++InstdAgt +++++FinInstnId +++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}			
0..1	OrgnlTxRef Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++OrgnlTxRef	Name Typ Original Transaction Reference SCLSDDOrgnlTransactionReference1		Teile der Originalnachricht (falls vorhanden): IntrBkSttlmAmt: der Betrag der Originalnachricht IntrBkSttlmDt: Fälligkeitstag der Originalnachricht. CdrAgt/FinInstnId/BIC: BIC der ersten Inkassostelle.	Parts of the original message (if present): <IntrBkSttlmAmt>: the amount of the original message <IntrBkSttlm Dt>: settlement date of the original message <CdrAgt>/<FinInstnId>/<BIC>: BIC of the creditor bank
1..1	IntrBkSttlmAmt Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++OrgnlTxRef +++++IntrBkSttlmAmt	Name Typ FractionDigits TotalDigits Inclusive Pattern Interbank Settlement Amount SCLSDDCurrencyAndAmount 2 18 0 .. [0-9]{0,15}(\.[0-9]{0,2}){0,1}		Der Betrag der Originalnachricht (abhängig vom Zahlungstyp): Im pacS.003 = Interbank Settlement Amount Im pacS.004 = Returned Interbank Settlement Amount. Im pacS.002 = nicht vorhanden	Amount of the original message (depending on payment type): In pacS.003 = Interbank Settlement Amount In pacS.004 = Returned Interbank Settlement Amount. In pacS.002 = not available

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
				Im camt.056 = nicht vorhanden Im pacs.007 = Reversed Interbank Settlement Amount	In camt.056 = Original Interbank Settlement Amount In pacs.007 = Reversed Interbank Settlement Amount
1..1	IntrBkSttlmDt Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++OrgnlTxRef ++++IntrBkSttlmDt	Name Typ Interbank Settlement Date ISODate		Das Interbank Settlement Date der Originalnachricht.	The interbank settlement date of the original message.
1..1	DbtrAgt Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++OrgnlTxRef ++++DbtrAgt	Name Typ Debtor Agent SCLSDDBranchAndFinancialInstitutionIdentification3			
1..1	FinInstnId Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++OrgnlTxRef ++++DbtrAgt +++++FinInstnId	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Choice			
1..1	BIC Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++OrgnlTxRef ++++DbtrAgt +++++FinInstnId ++++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}			
1..1	CdtrAgt Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++OrgnlTxRef ++++CdtrAgt	Name Typ Creditor Agent SCLSDDBranchAndFinancialInstitutionIdentification3		BIC der ersten Inkassostelle gemäß der Originalnachricht.	BIC of the creditor agent according to the original message.

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	FinInstnId Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++OrgnTxRef ++++CdtrAgt +++++FinInstnId	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Ch oice			
1..1	BIC Document +FIToFIPmtStsRptSCL ++TxInfAndSts +++OrgnTxRef ++++CdtrAgt +++++FinInstnId ++++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}			

Nachricht

SEPA Direct Debit – Interbank Direct Debit Reject Dataset (DS-05)

Verwendung des Interbank Payment Status Report (pacs.002.001.03SDD)

Die Nachricht wird verwendet, um Rückweisungen von Lastschriften zwischen Zahlungsdienstleistern zu transportieren.

Die Nachricht berücksichtigt **nur** Rückweisungen **einzelner Lastschriften**. Rückweisungen auf Bulk-Ebene werden vom SEPA-Clearer **nicht** unterstützt.

Hinweise:

- Attribut R1 in DS-05 wird impliziert durch den 'Message Name': 'pacs.002.001', die <OrgnlMsgNmId>: 'pacs.003' und den <GrpSts>: 'PART'.
- Attribut R4 'Settlement Date for the Reject, Return or Refund' ist nicht anwendbar.
- Nachrichtenelemente unter der 'Original Transaction Reference'-Sequenz basieren auf DS-04-Attributen.

ISO Nachrichtenstruktur

Eine Rückweisungsnachricht beinhaltet:

- einen einzelnen Group Header
- einen einzelnen Original Group Information and Status
- einen oder mehrere 'Transaction Information and Status'-Sequenzen, von denen jede die Rückweisung einer Lastschrift enthält, wie in DS-05 definiert.

Group Header

Der Group Header enthält Informationen, die für die Verarbeitung der gesamten Nachricht benötigt werden.

Use of Interbank Payment Status Report (pacs.002.001.03SDD):

The message is used to reject a direct debit between payment service providers.

The message caters for **single** reject instructions **only**. Bulk-level rejects are **not** supported by the SEPA-Clearer.

Notes:

- Attribute R1 in DS-05 is implied by the ‘message name’, ‘pacs.002.001’, the <OrgnlMsgNmId> set to ‘pacs.003’ and the <GrpSts>: ‘PART’.
- Attribute R4 ‘settlement date for the reject, return or refund’ is not applicable.
- Message elements under the ‘original transaction reference’ sequence are based on DS-04 attributes.

ISO message structure

A message used to reject a direct debit instruction contains:

- a single group header
- a single original group information and status
- one or more ‘transaction information and status’ sequences each containing a direct debit rejection instruction, as defined in DS-05.

Group header

The group header contains information required to process the entire message.

Nachrichtenstruktur / Message structure

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document Document	Typ Document			
1..1	FIToFIPmtStsRpt Document +FIToFIPmtStsRpt	Typ FIToFIPaymentStatusReportV03			
1..1	GrpHdr Document +FIToFIPmtStsRpt ++GrpHdr	Name Name des abweichenden Zahlungsempfängers Typ SCLSDDGroupHeader5		Enthält allgemeine Informationen der Verarbeitung, die auf jede einzelne Zahlung zutreffen	Contains general processing information which applies to whole payment payment.
1..1	MsgId Document +FIToFIPmtStsRpt ++GrpHdr +++MsgId	Name Message Identification Typ SCLSDDId7 Pattern ([A-Za-z0-9][+ \/ \- \(\) \.\ , ']){1,35}	AT-R5 Specific reference of the bank which initiated the Rejection	Referenz-Nr. des Bulks MsgId ist Bestandteil der Doppeleinreichungskontrolle auf Dateiebene (über 15 Kalendertage eindeutige Referenz). Fehlercode: B14 Die ersten 8 bzw. 11. Stellen der MsgId müssen im IDF mit dem BIC des Instructing Agent übereinstimmen. Der Rest des Feldes ist frei verfügbar. Fehlercode: B98	Bulk reference number MsgId is part of the duplication check at bulk level (unique reference over 15 calendar days). Error code: B14 The first 8 or 11 characters of MsgId must match the BIC of the instructing agent in the IDF. The rest of the field can be freely defined. Error code: B98
1..1	CreDtTm Document +FIToFIPmtStsRpt ++GrpHdr +++CreDtTm	Name Creation Date Time Typ ISODatetime Pattern [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}[T][0-9]{2,2}: [0-9]{2,2}:[0-9]{2,2}\S*		Erstellungsdatum und -zeit des Bulks	Bulk creation date and time.
0..1	InstgAgt Document +FIToFIPmtStsRpt ++GrpHdr +++InstgAgt	Name Instructing Agent Typ SCLSDDBranchAndFinancialInstitutionIdentification3	Usage Rule: Only BIC is allowed.	Nur bei Einlieferungen in den SEPA-Clearer zu belegen. Hier ist der BIC des SCL-Teilnehmers einzustellen, der zu dem technischen Unterkonto/Sub-Account in T2 gehört, das für die Durchführung der geldlichen Verrechnung herangezogen wird.	Only to be used for submissions to the SEPA-Clearer (IDF). Allocation of the BIC of the SCL participant which is linked with the T2 sub-account assigned for settlement with the SEPA-Clearer.

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
				Bestandteil der Doppeleinreichungskontrolle (geschäftstaglich eindeutige Referenz)	Part of duplication check (unique daily reference)
1..1	FinInstnId Document +FIToFIPmtStsRpt ++GrpHdr +++InstgAgt ++++FinInstnId	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Ch oice			
1..1	BIC Document +FIToFIPmtStsRpt ++GrpHdr +++InstgAgt ++++FinInstnId +++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}		BIC muss im Input Debit File (IDF) enthalten und einreichungsberechtigt sein. Fehlercode: B10 Prufung gegen den BIC im File Header (Sending Institution) auf Einreichungsberechtigung des Kommunikationspartners. Fehlercode: B10	BIC must be contained in the input debit file (IDF). Error code: B10 Communication partner's authorisation to submit verified against the BIC in the file header (Sending Institution). Error code: B10
0..1	InstdAgt Document +FIToFIPmtStsRpt ++GrpHdr +++InstdAgt	Name Typ Instructed Agent SCLSDDBranchAndFinancialInstitutionIdentif ication3	Usage Rule: Only BIC is allowed.	Nur bei Auslieferungen aus dem SEPA-Clearer belegt. Hier ist der BIC des SCL-Teilnehmers angegeben, der zu dem technischen Unterkonto/Sub- Account in T2- gehort, das fur die Durchfuhrung der geldlichen Verrechnung herangezogen wird.	Only to be used for deliveries from the SEPA-Clearer. Allocation of the BIC of the SCL participant which is linked with the T2 sub-account assigned for settlement with the SEPA-Clearer.
1..1	FinInstnId Document +FIToFIPmtStsRpt ++GrpHdr +++InstdAgt ++++FinInstnId	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Ch oice			
1..1	BIC Document	Name Typ BIC BICIdentifier		BIC darf nur im Debit Notification File (DNF) enthalten sein. Fehlercode: B11	BIC may only be contained in the debit notification file (DNF). Error code: B11

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+FIToFIPmtStsRpt ++GrpHdr +++InstdAgt +++FinInstnId ++++BIC	Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}			
1..1	OrgnlGrpInfAndSts Document +FIToFIPmtStsRpt ++OrgnlGrpInfAndSts	Name Typ Original Group Information SCLSDDOriginalGroupInformation1		Hinweis: Reject eines ganzen Bulks wird im SEPA-Clearer nicht unterstützt.	Note: Rejection of an entire bulk is not supported by the SEPA-Clearer
1..1	OrgnlMsgId Document +FIToFIPmtStsRpt ++OrgnlGrpInfAndSts +++OrgnlMsgId	Name Typ Pattern Original Message Identification SCLSDDId7 ([A-Za-z0-9][+ ? / \- : () \. , '])(1,35)		Referenz-Nr. des Original-Bulks	Reference number (<MsgId>) of original bulk
1..1	OrgnlMsgNmId Document +FIToFIPmtStsRpt ++OrgnlGrpInfAndSts +++OrgnlMsgNmId	Name Typ Pattern Original Message Name Identification SCLSDDOrgnlMsgNmId pacs\003[A-Za-z0-9\.](0,27) PACS\003[A-Za-z0-9\.](0,27)	Usage Rule: Only pacs.003.001.02 is allowed.	Nachrichtentyp des ursprünglichen Bulks Belegung mit "pacs.003" oder "PACS.003" zulässig. (Schema-Validierung)	Original bulk name May be completed with 'pacs.003' or 'PACS.003'. (Schema validation)
1..1	GrpSts Document +FIToFIPmtStsRpt ++OrgnlGrpInfAndSts +++GrpSts	Name Typ GroupStatus SCLSDDTransactionGroupStatus1Code	AT-R1 Type of R Message Usage Rule: Only 'RJCT' and 'PART' are allowed.	Nur der Status "PART" ist erlaubt. (Schema-Validierung)	Only the status 'PART' is permitted. (Schema validation)
Anwendbare Codes / Acceptable Codes					
PART					
1..n	TxInfAndSts Document +FIToFIPmtStsRpt ++TxInfAndSts	Name Typ Transaction Information And Status SCLSDDPaymentTransactionInformation1		Mindestens eine Transaktion muss angegeben werden, da Rückweisung auf Bulkebene nicht unterstützt wird. (Schema-Validierung) Max. 100.000 Datensätze zulässig. Fehlercode: B02	At least one transaction must be given as rejection at bulk level is not supported. (Schema validation) Maximum of 100,000 data records allowed. Error code: B02
1..1	StsId Document +FIToFIPmtStsRpt	Name Typ Pattern Status Identification SCLSDDId7 ([A-Za-z0-9][+ ? / \- : () \. , '])(1,35)	Mandatory AT-R5 Specific reference of the bank that initiated the reject	Referenznummer der Bank, welche die Rückweisung initiiert hat.	Reference number of the credit institution that initiated the reject.

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++TxInfAndSts +++StsId			Status Id ist Bestandteil der Doppeleinreichungskontrolle auf Einzelsatzebene. Fehlercode: AM05	Status ID is part of the duplication check at single record level Error code: AM05
0..1	OrgnlInstrId Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlInstrId	Name Original Instruction Identification Typ SCLSDDId7 Pattern ([A-Za-z0-9][+ \? / - :\(\) \.\, '])(1,35)	Usage Rule: Mandatory if provided in the original instruction	Ursprüngliche Referenznummer des Instructing Agent ("eigene Ref."). Punkt-zu-Punkt-Referenz.	Original "Original Instruction ID" of the original bulk. Is only given if was already part of the original debit.
1..1	OrgnlEndToEndId Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlEndToEndId	Name Original End To End Identification Typ Max35Text Length 1 .. 35 Pattern \S+ WhiteSpace collapse	Mandatory AT-10 Creditor's reference of the Collection	Ursprüngliche Referenz des Zahlungsempfängers (Auftraggeberreferenz).	Creditor's original reference. End-to-End-ID of the original payment
1..1	OrgnlTxId Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxId	Name Original Transaction Identification Typ SCLSDDId7 Pattern ([A-Za-z0-9][+ \? / - :\(\) \.\, '])(1,35)	Mandatory AT-43 Creditor Bank's reference of the Collection Usage Rule: Must contain a reference that is unique over time.	Ursprüngliche Referenz der ersten Inkassostelle (Auftraggeberbank) aus der Originalnachricht. Die Originaltransaktion (pac.003) muss im SEPA Clearer verarbeitet worden sein. Fehlercode XT75 Ggf. Fehlercode XT75 oder XT74, falls Weiterleitung der Zahlung über andere CSM erfolgt.	Original reference of the creditor bank Transaction ID of the original payment. The original transaction (pac.003) must have been processed in the EPA-Clearer. Error code: XT75 Where applicable, error code XT75 or XT74 if payment is forwarded via another CSM.
1..1	TxSts Document +FIToFIPmtStsRpt ++TxInfAndSts +++TxSts	Name Transaction Status Typ SCLSDDTransactionIndividualStatus1Code	AT-R1 Type of R message Usage Rule: Only "RJCT" is allowed.	Typ der R-Nachricht. Nur der Wert "RJCT" = Rückweisung ist erlaubt. (Schema-Validierung)	Status of the R-transaction Only the value 'RJCT' = reject is permitted. (Schema validation)
Anwendbare Codes / Acceptable Codes					
RJCT					
1..1	StsRsnInf Document +FIToFIPmtStsRpt ++TxInfAndSts +++StsRsnInf	Name Status Reason Information Typ SCLSDDStatusReasonInformation1	Usage Rule: Only one Occurrence of 'Status Reason Information' is allowed. 'Status Reason Information' must be present either in	Im SEPA-Clearer ist Status Reason Information nur auf der "Transaction Information and Status"-Ebene erlaubt. (Schema-Validierung)	In the SEPA-Clearer, status reason information is only permitted in 'transaction information and status'. (Schema validation)

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Orgtr Document +FIToFIPmtStsRpt ++TxInfAndSts +++StsRsnInf ++++Orgtr	Name Typ Originator SCLSDDId5	'Original Group Information And Status' or in 'Transaction Information and Status'. Mandatory AT-R2 Identification of the type of party that initiated the reject Usage Rule: Limited to BIC to identify the bank or CSM originating the status or to 'Name' to indicate the Debtor or CSM when it has no BIC. 'Name' is limited to 70 characters in length.	Identifikation des Teilnehmers der den Reject initiiert hat. Beschränkt auf BIC, um die Bank oder das CSM zu identifizieren, oder Name um den Zahlungspflichtigen oder CSM zu kennzeichnen (falls CSM nicht über einen BIC identifizierbar ist).	Initiator of the R-transaction. Limited to BIC, in order to identify the credit institution or CSM, or to a name to indicate the debtor or CSM (if the CSM cannot be identified using a BIC)
1..1	Nm Document +FIToFIPmtStsRpt ++TxInfAndSts +++StsRsnInf ++++Orgtr +++++Nm	Name Typ Length Pattern WhiteSpace Name Max70Text 1 .. 70 \\S+.* collapse		Der Kunde, der den pacs.002 beauftragt hat. Indiziert, dass es sich um einen Refusal (= Kundenrückweisung) handelt. Darf nur belegt sein, wenn Code unter StsRsn MS02 lautet. Fehlercode XT13 BIC und Namensangabe dürfen nicht gleichzeitig vorkommen (Schema-Validierung).	Customer who initiated the pacs.002 Serves to indicate a refusal (= customer refusal). May be valid only if code under StsRsn is MS02 Error code: XT13 BIC and name cannot be entered simultaneously. (Schema validation)
1..1	Id Document +FIToFIPmtStsRpt ++TxInfAndSts +++StsRsnInf ++++Orgtr +++++Id	Name Typ Identification SCLSDDParty3Choice		BIC und Namensangabe dürfen nicht gleichzeitig vorkommen. (Schema-Validierung)	BIC and name cannot be entered simultaneously. (Schema validation)
1..1	Orgld Document +FIToFIPmtStsRpt	Name Typ Organisation Identification SCLSDDOrganisationIdentification2			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++TxInfAndSts +++StsRsnInf ++++Orgtr +++++Id ++++++Orgld				
1..1	BICorBEI Document +FIToFIPmtStsRpt ++TxInfAndSts +++StsRsnInf ++++Orgtr +++++Id ++++++Orgld +++++++BICorBEI	Name Typ Pattern BIC or BEI BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}			
1..1	Rsn Document +FIToFIPmtStsRpt ++TxInfAndSts +++StsRsnInf ++++Rsn	Name Typ Reason SCLSDDStatusReason1Choice	Mandatory AT-R3 Reason Code for Non-Acceptance	Es darf entweder nur Code oder Proprietary angegeben werden. (Schema-Validierung)	Only the code or proprietary name may be given. (Schema validation)
1..1	Cd Document +FIToFIPmtStsRpt ++TxInfAndSts +++StsRsnInf ++++Rsn +++++Cd	Name Typ Code SCLSDDTransactionRejectReason3Code	See Message Element Specifications below.	Rückweisungsgrund / Ursache der Nicht-Akzeptanz. Nur die zugelassenen Reason Codes für Refusals/Rejects dürfen hier angegeben werden. (Schema-Validierung) Der Code AC13 darf nur im B2B- Dienst genutzt werden. Fehlercode: XT33	Reason for rejection/cause of non-acceptance Only the permitted reason codes for refusals/rejects may be entered here. (Schema validation) The code 'AC13' is only allowed to be used in the SEPA B2B Direct Debit Scheme. Error code: XT33
Anwendbare Codes / Acceptable Codes					
AC01					
AC04					
AC06					
AC13					
AG01					
AG02					

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
		Anwendbare Codes / Acceptable Codes			
		AM04			
		AM05			
		BE05			
		CNOR			
		DNOR			
		ED05			
		FF01			
		MD01			
		MD02			
		MD07			
		MS02			
		MS03			
		RC01			
		RR01			
		RR02			
		RR03			
		RR04			
		SL01			
0..1	ChrgsInf Document +FIToFIPmtStsRpt ++TxInfAndSts +++ChrgsInf	Name Charges Information Typ SCLSDDChargesInformation1	Usage Rule: Only one occurrence is allowed.		
1..1	Amt Document +FIToFIPmtStsRpt ++TxInfAndSts +++ChrgsInf ++++Amt	Name Amount Typ SCLSDDCurrencyAndAmount_Tx FractionDigits 2 TotalDigits 18 Inclusive 0.01 .. 999999999.99 Pattern [0-9]{0,15}(\.[0-9]{0,2}){0,1}	AT-R8 Amount of the Interchange Fee Usage Rule: Only 'EUR' is allowed. Usage Rule: Amount must be 0.01 or more and 999999999.99 or less. Format Rule: The fractional part has a maximum of two digits.	Maximal zwei Nachkommastellen erlaubt. (Schema-Validierung) Währungskennzeichen ist immer "EUR". (Schema-Validierung) Betragsangabe muss mindestens den Wert 0.01 enthalten und darf den Wert 999999999.99 nicht übersteigen. (Schema-Validierung)	The currency symbol must be 'EUR'. (Schema validation) A maximum of two decimal places may be used. (Schema validation) Amount must not exceed permitted maximum amount (999999999.99) and must be greater than '0'. (Schema validation)

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Pty Document +FIToFIPmtStsRpt ++TxInfAndSts +++ChrgsInf ++++Pty	Name Typ Party SCLSDDBranchAndFinancialInstitutionIdentification3			
1..1	FinInstnId Document +FIToFIPmtStsRpt ++TxInfAndSts +++ChrgsInf ++++Pty +++++FinInstnId	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Choice	AT-13 BIC of the Debtor Bank Usage Rule: Only BIC is allowed.		
1..1	BIC Document +FIToFIPmtStsRpt ++TxInfAndSts +++ChrgsInf ++++Pty +++++FinInstnId ++++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}			
0..1	InstgAgt Document +FIToFIPmtStsRpt ++TxInfAndSts +++InstgAgt	Name Typ Instructing Agent SCLSDDBranchAndFinancialInstitutionIdentification3	Usage Rule: Only BIC is allowed.	Ursprünglicher Einreicher (Auftraggeber) des Bulks, in dem die Rückweisung bei Einreichung in den SEPA-Clearer enthalten war. Belegung nur im Debit Notification File (DNF) erlaubt, darf im Input Debit File (IDF) des Teilnehmers an den SCL nicht enthalten sein. Fehlercode: XT13	Original submitter of the bulk which contained the reject . Only to be completed in the Debit Notification File (DNF), not in a Input Debit File (IDF) of the participant. Error code: XT13
1..1	FinInstnId Document +FIToFIPmtStsRpt ++TxInfAndSts +++InstgAgt ++++FinInstnId	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Choice			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	BIC Document +FIToFIPmtStsRpt ++TxInfAndSts +++InstgAgt ++++FinInstnId +++++BIC	Name BIC Typ BICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}		Darf nur im DNF vorkommen. Fehlercode: XT13	Only permitted in DNF. Error code: XT13
1..1	OrgnlTxRef Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef	Name Original Transaction Reference Typ SCLSDDOrgnlTransactionReference1	Mandatory An exact copy of all attributes of the received DS-04 which is being rejected Usage Rule: The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction.	Kopie der Originalnachricht.	Copy of original message.
1..1	IntrBkSttlmAmt Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef +++++IntrBkSttlmAmt	Name Interbank Settlement Amount Typ SCLSDDCurrencyAndAmount_Tx FractionDigits 2 TotalDigits 18 Inclusive 0.01 .. 999999999.99 Pattern [0-9]{0,15}(\.([0-9]{0,2}))?{0,1}	AT-06 Amount of the Collection in euro	Der Betrag der ursprünglichen Lastschrift. Das Währungskennzeichen muss "EUR" lauten. (Schema-Validierung) Maximal zwei Nachkommastellen dürfen aufgrund des Währungskennzeichens "EUR" angegeben werden. (Schema-Validierung) Betrag darf den vorgesehenen Maximalbetrag (999999999.99) nicht übersteigen und muss größer als "0" sein. (Schema-Validierung)	The amount of the original direct debit. The currency symbol must be 'EUR'. (Schema validation) A maximum of two decimal places may be used due to currency symbol 'EUR'. (Schema validation) Amount must not exceed permitted maximum amount (999999999.99) and must be greater than '0'. (Schema validation)

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
				Hinweis: In Ermangelung einer Gesamtsumme zur Buchung auf Bulkebene, wird der zu buchende Gesamtbetrag vom SCL ausschließlich aus der Summe aller Transaktionen im Bulk (<IntrBkSttlmAmt>) ermittelt. Ggf. vorhandene Charges Information (<ChrgsInf><Amt>) werden bei der Buchung nicht berücksichtigt.	Note: In the absence of a total amount field at bulk level which could be used for settlement, the total amount to be booked will be calculated by the SCL exclusively on the basis of the sum of the amounts of the transactions included in the bulk (<IntrBkSttlmAmt>). Allocated amounts in the Charges Information fields (<ChrgsInf><Amt>) are not taken into account for the settlement.
1..1	IntrBkSttlmDt Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++IntrBkSttlmDt	Name Interbank Settlement Date Type ISODate Pattern [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}	AT-26 Settlement date of the Collection	Verarbeitungstag der ursprünglichen Lastschrift. Dieses Datum muss ein T2-Geschäftstag sein und mindestens dem aktuellen SEPA-Clearer-Geschäftstag entsprechen oder bis zu maximal 14 Kalendertagen in der Zukunft liegen. Ist das Datum bei mindestens einer Transaktion gleichlautend mit dem SEPA-Clearer-Geschäftstag und die Einreichung erfolgt nach 10:00 Uhr (SDD-Core) bzw. 11:00 Uhr (SDD B2B) oder liegt es in der Vergangenheit, wird das gesamte Bulk zurückgewiesen. Fehlercode: B15 In Ermangelung eines <IntrBkSttlmDt> auf GrpHdr-Ebene, müssen die <IntrBkSttlmDt> aller Transaktionen des Bulks in Bezug auf die <OrgnlMsgld> identisch sein. Ist dies der Fall wird das <IntrBkSttlmDt> der ersten Transaktion als Buchungsdatum herangezogen.	Settlement date of the original direct debit. Interbank settlement date must be a T2 business day and correspond to the current SEPA business day or be in the future up to 14 calendar days. If the date of at least one transaction lies in the past or if the bulk is submitted after 10.00 (= cut-off time for SEPA Core direct debits) or 11.00 (= cut-off time for SEPA B2B direct debits) and the date of at least one transaction is the same as the SEPA-Clearer business day the entire bulk will be rejected. Error code: B15 In the absence of an <IntrBkSettlmDt> at the GrpHdr level, the <IntrBkSettlmDt> of all bulk transactions related to <OrgnlMsgld> must be identical. If this is case, the <IntrBkSettlmDt> of the first transaction is used as the settlement date .

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
				<p>Liegt keine Identität der <IntrBkSttlmDt> vor, erfolgt eine Bulkrückweisung. Fehlercode. B97</p> <p>Das <IntrBkSttlmDt> der ersten Transaktion wird bei der Doppeleinreichungskontrolle herangezogen.</p> <p>Bei Auslieferungen aus dem SEPA-Clearer enthalten alle Einzeltransaktionen ein gleichlautendes <IntrBkSttlmDt>.</p> <p>Die Originaltransaktion (pacs.003) muss im SEPA Clearer verarbeitet worden sein. Fehlercode XT75</p>	<p>If no <IntrBkSettlmDt> identity exists, a bulk rejection will occur. Error code: B97</p> <p><IntrBkSttlmDt> date of the first transaction is included in the duplication check.</p> <p>In the case of deliveries from the SEPA-Clearer, all individual transactions contain an identical <IntrBkSttlmDt>.</p> <p>Original transaction (pacs.003) must have been processed in the SEPA-Clearer. Error code: XT75</p>
1..1	ReqdColltnDt Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++ReqdColltnDt	Name Typ Pattern Requested Collection Date ISODate [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}	AT-11 Due date of the Collection	Fälligkeitsdatum des Einzugs aus der ursprünglichen Lastschrift.	Due date of collection of the original direct debit.
1..1	CdtrSchmeld Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++CdtrSchmeld	Name Typ Creditor Scheme Identification SCLSDDCdtrSchmeld	AT-02 Identifier of the Creditor	Identifikation des Zahlungsempfängers aus der Originalnachricht.	Identifier of creditor from the original message
1..1	Id Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++CdtrSchmeld +++++Id	Name Typ Identification SCLSDDPrivateldentification2		Identifikation des Zahlungsempfängers aus der Originalnachricht.	Identifier of creditor from the original message
1..1	PrvtId	Name Typ Private Identification SCLSDDPrty2			

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++CdtrSchmeld +++++Id ++++++PrvtId				
1..1	Othr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++CdtrSchmeld +++++Id ++++++PrvtId +++++++Othr	Name Typ	Other SCLSDDId10		
1..1	Id Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++CdtrSchmeld +++++Id ++++++PrvtId +++++++Othr +++++++Id	Name Typ Pattern	Identification SCLSDDId8 ([A-Za-z0-9][+ \? / - : \(\) \. ' \"}]1,35)	Identifikation des Zahlungsempfängers aus der Originalnachricht.	Identifier of creditor from the original message.
1..1	SchmeNm Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++CdtrSchmeld +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm	Name Typ	Scheme Name FinancialIdentificationSchemeName2		
1..1	Prtry Document +FIToFIPmtStsRpt	Name Typ	Proprietary SCLSDDId9		

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++TxInfAndSts +++OrgnlTxRef ++++CdtrSchmeld +++++Id ++++++PrvtId ++++++Othr +++++++SchmeNm +++++++Prtry				
Anwendbare Codes / Acceptable Codes					
SEPA					
0..1	SttlmInf Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++SttlmInf	Name Settlement Information Typ SCLSDDSettlementInformation3			
1..1	SttlmMtd Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++SttlmInf +++++SttlmMtd	Name Settlement Method Typ SCLSDDSettlementMethod1Code		Information über den Settlement Mechanismus. Nur der Code "CLRG" ist zulässig. (Schema-Validierung)	Information about the settlement mechanism. Only the code "CLRG" is allowed. (Schema validation)
Anwendbare Codes / Acceptable Codes					
CLRG					
0..1	ClrSys Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++SttlmInf +++++ClrSys	Name Clearing System Typ SCLSDDClearingSystemIdentification1Choice			
1..1	Prtry Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++SttlmInf +++++ClrSys ++++++Prtry	Name Proprietary Typ Max35Text_Prtry Length 1 .. 35 Pattern \S+.* WhiteSpace collapse		Kennzeichen für das Clearing System. Für den SEPA-Clearer ist nur der Wert "SCL" zu verwenden. (Schema-Validierung)	Code for the clearing system. For the SEPA-Clearer, only the code "SCL" is to be used. (Schema validation)

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
Anwendbare Codes / Acceptable Codes					
SCL					
1..1	PmtTplnf Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++PmtTplnf	Name Payment Type Information Typ SCLSDDPaymentTypeInformation6	AT-20 Identification code of the Scheme AT-20 Identification code of the B2B Scheme AT-21 Transaction / Sequence Type AT-59 Category purpose of the Collection	Kennzeichnung, ob Lastschrift des Core- oder des B2B-Verfahrens.	
1..1	SvcLvl Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++PmtTplnf +++++SvcLvl	Name Service Level Typ SCLSDDServiceLevel2Choice			
1..1	Cd Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++PmtTplnf +++++SvcLvl +++++Cd	Name Code Typ SCLSDDServiceLevel1Code		Im SEPA-Clearer ist nur der Code "SEPA" erlaubt. (Schema-Validierung)	In the SEPA-Clearer, only the code 'SEPA' is allowed. (Schema validation)
Anwendbare Codes / Acceptable Codes					
SEPA					
1..1	LclInstrm Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++PmtTplnf +++++LclInstrm	Name Local Instrument Typ SCLSDDLocalInstrument1Choice			
1..1	Cd	Name Code Typ ExternalLocalInstrument1Code		Belegung gem. Originalzahlung.	Specified according to original message.

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++PmtTplnf +++++LclInstrm ++++++Cd	Length 1 .. 35		Es dürfen nur die Werte "CORE" oder "B2B" enthalten sein (Schema-Validierung). In einem COR-File dürfen nur CORE- Bulks und in einem B2B-File nur B2B-Bulks enthalten sein. Fehlercode: XT43 Eine gemischte Einreichung von B2B- und CORE-Lastschriften in einem Bulk ist nicht zulässig. Fehlercode: XT43 Die Originaltransaktion (pacs.003) muss im SEPA Clearer verarbeitet worden sein. Fehlercode XT75	May only contain the codes "CORE" or "B2B". (Schema validation) In a COR file only CORE bulks are permitted. In a B2B file only B2B bulks are permitted. Error code: XT43 Mixed submission of B2B and CORE direct debits in a single file is not permitted. Error code: XT43 Original transaction (pacs.003) must have been processed in the SEPA-Clearer. Error code: XT75
Anwendbare Codes / Acceptable Codes					
B2B					
CORE					
1..1	SeqTp Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++PmtTplnf +++++SeqTp	Name Type Sequence Type SCLSDDSequenceType1Code		Lastschrift-Typ: FNAL: letztmalig FRST: erstmalig OOFF: einmalig RCUR: wiederholend (Schema-Validierung)	Direct debit type: FNAL: final FRST: first OOFF: one-off RCUR: recurring (Schema validation)
Anwendbare Codes / Acceptable Codes					
FNAL					
FRST					
OOFF					
RCUR					
0..1	CtgyPurp Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++PmtTplnf +++++CtgyPurp	Name Type Category Purpose CategoryPurpose1Choice		Über das Schema hinaus sind keine weiteren fachlichen Prüfungen vorgesehen.	No additional checks are performed in addition to schema validation.

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Cd Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++PmtTplnf +++++CtgyPurp ++++++Cd	Name Code Typ ExternalCategoryPurpose1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++PmtTplnf +++++CtgyPurp ++++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	MndtRltdInf Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++MndtRltdInf	Name Mandate Related Information Typ SCLSDDMandateRelatedInformation1	AT-01 Unique Mandate reference AT-16 Placeholder for the electronic signature data, if applicable AT-17 The type of Mandate (paper or e-Mandate) AT-18 Identifier of the original Creditor who issued the Mandate AT-19 Unique mandate reference as given by the original creditor who issued the mandate AT-24 Reason for Amendment of the Mandate AT-25 Signing date of the Mandate AT-60 Reference of the validation made by the Debtor Bank (if present in DS-03)	Eindeutige Mandatsreferenz. Platzhalter für die elektronische Signatur, falls vorhanden. Identifikator des ursprünglichen Zahlungsempfängers, der das Mandat herausgegeben hat. Eindeutige Mandatsreferenz wie durch den ursprünglichen Zahlungsempfänger gegeben, der das Mandat herausgegeben hat. Ursache für Änderung des Mandats. Unterschriftsdatum des Mandats.	Unique mandate reference. Placeholder for electronic signature, where available Identifier of original creditor who issued the mandate. Unique mandate reference, as specified by original creditor who issued the mandate. Reason for changing mandate. Date when mandate was signed.
1..1	MndtId	Name Mandate Identification		Eindeutige Mandatsreferenz.	Unique mandate reference.

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++MndtRltdInf +++++Mndtld	Typ Pattern SCLSDDId8 ([A-Za-z0-9][+ \?/ -:\ (\) \.\ ' \s]){1,35}			
1..1	DtOfSgntr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++MndtRltdInf +++++DtOfSgntr	Name Typ Pattern Date Of Signature ISODate [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}		Unterschriftsdatum des Mandats.	Date when mandate was signed.
0..1	AmdmntInd Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInd	Name Typ Amendment Indicator TrueFalseIndicator		Belegung gemäß Originaltransaktion	Copy of the original message.
0..1	AmdmntInfDtls Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtls	Name Typ Amendment Information Details SCLSDDAmendmentInformationDetails1		Belegung gemäß Originaltransaktion.	Copy of the original message.
0..1	OrgnlMndtld Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtls ++++++OrgnlMndtld	Name Typ Pattern Original Mandate Identification SCLSDDId8 ([A-Za-z0-9][+ \?/ -:\ (\) \.\ ' \s]){1,35}		Eindeutige Mandatsreferenz wie durch den ursprünglichen Zahlungsempfänger gegeben, der das Mandat herausgegeben hat.	Unique mandate reference as specified by the original creditor who issued the mandate..
0..1	OrgnlCdtrSchmeld Document +FIToFIPmtStsRpt	Name Typ Original Creditor Scheme Identification SCLSDDCdrSchmeld1			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++TxInfAndSts +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlCdtrSchmeld				
0..1	Nm Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlCdtrSchmeld +++++++Nm	Name Name Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse			
0..1	Id Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlCdtrSchmeld +++++++Id	Name Identification Typ SCLSDDPriateIdentification			
1..1	PrvtId Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlCdtrSchmeld +++++++Id +++++++PrvtId	Name Private Identification Typ SCLSDDPrtY1			
1..1	Othr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++MndtRltdInf	Name Other Typ SCLSDDI4			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+++++AmdmntInfDtIs +++++OrgnCctrSchmeld +++++Id +++++PrvtId +++++Othr				
1..1	Id Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++MndtRltdInf +++++AmdmntInfDtIs +++++OrgnCctrSchmeld +++++Id +++++PrvtId +++++Othr +++++Id	Name Typ Pattern Identification SCLSDDId8 ([A-Za-z0-9][+ / \- :\(\/)\ \- ' \"s]){1,35}			
1..1	SchmeNm Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++MndtRltdInf +++++AmdmntInfDtIs +++++OrgnCctrSchmeld +++++Id +++++PrvtId +++++Othr +++++SchmeNm	Name Typ Scheme Name FinancialIdentificationSchemeName2			
1..1	Prtry Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++MndtRltdInf +++++AmdmntInfDtIs +++++OrgnCctrSchmeld +++++Id +++++PrvtId +++++Othr	Name Typ Proprietary SCLSDDId9		Nur "SEPA" ist zulässig (Schema-Validierung).	Only the code 'SEPA' is allowed. (Schema validation)

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+++++++SchmeNm +++++++Prtry				
		Anwendbare Codes / Acceptable Codes			
		SEPA			
0..1	OrgnIDbtrAcct Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++MndtRItIdInf +++++AmdmntInfDtIs +++++OrgnIDbtrAcct	Name Original Debtor Account Typ SCLSDDCashAccount8			
1..1	Id Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++MndtRItIdInf +++++AmdmntInfDtIs +++++OrgnIDbtrAcct +++++Id	Name Identification Typ SCLSDDAccountIdentification4Choice			
1..1	IBAN Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++MndtRItIdInf +++++AmdmntInfDtIs +++++OrgnIDbtrAcct +++++Id +++++IBAN	Name IBAN Typ IBANIdentifier Pattern [a-zA-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}			
1..1	Othr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++MndtRItIdInf +++++AmdmntInfDtIs +++++OrgnIDbtrAcct	Name Other Typ SCLSDDOrgnIDbtrAcctOther2			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	++++++Id ++++++Othr Id Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntlnfDtls ++++++OrgnlDbtrAcct ++++++Id ++++++Othr ++++++Id	Name Identification Typ Max34Text Length 1 .. 34 Pattern \S+.* WhiteSpace collapse			
0..1	OrgnlDbtrAgt Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntlnfDtls ++++++OrgnlDbtrAgt	Name Original Debtor Agent Typ SCLSDDOrgnlDbtrAgt			
1..1	FinInstnld Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntlnfDtls ++++++OrgnlDbtrAgt ++++++FinInstnld	Name Financial Institution Identification Typ SCLSDDOrgnlDbtrAgt1			
1..1	BIC Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntlnfDtls ++++++OrgnlDbtrAgt ++++++FinInstnld ++++++BIC	Name BIC Typ BICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Othr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnIDbtrAgt +++++++FinInstnId +++++++Othr	Name Other Typ SCLSDDOrgnIDbtrAgtOther2			
1..1	Id Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnIDbtrAgt +++++++FinInstnId +++++++Othr +++++++Id	Name Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	ElectrcSgnt Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++MndtRltdInf +++++ElectrcSgnt	Name Electronic Signature Typ Max1025Text Length 1 .. 1025 Pattern \S+.* WhiteSpace collapse			
0..1	RmtInf Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++RmtInf	Name Remittance Information Typ SCLSDDRemittanceInformation1	AT-22 Remittance information	Strukturierter oder unstrukturierter Verwendungszweck. (Schema-Validierung)	Structured or unstructured remittance information. (Schema validation)
1..1	Ustrd Document +FIToFIPmtStsRpt	Name Unstructured Typ Max140Text Length 1 .. 140 Pattern \S+.*			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++TxInfAndSts +++OrgnlTxRef ++++RmtInf +++++Ustrd	WhiteSpace collapse			
1..1	Strd Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++RmtInf +++++Strd	Name Typ Structured SCLSDDStructuredRemittanceInformation6		Im strukturierten Verwendungszweck dürfen max. 140x vorkommen. Es zählen nur die Informationen innerhalb des Elements <Strd>. Die Elemente inklusive Inhalte innerhalb des XML-Tags <Strd> werden mitgezählt. Fehlercode: XT33. Alle ISO 20022 Feldoptionen sind erlaubt.	Structured remittance information must not exceed 140 characters. Only information within the <Strd> element is counted. The elements including the contents within the tag <Strd> are also counted. Error code: XT33 All ISO 20022 field options are allowed
0..1	CdtrRefInf Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++RmtInf +++++Strd ++++++CdtrRefInf	Name Typ Creditor Reference Information SCLSDDCreditorReferenceInformation2			
1..1	Tp Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++RmtInf +++++Strd ++++++CdtrRefInf +++++++Tp	Name Typ Type SCLSDDCreditorReferenceType2			
1..1	CdOrPrtry Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++RmtInf +++++Strd	Name Typ Code or Proprietary SCLSDDCreditorReferenceType1Choice			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	<p>+++++CdtrRefInf +++++Tp +++++CdOrPrtry</p> <p>Cd</p> <p>Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++RmtInf +++++Strd +++++CdtrRefInf +++++Tp +++++CdOrPrtry +++++Cd</p>	<p>Name Code Typ SCLSDDDocumentType3Code</p>			
Anwendbare Codes / Acceptable Codes					
SCOR					
0..1	<p>Issr</p> <p>Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++RmtInf +++++Strd +++++CdtrRefInf +++++Tp +++++Issr</p>	<p>Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse</p>			
1..1	<p>Ref</p> <p>Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++RmtInf +++++Strd +++++CdtrRefInf +++++Ref</p>	<p>Name Reference Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse</p>			
0..1	<p>UltmtDbtr</p> <p>Document +FIToFIPmtStsRpt ++TxInfAndSts</p>	<p>Name Ultimate Debtor Typ SCLSDDPartyIdentification10</p>	<p>AT-15 Name of the Debtor Reference Party AT-37 Identification code of the Debtor</p>		

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	+++OrgnlTxRef ++++UltmtDbtr Nm Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtDbtr +++++Nm	Name Typ Name Length Max70Text Pattern 1 .. 70 WhiteSpace \S+.* collapse	Reference Party	Name des abweichenden Zahlers	Name of ultimate debtor
0..1	PstlAdr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtDbtr +++++PstlAdr	Name Typ Postal Address Type SCLSDDPPostalAddress1			
0..1	Ctry Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtDbtr +++++PstlAdr ++++++Ctry	Name Typ Country Pattern CountryCode [A-Z]{2,2}			
0..2	AdrLine Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtDbtr +++++PstlAdr ++++++AdrLine	Name Typ Address Line Length Max70Text Pattern 1 .. 70 WhiteSpace \S+.* collapse			
0..1	Id Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtDbtr +++++Id	Name Typ Identification Type SCLSDDPParty4Choice		Identifikation des abweichenden Zahlers	Identifier of ultimate debtor

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	OrgId Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++OrgId	Name Typ Organisation Identification SCLSDDOrganisationIdentification4			
1..1	BICorBEI Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++OrgId ++++++BICorBEI	Name Typ Pattern BIC or BEI SCLSDDAnyBICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}			
1..1	Othr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++OrgId ++++++Othr	Name Typ Other SCLSDDGenericOrganisationIdentification1			
1..1	Id Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++OrgId ++++++Othr ++++++Id	Name Typ Length Pattern WhiteSpace Identification Max35Text 1 .. 35 \\S+.* collapse			
0..1	SchmeNm	Name Typ Scheme Name SCLSDDOrganisationIdentificationSchemeN			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++Orgld +++++++Othr +++++++SchmeNm	ame1Choice			
1..1	Cd Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++Orgld +++++++Othr +++++++SchmeNm +++++++Cd	Name Code Typ SCLSDDExternalOrganisationIdentification1 Code Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++Orgld +++++++Othr +++++++SchmeNm +++++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++Orgld +++++++Othr +++++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	PrvtId Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId	Name Typ Private Identification SCLSDDPersonIdentification5			
1..1	DtAndPlcOfBirth Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId ++++++DtAndPlcOfBirth	Name Typ Date and Place of Birth DateAndPlaceOfBirth			
1..1	BirthDt Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId ++++++DtAndPlcOfBirth ++++++BirthDt	Name Typ Pattern Birth Date ISODate [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}			
0..1	PrvcOfBirth Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId ++++++DtAndPlcOfBirth ++++++PrvcOfBirth	Name Typ Length Pattern WhiteSpace Province of Birth Max35Text 1 .. 35 \\S+.* collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	CityOfBirth Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth +++++++CityOfBirth	Name City of Birth Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	CtryOfBirth Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth +++++++CtryOfBirth	Name Country of Birth Typ CountryCode Pattern [A-Z]{2,2}			
1..1	Othr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++Othr	Name Other Typ SCLSDDGenericPersonIdentification1			
1..1	Id Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++Othr +++++++Id	Name Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	SchmeNm Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm	Name Scheme Name Typ SCLSDDPersonIdentificationSchemeName1 Choice			
1..1	Cd Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm +++++++Cd	Name Code Typ SCLSDDExternalPersonIdentification1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm +++++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++UltmtDbtr +++++Id ++++++PrvtId	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	+++++Othr +++++Issr CtryOfRes Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtDbtr +++++CtryOfRes	Name Typ Pattern Country of Residence CountryCode [A-Z]{2,2}			
1..1	Dbtr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Dbtr	Name Typ Debtor SCLSDDPartyIdentification9	AT-14 Name of the Debtor AT-09 Address of the Debtor AT-27 Debtor identification code	Name des Zahlers Adresse des Zahlers Identifikation des Zahlers	Debtor name. Debtor address. Debtor identifier.
1..1	Nm Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Dbtr +++++Nm	Name Typ Length Pattern WhiteSpace Name Max70Text 1 .. 70 \\S+.* collapse		Name des Zahlers oder Ersatzinformationen gemäß Originalnachricht	Name of debtor or additional informations according to the original message
0..1	PstlAdr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Dbtr +++++PstlAdr	Name Typ Postal Address SCLSDDPPostalAddress1		Adresse des Zahlers	Address of debtor.
0..1	Ctry Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Dbtr +++++PstlAdr +++++Ctry	Name Typ Pattern Country CountryCode [A-Z]{2,2}			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..2	AdrLine Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Dbtr +++++PstlAdr ++++++AdrLine	Name Address Line Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse			
0..1	Id Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Dbtr +++++Id	Name Identification Typ SCLSDDParty4Choice		Identifikation des Zahlers Entweder 'Organisation Identification' oder 'Private Identification' müssen ausgewählt werden. (Schema-Validierung)	Identifier of debtor. Either 'Organisation Identification' or 'Private Identification' must be selected (Schema validation)
1..1	Orgld Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Dbtr +++++Id ++++++Orgld	Name Organisation Identification Typ SCLSDDOrganisationIdentification4		Alle ISO 20022 Feldoptionen sind erlaubt.	All ISO 20022 field options are allowed.
1..1	BICorBEI Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Dbtr +++++Id ++++++Orgld +++++++BICorBEI	Name BIC or BEI Typ SCLSDDAnyBICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}			
1..1	Othr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Dbtr +++++Id	Name Other Typ SCLSDDGenericOrganisationIdentification1			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	+++++OrgId +++++Othr Id Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Dbtr ++++Id +++++OrgId +++++Othr +++++Id	Name Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	SchmeNm Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Dbtr ++++Id +++++OrgId +++++Othr +++++SchmeNm	Name Scheme Name Typ SCLSDDOrganisationIdentificationSchemeName1Choice			
1..1	Cd Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Dbtr ++++Id +++++OrgId +++++Othr +++++SchmeNm +++++Cd	Name Code Typ SCLSDDExternalOrganisationIdentification1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Dbtr	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+++++Id +++++OrgId +++++Othr +++++SchmeNm +++++Prtry				
0..1	Issr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Dbtr +++++Id +++++OrgId +++++Othr +++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	PrvtId Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Dbtr +++++Id +++++PrvtId	Name Private Identification Typ SCLSDDPersonIdentification5		'Identification Type' unter 'Other Identifikation' darf nur den Wert 'SEPA' enthalten. (Schema-Validierung) Alle ISO 20022 Feldoptionen sind erlaubt.	'Identification Type' unter 'Other Identifikation' may only contain the code 'SEPA'. (Schema validation) All ISO 20022 field options are allowed.
1..1	DtAndPlcOfBirth Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Dbtr +++++Id +++++PrvtId +++++DtAndPlcOfBirth	Name Date and Place of Birth Typ DateAndPlaceOfBirth			
1..1	BirthDt Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Dbtr +++++Id	Name Birth Date Typ ISODate Pattern [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	<p>+++++PrvtId +++++DtAndPlcOfBirth +++++BirthDt</p> <p>PrvcOfBirth</p> <p>Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef +++Dbtr +++++Id +++++PrvtId +++++DtAndPlcOfBirth +++++PrvcOfBirth</p>	<p>Name Province of Birth Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse</p>			
1..1	<p>CityOfBirth</p> <p>Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef +++Dbtr +++++Id +++++PrvtId +++++DtAndPlcOfBirth +++++CityOfBirth</p>	<p>Name City of Birth Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse</p>			
1..1	<p>CtryOfBirth</p> <p>Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef +++Dbtr +++++Id +++++PrvtId +++++DtAndPlcOfBirth +++++CtryOfBirth</p>	<p>Name Country of Birth Typ CountryCode Pattern [A-Z]{2,2}</p>			
1..1	<p>Othr</p> <p>Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef +++Dbtr</p>	<p>Name Other Typ SCLSDDGenericPersonIdentification1</p>			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	+++++Id +++++PrvtId +++++Othr Id Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef +++Dbtr +++++Id +++++PrvtId +++++Othr +++++Id	Name Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	SchmeNm Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef +++Dbtr +++++Id +++++PrvtId +++++Othr +++++SchmeNm	Name Scheme Name Typ SCLSDDPersonIdentificationSchemeName1 Choice			
1..1	Cd Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef +++Dbtr +++++Id +++++PrvtId +++++Othr +++++SchmeNm +++++Cd	Name Code Typ SCLSDDExternalPersonIdentification1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++++Dbtr +++++Id ++++++PrvtId ++++++Othr ++++++SchmeNm ++++++Prtry				
0..1	Issr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++Dbtr +++++Id ++++++PrvtId ++++++Othr ++++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	DbtrAcct Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++DbtrAcct	Name Debtor Account Typ SCLSDDCashAccount7	AT-07 Account number (IBAN) of the Debtor		
1..1	Id Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++DbtrAcct +++++Id	Name Identification Typ SCLSDDAccountIdentification3Choice			
1..1	IBAN Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++DbtrAcct +++++Id ++++++IBAN	Name IBAN Typ IBANIdentifier Pattern [a-zA-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}		Kontonummer des Zahlers	Account number of debtor.
1..1	DbtrAgt	Name Debtor Agent Typ SCLSDDBranchAndFinancialInstitutionIdentif	AT-13 BIC of the Debtor Bank	BIC der Zahlstelle.	BIC of the debtor agent

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++DbtrAgt	ication3			
1..1	FinInstnld Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++DbtrAgt +++++FinInstnld	Name Typ	Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Ch oice		
1..1	BIC Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++DbtrAgt +++++FinInstnld +++++BIC	Name Typ Pattern	BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}	BIC der Zahlstelle. Debtor Agent BIC ist Bestandteil der Doppeleinreichungskontrolle auf Einzelsatzebene. Fehlercode: AM05	BIC of the debtor agent. Debtor agent BIC is included in the duplication check at single record level. Error code: AM05
1..1	CdtrAgt Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++CdtrAgt	Name Typ	Creditor Agent SCLSDDBranchAndFinancialInstitutionIdentif ication3	AT-12 BIC of the Creditor Bank	BIC der ersten Inkassostelle. BIC of the creditor agent.
1..1	FinInstnld Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++CdtrAgt +++++FinInstnld	Name Typ	Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Ch oice		
1..1	BIC Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef	Name Typ Pattern	BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}	Gültigkeit des BIC anhand des SCL-Directory. Fehlercode: XT27 Ggf. Fehlercode XT74, falls Weiterleitung der Zahlung über	Validity check of BIC using SCL-Directory. Error code: XT27 Where applicable, error code XT74, if payment is forwarded via

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++++CdtrAgt +++++FinInstnId +++++BIC			andere CSM erfolgt. Die Originaltransaktion (pac.003) muss im SEPA Clearer verarbeitet worden sein. Fehlercode XT75	the other CSMs. Original transaction (pac.003) must have been processed in the SEPA-Clearer. Error code: XT75
1..1	Cdtr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Cdtr	Name Creditor Typ SCLSDDId2	AT-03 Name of the Creditor AT-05 Address of the Creditor		
1..1	Nm Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Cdtr ++++Nm	Name Name Typ Max70Text Length 1 .. 70 Pattern \S+* WhiteSpace collapse		Name des Zahlungsempfängers.	Name of creditor.
0..1	PstlAdr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Cdtr +++++PstlAdr	Name Postal Adress Typ SCLSDDPostalAddress1		Adresse des Zahlungsempfängers	Address of creditor
0..1	Ctry Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++Cdtr +++++PstlAdr +++++Ctry	Name Country Typ CountryCode Pattern [A-Z]{2,2}			
0..2	AdrLine Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef	Name Address Line Typ Max70Text Length 1 .. 70 Pattern \S+* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	++++Cdtr +++++PstlAdr +++++AdrLine CdtrAcct Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++CdtrAcct	Name Typ Creditor Account SCLSDDCashAccount7	AT-04 Account number (IBAN) of the Creditor	Kontonummer des Zahlungsempfängers.	Account number of creditor.
1..1	Id Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++CdtrAcct +++++Id	Name Typ Identification SCLSDDAccountIdentification3Choice			
1..1	IBAN Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++CdtrAcct +++++Id +++++IBAN	Name Typ Pattern IBAN IBANIdentifier [a-zA-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}		Kontonummer (IBAN) des Zahlungsempfängers.	IBAN of the creditor.
0..1	UltmtCdtr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtCdtr	Name Typ Ultimate Creditor SCLSDDPartyIdentification10	AT-38 Name of the Creditor Reference Party AT-39 Identification code of the Creditor Reference Party		
0..1	Nm Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtCdtr +++++Nm	Name Typ Length Pattern WhiteSpace Name Max70Text 1 .. 70 \\S+.* collapse		Name des abweichenden Zahlungsempfängers	Name of ultimate creditor
0..1	PstlAdr	Name Postal Address			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtCdtr +++++PstlAdr	Typ SCLSDDPostalAddress1			
0..1	Ctry Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtCdtr +++++PstlAdr +++++Ctry	Name Typ Pattern Country CountryCode [A-Z]{2,2}			
0..2	AdrLine Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtCdtr +++++PstlAdr +++++AdrLine	Name Typ Length Pattern WhiteSpace Address Line Max70Text 1 .. 70 \S+.* collapse			
0..1	Id Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtCdtr +++++Id	Name Typ Identification SCLSDDParty4Choice		Identifikation des abweichenden Zahlungsempfängers	Identifier of ultimate creditor
1..1	OrgId Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtCdtr +++++Id +++++OrgId	Name Typ Organisation Identification SCLSDDOrganisationIdentification4			
1..1	BICorBEI	Name BIC or BEI			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++Orgld +++++++BICOrBEI	Typ Pattern	SCLSDDAnyBICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}		
1..1	Othr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++Orgld +++++++Othr	Name Typ	Other SCLSDDGenericOrganisationIdentification1		
1..1	Id Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++Orgld +++++++Othr +++++++Id	Name Typ Length Pattern WhiteSpace	Identification Max35Text 1 .. 35 \ <s+.* </s+.* collapse		
0..1	SchmeNm Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++Orgld +++++++Othr +++++++SchmeNm	Name Typ	Scheme Name SCLSDDOrganisationIdentificationSchemeName1Choice		
1..1	Cd Document	Name Typ	Code SCLSDDExternalOrganisationIdentification1 Code		

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++UltmtCdtr +++++Id ++++++Orgld +++++++Othr +++++++SchmeNm +++++++Cd	Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++UltmtCdtr +++++Id ++++++Orgld +++++++Othr +++++++SchmeNm +++++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++UltmtCdtr +++++Id ++++++Orgld +++++++Othr +++++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	Prvtld Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++UltmtCdtr +++++Id ++++++Prvtld	Name Private Identification Typ SCLSDDPersonIdentification5			
1..1	DtAndPlcOfBirth	Name Date and Place of Birth Typ DateAndPlaceOfBirth			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth				
1..1	BirthDt Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth +++++++BirthDt	Name Birth Date Typ ISODate Pattern [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}			
0..1	PrvcOfBirth Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth +++++++PrvcOfBirth	Name Province of Birth Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	CityOfBirth Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth +++++++CityOfBirth	Name City of Birth Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	CtryOfBirth	Name Country of Birth Typ CountryCode			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth +++++++CtryOfBirth	Pattern [A-Z]{2,2}			
1..1	Othr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++PrvtId +++++++Othr	Name Typ Other SCLSDDGenericPersonIdentification1			
1..1	Id Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++PrvtId +++++++Othr +++++++Id	Name Typ Length Pattern WhiteSpace Identification Max35Text 1 .. 35 \\S+.* collapse			
0..1	SchmeNm Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm	Name Typ Scheme Name SCLSDDPersonIdentificationSchemeName1 Choice			
1..1	Cd	Name Typ Code SCLSDDExternalPersonIdentification1Code			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++UltmtCdtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm +++++++Cd	Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++UltmtCdtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm +++++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++UltmtCdtr +++++Id ++++++PrvtId +++++++Othr +++++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	CtryOfRes Document +FIToFIPmtStsRpt ++TxInfAndSts +++OrgnITxRef ++++UltmtCdtr +++++CtryOfRes	Name Country of Residence Typ CountryCode Pattern [A-Z]{2,2}			

Nachricht

SEPA Direct Debit – Payment Cancellation Request

Verwendung des Payment Cancellation Request (camt.056.001.01SDD)

Diese Nachricht wird verwendet, um einzelne Lastschriften – vor Settlement – zu stornieren. Sie wird vom Zahlungsdienstleister des Zahlungsempfängers zum Zahlungsdienstleister des Zahlers transportiert. Der Nachrichtentyp ist nicht Bestandteil der EPC-Spezifikationen, wird jedoch aus Gründen der Interoperabilität mit anderen CSM dennoch unterstützt. Die Stornierung eines kompletten Bulks ist nicht möglich.

Da der Rückruf nur vor Settlement erfolgen kann, ist er selbst stets buchungsrelevant. Der Zahlungsdienstleister des Zahlers wird mit dem Gegenwert der stornierten Original-Lastschrift am <Interbank Settlement Date> zwar belastet, aber es erfolgt eine Umkehrbuchung (Wiedergutschrift) im selben Buchungsfenster. Entsprechend erhält der Einreicher der Original-Lastschrift zusammen mit der Gutschrift des eingereichten Original-Bulks die Belastung der Stornierung (jeweils Bruttoprinzip).

Auf Grund seiner Natur als Stornierungsnachricht gibt es zum camt.056.001.01 im SDD-Dienst – im Gegensatz zum SCT-Dienst – keinen pacs.004.001.02 und keinen camt.029.001.03 als positive bzw. negative Antwort.

Der SEPA-Clearer nimmt eine Doppeleinreichungskontrolle und eine Cross-Referenzierung vor. So wird z. B. geprüft, ob die Originalzahlung über den SEPA-Clearer zum angegebenen Zeitpunkt abgewickelt wurde oder bereits eine Stornierung oder Rückweisung für diese Originalzahlung vorgelegen hat.

Die Nachricht ist einlieferungsseitig Bestandteil des Input Debit Files (IDF), auslieferungsseitig Bestandteil des Debit Notification Files (DNF).

ISO Nachrichtenstruktur

Ein Payment Cancellation Request beinhaltet:

- ein einzelnes „Assignment“ (äquivalent dem Group Header in pacs-Nachrichtentypen)
- ein „Control Data“
- ein „Underlying“, das eine oder mehrere „Transaction Information“-Sequenzen enthält, die jeweils die Transaktionsdaten einer einzelnen zu Grunde liegenden Lastschrift beinhalten.

Assignment

Das Assignment enthält Informationen, die für die Verarbeitung der gesamten Nachricht benötigt werden.

Use of “Payment Cancellation Request” (camt.056.001.01)

This message is used to cancel individual direct debits prior to settlement. The message is transported from the creditor bank to the debtor bank. It is not specified by the EPC but is supported for reasons of interoperability with other CSMs. It is not possible to cancel an entire bulk payment.

As the cancellation can only be effected prior to settlement, it is always booking-relevant. The debtor bank is debited with the settlement amount of the cancelled original direct debit on the <Interbank Settlement Date>, however the amount is refunded promptly within the same settlement window. Correspondingly, the submitter of the original direct debit receives the debit entry of the cancellation amount together with the credit entry for the submitted original bulk (gross settlement principle in both instances).

In contrast to the SCT service, owing to the fact that the payment is cancelled before settlement, there is no pacs.004.001.02 or camt.029.001.03 as a positive or negative response to camt.056.001.01 in the SDD service.

The SEPA-Clearer carries out a duplication check and make a cross reference check. For example, check is made as to whether the original payment was processed on the given date in the SEPA-Clearer or whether a cancellation request or reject has already been submitted for this original payment.

The message is a component of the input debit file (IDF) on the submitter side and a component of the debit notification file (DNF) on the delivery side.

ISO message structure

A payment cancellation request contains:

- a single “assignment” (equivalent the group header in pacs-messages)
- control data
- an ‘underlying’ element, consisting of one or more ‘transaction information’ sequences, each of which contains the transaction data of an individual underlying direct debit.

Assignment

The “assignment” contains information required to process the entire message.

Nachrichtenstruktur / Message structure

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document Document	Typ Document			
1..1	FIToFIPmtCxlReq Document +FIToFIPmtCxlReq	Name Typ Payment Cancellation Request FIToFIPaymentCancellationRequestV01			
1..1	Assgnmt Document +FIToFIPmtCxlReq ++Assgnmt	Name Typ Assignment SCLSDDCaseAssignment2		Rückruf-Auftrag	The assignment contains informations for the processing of the whole message.
1..1	Id Document +FIToFIPmtCxlReq ++Assgnmt +++Id	Name Typ Pattern Identification SCLSDDId7 ([A-Za-z0-9][+ \? / - : \(\) \., '])(1,35}		Identifikation des Auftrags Bestandteil der Doppelinreichungskontrolle (geschäftstäglich eindeutige Referenz). Fehlercode: B14 Die ersten 8 bzw. 11 Stellen der Id müssen im IDF mit dem BIC des Assigner übereinstimmen. Der Rest des Feldes ist frei verfügbar. Fehlercode: B98	Reference number of the bulk. <Id> is part of duplication check on bulk level (unique daily reference). Error code: B14 The first 8 or 11 characters of Id must match the BIC of Assigner in IDF. The rest of the field can be freely defined. Error code: B98
1..1	Assgnr Document +FIToFIPmtCxlReq ++Assgnmt +++Assgnr	Name Typ Assigner SCLSDDParty7Choice		IDF: Rückruf einreichende Institution. Bei Einlieferung in den SCL mit dem BIC des Einreichers zu belegen. DNF: Rückruf ausliefernde Institution. Bei Auslieferung aus dem SCL mit "MARKDEFF" belegt.	IDF: To be completed with the BIC of the submitter for transmission to the SCL. DNF: To be completed with "MARKDEFF" for delivery from the SCL.
1..1	Agt Document +FIToFIPmtCxlReq ++Assgnmt +++Assgnr ++++Agt	Name Typ Agent SCLSDDBranchAndFinancialInstitutionIdentification4			

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	FinInstnId Document +FIToFIPmtCxlReq ++Assgnmt +++Assgnr ++++Agt +++++FinInstnId	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification7			
1..1	BIC Document +FIToFIPmtCxlReq ++Assgnmt +++Assgnr ++++Agt +++++FinInstnId ++++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}		Einlieferung: BIC muss einreichungsberechtigt sein. Fehlercode: B12 Prüfung gegen den BIC im File Header (Sending Institution) auf Einreichungsberechtigung des Kommunikationspartners. Fehlercode: B12	Submission: BIC must be completed correctly and eligible for transmission. Error code: B12 Communication partner's authorisation to submit verified against the BIC in the file header (Sending Institution). Error code: B12
1..1	Assgne Document +FIToFIPmtCxlReq ++Assgnmt +++Assgne	Name Typ Assignee SCLSDDParty7Choice		IDF: Mit dem Rückruf beauftragte Institution. Bei Einlieferung in den SCL mit "MARKDEFF" zu belegen. DNF: Mit dem Rückruf beauftragte Institution. Bei Auslieferung aus dem SCL mit dem BIC des Empfängers belegt.	IDF: To be completed with "MARKDEFF" for submission to the SCL. DNF: To be completed with the BIC of the settlement agent for delivery from the SCL.
1..1	Agt Document +FIToFIPmtCxlReq ++Assgnmt +++Assgne ++++Agt	Name Typ Agent SCLSDDBranchAndFinancialInstitutionIdentification4			
1..1	FinInstnId Document +FIToFIPmtCxlReq ++Assgnmt +++Assgne ++++Agt +++++FinInstnId	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification7			
1..1	BIC Document	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3})		IDF: Bei Einlieferung in den SCL mit „MARKDEFF“ zu belegen. Fehlercode: B12	IDF: For submission in the SCL to be completed with „MARKDEFF“. Error code: B12

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+FIToFIPmtCxlReq ++Assgnmt +++Assgne ++++Agt +++++FinInstnld ++++++BIC	{0,1}			
1..1	CreDtTm Document +FIToFIPmtCxlReq ++Assgnmt +++CreDtTm	Name Typ Pattern Creation Date Time ISODatetime [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}[T][0-9]{2,2}: [0-9]{2,2}:[0-9]{2,2}[\S]*			
1..1	CtrlData Document +FIToFIPmtCxlReq ++CtrlData	Name Typ Control Data ControlData1			
1..1	NbOfTxs Document +FIToFIPmtCxlReq ++CtrlData +++NbOfTxs	Name Typ Pattern Number Of Transactions Max15NumericText [0-9]{1,15}		Gesamtanzahl der Einzeltransaktionen im Bulk Darf nicht größer sein als 100.000 (maximaler Parameter der Datensätze im Bulk). Fehlercode: B02 Gesamtanzahl der Datensätze muss der tatsächlichen Anzahl der Einzeldatensätze im Bulk entsprechen. Fehlercode: B03	Total number of single transactions in the bulk. Must not exceed 100,000 (maximum parameter of data records in the file). Error code: B02 Total number of data records must be equal to the actual number of individual data records in the file. Error code: B03
1..1	Undrlyg Document +FIToFIPmtCxlReq ++Undrlyg	Name Typ Underlying SCLSDDUnderlyingTransaction2		Daten der dem Rückruf zu Grunde liegenden Originaltransaktion(en)	Data of the underlying original transaction(s) being cancelled.
1..n	TxInf Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf	Name Typ Transaction Information SCLSDDPaymentTransactionInformation31		Mandatory	Mandatory
1..1	CxllId	Name Typ Cancellation Identification SCLSDDId7		Referenz des den Rückruf veranlassenden Kreditinstitutes	Reference of the credit institution requesting the cancellation.

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++CxlId	Pattern ([A-Za-z0-9][+ ? / -: (\) \. , '])(1,35)		Cancellation ID ist Bestandteil der Doppeleinreichungskontrolle auf Einzelsatzebene. Fehlercode: AM05	Cancellation Id is an element of the duplication check at single record level. Error code: AM05
1..1	OrgnlGrpInf Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlGrpInf	Name Original Group Information Typ SCLSDDOriginalGroupInformation3			
1..1	OrgnlMsgId Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlGrpInf +++++OrgnlMsgId	Name Original Message Identification Typ SCLSDDId7 Pattern ([A-Za-z0-9][+ ? / -: (\) \. , '])(1,35)		Message ID der Originalzahlung	Message Id of original payment
1..1	OrgnlMsgNmId Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlGrpInf +++++OrgnlMsgNmId	Name Original Message Name Identification Typ SCLSDDOrgnlMsgNmId Pattern pacs\003[A-Za-z0-9\.\{0,27} PACS\003[A-Za-z0-9\.\{0,27}		Message Name ID der Originalzahlung Belegung mit "pacs.003" oder "PACS.003", ggf. zzgl. weiterer Zeichen gem. Schema-Validierung zulässig.	Message typ of original payment To be completed with "pacs.003" or "PACS.003", where necessary further characters in accordance with schema alidation permitted.
0..1	OrgnlInstrId Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlInstrId	Name Original Instruction Identification Typ SCLSDDId7 Pattern ([A-Za-z0-9][+ ? / -: (\) \. , '])(1,35)		Instruction ID der Originalzahlung	Instruction Id of original payment
1..1	OrgnlEndToEndId Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlEndToEndId	Name Original End To End Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse		End-to-End-ID der Originalzahlung	End to End Id of original payment
1..1	OrgnlTxId	Name Original Transaction Identification		Transaction ID der Originalzahlung	Transaction Id of original payment

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFIPmtCxlReq ++Undrlyg +++Txlnf ++++OrgnlTxld	Typ Pattern SCLSDDId7 ([A-Za-z0-9][+ \? / \- :\(\)\ \.\, ']){1,35}		Die Originaltransaktion (pacs.003) muss im SEPA Clearer verarbeitet worden sein. Fehlercode XT75	The original transaction (pacs.003) must have been processed in the SEPA-Clearer. Error code: XT75
1..1	OrgnlIntrBkSttlmAmt Document +FIToFIPmtCxlReq ++Undrlyg +++Txlnf ++++OrgnlIntrBkSttlmAmt	Name Typ FractionDigits TotalDigits Inclusive Pattern Original Interbank Settlement Amount SCLSDDCurrencyAndAmount_2 2 18 0.01 .. 999999999.99 [0-9]{0,15}(\.([0-9]{0,2}))?{0,1}		Betrag der Originalzahlung In Ermangelung einer Gesamtsumme auf Bulkebene, wird der zu belastende Buchungsbetrag aus der Summe aller Einzelbeträge (Original Interbank Settlement Amount) ermittelt.	Original payment amount In the absence of a total at the bulk level, the amount to be debited will be calculated from the total of all individual amounts (Original Interbank Settlement Amount).
1..1	OrgnlIntrBkSttlmDt Document +FIToFIPmtCxlReq ++Undrlyg +++Txlnf ++++OrgnlIntrBkSttlmDt	Name Typ Pattern Original Interbank Settlement Date ISODate [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}		"Interbank Settlement Date" der Originalzahlung Muss mit dem Datum der Original-Transaktion übereinstimmen. Ggf. Rückweisung bei Weiterleitung an andere CSM mit Fehlercode: XT74 Dieses Datum muss ein T2-Geschäftstag sein und min. dem aktuellen SEPA-Clearer-Geschäftstag entsprechen oder bis zu maximal 14 Kalendertage in der Zukunft liegen. Ist das Datum bei mindestens einer Transaktion gleichlautend mit dem SEPA-Clearer-Geschäftstag und die Einreichung erfolgt nach 10:00 Uhr (SDD Core) bzw. 11:00 Uhr (SDD B2B) oder liegt es in der Vergangenheit, wird das gesamte Bulk zurückgewiesen. Fehlercode: B15	Interbank settlement date of original payment. Must match date of the original transaction. If applicable, rejection via other CSMs using error code: XT74 Interbank settlement date must be a T2 business day and correspond to the current SEPA business day or be in the future up to 14 calendar days. If the date of at least one transaction lies in the past or if the bulk is submitted after 10.00 (= cut-off time for SEPA Core direct debits) or 11.00 (= cut-off time for SEPA B2B direct debits) and the date of at least one transaction is the same as the SEPA-Clearer business day the entire bulk will be rejected. Error code: B15

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
				<p>Ein Rückruf ist nur vor Settlement zulässig. Die Einreichung muss bis spätestens 10:00 Uhr (SDD Core) bzw. 11:00 Uhr (SDD B2B) des Geschäftstages erfolgen, der dem <OrgnlIntrBkStlmDt> (= <IntrBkStlmDt> des zu Grunde liegenden pacs.003) entspricht. Fehlercode: B15</p> <p>In Ermangelung eines (Buchungs-)datums im GrpHdr müssen die <OrgnlIntrBkStlmDt> aller Transaktionen eines Bulks identisch sein. Ist dies der Fall, wird das <OrgnlIntrBkStlmDt> der ersten Transaktion als Buchungsdatum herangezogen. Liegt keine Identität der <OrgnlIntrBkStlmDt> vor, erfolgt eine Bulkrückweisung. Fehlercode: B97</p> <p>Hinweis: Bei Auslieferungen aus dem SCL enthalten alle Einzeltransaktionen des Bulks ebenfalls ein gleichlautendes <OrgnlIntrBkStlmDt>.</p> <p>Bei der Doppelinreichungskontrolle wird das aktuelle <IntrBkStlmDt> des SCL unterstellt. Die Originaltransaktion (pacs.003) muss im SEPA Clearer verarbeitet worden sein. Fehlercode XT75</p>	<p>A cancellation is only permitted prior to settlement. The submission must take place, at the latest, until 10.00 (SDD Core) or 11.00 (SDD B2B) on the settlement day which corresponds to the <OrgnlIntrBkStlmDt> (= <IntrBkStlmDt> of the underlying pacs.003). Error code: B15</p> <p>In the absence of a settlement date in <GrpHdr>, the <OrgnlIntrBkStlmDt> of all transactions in the bulk must be identical. If this is case, the <OrgnlIntrBkStlmDt> of the first transaction is used as the settlement date. If no <OrgnlIntrBkStlmDt> identity exists, a bulk rejection will occur. Error code: B97</p> <p>Note: In deliveries from the SCL all individual transactions of the bulk contain also an identical <OrgnlIntrBkStlmDt>.</p> <p>The current SCL <IntrBkStlmDt> is assumed for the duplication check. The original transaction (pacs.003) must have been processed in the SEPA-Clearer. Error code: XT75</p>

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	Assgnr Document +FIToFIPmtCxlReq ++Undrlyg +++Txlnf ++++Assgnr	Name Typ Assigner SCLSDDBranchAndFinancialInstitutionIdentification4		IDF: Darf in der Einlieferung nicht belegt werden. DNF: Wird in der Auslieferung vom SCL belegt.	IDF: must not be completed for submission. DNF: is completed upon delivery from the SCL.
1..1	FinInstnld Document +FIToFIPmtCxlReq ++Undrlyg +++Txlnf ++++Assgnr +++++FinInstnld	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification7			
1..1	BIC Document +FIToFIPmtCxlReq ++Undrlyg +++Txlnf ++++Assgnr +++++FinInstnld ++++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}		IDF: Darf in der Einlieferung nicht belegt werden. Fehlercode: XT13 DNF: Bei Auslieferung aus dem SCL mit dem BIC des Einreichers des Rückrufs belegt.	IDF: must not be completed for transmission. Error code: XT13 DNF: for delivery from the SCL completed with the BIC of the submitter of the bulk which contain the cancellation.
1..1	CxlRsnInf Document +FIToFIPmtCxlReq ++Undrlyg +++Txlnf ++++CxlRsnInf	Name Typ Cancellation Reason Information SCLSDDCancellationReasonInformation3		Informationen zum Grund des Rückrufs	Information on the reason for cancellation
1..1	Orgtr Document +FIToFIPmtCxlReq ++Undrlyg +++Txlnf ++++CxlRsnInf +++++Orgtr	Name Typ Originator SCLSDDId5		BIC oder Name der den Rückruf veranlassenden Institution	BIC or name of the institution requesting the cancellation
1..1	Nm Document +FIToFIPmtCxlReq ++Undrlyg +++Txlnf	Name Typ Length Pattern WhiteSpace Name Max70Text 1 .. 70 \\S+.* collapse		Name der den Rückruf veranlassenden Institution	Name of the institution requesting the cancellation

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	++++CxlRsnInf +++++Orgtr +++++Nm Id Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++CxlRsnInf +++++Orgtr +++++Id	Name Typ Identification SCLSDDParty6Choice2		BIC der den Rückruf veranlassenden Institution	BIC of the institution requesting the cancellation
1..1	OrgId Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++CxlRsnInf +++++Orgtr +++++Id +++++OrgId	Name Typ Organisation Identification SCLSDDOrganisationIdentification4			
1..1	BICorBEI Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++CxlRsnInf +++++Orgtr +++++Id +++++OrgId +++++BICorBEI	Name Typ Pattern BIC Or BEI AnyBICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}			
1..1	Rsn Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++CxlRsnInf +++++Rsn	Name Typ Reason CancellationReason2Choice		Grund des Rückrufs	Reason for cancellation.
1..1	Cd	Name Typ Code CancellationReason4Code		Code für den Grund des Rückrufs (Schema-Validierung).	Cancellation reason code (schema validation)

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++CxlRsnInf +++++Rsn ++++++Cd				
		Anwendbare Codes / Acceptable Codes			
		AGNT CURR CUST CUTA DUPL UPAY			
1..1	Prtry Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++CxlRsnInf +++++Rsn ++++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse		Hier können die Rückrufgründe "TECH" und "FRAD" eingestellt werden (keine ISO-Codes). Keine fachliche oder Schema-Validierung.	Recall reasons "TECH" and "FRAD" can be entered here (no ISO codes). No technical or schema validation.
1..1	OrgnITxRef Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef	Name Original Transaction Reference Typ extension (SCLSDDOriginalTransactionReference13)			
1..1	ReqdColltnDt Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++ReqdColltnDt	Name Requested Collection Date Typ ISODate Pattern [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}			
1..1	CdtrSchmeld Document +FIToFIPmtCxlReq	Name Creditor Scheme Identification Typ SCLSDDCdtrSchmeld			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++Undrlyg +++TxInf ++++OrgnITxRef +++++CdtrSchmeld				
1..1	Id Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++CdtrSchmeld +++++Id	Name Typ Identification SCLSDDPrivateIdentification2			
1..1	PrvtId Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++CdtrSchmeld +++++Id +++++PrvtId	Name Typ Private Identification SCLSDDPrty2			
1..1	Othr Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++CdtrSchmeld +++++Id +++++PrvtId +++++Othr	Name Typ Other SCLSDDId10			
1..1	Id Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++CdtrSchmeld +++++Id	Name Typ Pattern Identification SCLSDDId8 ([A-Za-z0-9][+ ? / - : () \. ' \" s]){1,35}			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	<p>+++++PrvtId +++++Othr +++++Id</p> <p>SchmeNm</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++CdtrSchmeld +++++Id +++++PrvtId +++++Othr +++++SchmeNm</p>	<p>Name Typ</p> <p>Scheme Name FinancialIdentificationSchemeName2</p>			
1..1	<p>Prtry</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++CdtrSchmeld +++++Id +++++PrvtId +++++Othr +++++SchmeNm +++++Prtry</p>	<p>Name Typ</p> <p>Proprietary SCLSDDId9</p>		Nur "SEPA" ist zulässig (Schema-Validierung).	Only "SEPA" is allowed (Schema validation).
Anwendbare Codes / Acceptable Codes					
SEPA					
1..1	<p>SttlmInf</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++SttlmInf</p>	<p>Name Typ</p> <p>Settlement Information SCLSDDSettlementInformation13</p>			
1..1	<p>SttlmMtd</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg</p>	<p>Name Typ</p> <p>Settlement Method SettlementMethod1Code</p>		Nur "CLRG" ist zulässig (Schema-Validierung).	Only "CLRG" is allowed (Schema validation).

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+++TxInf ++++OrgnITxRef +++++SttlmInf ++++++SttlmMtd				
Anwendbare Codes / Acceptable Codes					
CLRG					
1..1	ClrSys Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++SttlmInf ++++++ClrSys	Name Clearing System Typ SCLSDDClearingSystemIdentification1Choice			
1..1	Prtry Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++SttlmInf ++++++ClrSys ++++++Prtry	Name Proprietary Typ SCLSCTMax35Text_SCL Length 1 .. 35 Pattern \S+.* WhiteSpace collapse		Belegung gem. Originalzahlung.	Entry according to original payment
Anwendbare Codes / Acceptable Codes					
SCL					
1..1	PmtTplnf Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++PmtTplnf	Name Payment Type Information Typ SCLSDDPaymentTypeInfoInformation22		Zahlungsartinformationen	Payment type information
1..1	SvcLvl Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++PmtTplnf	Name Service Level Typ SCLSDDServiceLevel8Choice			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	<p>+++++SvcLvl</p> <p>Cd</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++PmtTpInf +++++SvcLvl +++++Cd</p>	<p>Name Code Typ SCLSDDExternalServiceLevel1Code</p>		Nur "SEPA" ist zulässig (Schema-Validierung).	Only "SEPA" is allowed (Schema validation)
Anwendbare Codes / Acceptable Codes					
SEPA					
1..1	<p>LclInstrm</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++PmtTpInf +++++LclInstrm</p>	<p>Name Local Instrument Typ SCLSDDLocalInstrument2Choice</p>		Kennzeichnung, ob Lastschrift des Core- oder des B2B-Verfahrens.	Indication as to whether B2B or CORE Direct Debit
1..1	<p>Cd</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++PmtTpInf +++++LclInstrm +++++Cd</p>	<p>Name Code Typ ExternalLocalInstrument1Code Length 1 .. 35</p>		<p>Belegung gem. Originalzahlung.</p> <p>Es dürfen nur die Werte "CORE" oder "B2B" enthalten sein (Schema-Validierung).</p> <p>In einem COR-File dürfen nur CORE- -Bulks und in einem B2B-File nur B2B-Bulks enthalten sein.</p> <p>Eine gemischte Einreichung von B2B- und CORE-Lastschriften in einem Bulk ist nicht zulässig. Fehlercode: XT43</p> <p>Die Originaltransaktion (pacs.003) muss im SEPA Clearer verarbeitet worden sein. Fehlercode XT75</p>	<p>Entry according to original payment.</p> <p>Only 'CORE' or 'B2B' are allowed. (Schema validation)</p> <p>In a COR-File only CORE bulks are allowed. In a B2B file only B2B-Bulks are allowed.</p> <p>Mixed submission of B2B, CORE and COR1 Direct Debits in a single bulk is not permissible. Error code: XT43</p> <p>The original transaction (pacs.003) must have been processed in the SEPA-Clearer. Error code: XT75</p>

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
		Anwendbare Codes / Acceptable Codes			
		B2B CORE			
1..1	SeqTp Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlTxRef +++++PmtTpInf ++++++SeqTp	Name Sequence Type Typ SequenceType1Code		Belegung gem. Originalzahlung. (Schema-Validierung)	Entry according to original payment. (Schema validation)
		Anwendbare Codes / Acceptable Codes			
		FNAL FRST OOFF RCUR			
0..1	CtgyPurp Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlTxRef +++++PmtTpInf ++++++CtgyPurp	Name Category Purpose Typ SCLSDDCategoryPurpose1Choice		Verschlüsselter Verwendungszweck	Category Purpose
1..1	Cd Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlTxRef +++++PmtTpInf ++++++CtgyPurp +++++++Cd	Name Code Typ ExternalCategoryPurpose1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse		Belegung gem. Originalzahlung.	Entry according to original payment.
1..1	Prtry Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse		Belegung gem. Originalzahlung.	Entry according to original payment.

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++++OrgnITxRef +++++PmtTpInf +++++CtgyPurp +++++Prtry				
1..1	MndtRltdInf Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++MndtRltdInf	Name Typ Mandate Related Information SCLSDDMandateRelatedInformation1			
1..1	MndtId Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++MndtRltdInf +++++MndtId	Name Typ Pattern Mandate Identification SCLSDDI8 ([A-Za-z0-9][+ \/ \- \(\) \.\ ' \\s]){1,35}		Belegung gem. Originalzahlung.	Entry according to original payment.
1..1	DtOfSgntr Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++MndtRltdInf +++++DtOfSgntr	Name Typ Pattern Date of Signature ISODate [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}		Belegung gem. Originalzahlung.	Entry according to original payment.
0..1	AmdmntInd Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++MndtRltdInf +++++AmdmntInd	Name Typ Amendment Indicator TrueFalseIndicator		Belegung gemäß Originaltransaktion.	Entry according to original payment.
0..1	AmdmntInfDtls Document +FIToFIPmtCxlReq	Name Typ Amendment Information Details SCLSDDAmdmntInformationDetails1		Belegung gemäß Originaltransaktion.	Entry according to original payment.

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	<p>++Undrlyg +++TxInf ++++OrgnITxRef ++++MndtRltdInf +++++AmdmntInfDtls</p> <p>OrgnlMndtld</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++MndtRltdInf +++++AmdmntInfDtls +++++OrgnlMndtld</p>	<p>Name Original Mandate Identification Typ SCLSDDId8 Pattern ([A-Za-z0-9][+ ? / \-: \(\) \., '\ s]){1,35}</p>		Belegung gem. Originalzahlung.	Entry according to original payment.
0..1	<p>OrgnlCdrSchmeld</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++MndtRltdInf +++++AmdmntInfDtls +++++OrgnlCdrSchmeld</p>	<p>Name Original Creditor Scheme Identification Typ SCLSDDCdrSchmeld1</p>			
0..1	<p>Nm</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++MndtRltdInf +++++AmdmntInfDtls +++++OrgnlCdrSchmeld +++++Nm</p>	<p>Name Name Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse</p>		Belegung gem. Originalzahlung.	Entry according to original payment.
0..1	<p>Id</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef</p>	<p>Name Identification Typ SCLSDDPrivateIdentification</p>			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	<p>++++MndtRltdInf +++++AmdmntInfDtIs +++++++OrgnlCdtrSchmeld +++++++Id</p> <p>PrvtId</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlTxRef +++++MndtRltdInf +++++AmdmntInfDtIs +++++OrgnlCdtrSchmeld +++++Id +++++++PrvtId</p>	<p>Name Typ</p> <p>Private Identification SCLSDDPrt1</p>			
1..1	<p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlTxRef +++++MndtRltdInf +++++AmdmntInfDtIs +++++OrgnlCdtrSchmeld +++++Id +++++++PrvtId +++++++Othr</p> <p>Othr</p>	<p>Name Typ</p> <p>Other SCLSDDid4</p>			
1..1	<p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlTxRef +++++MndtRltdInf +++++AmdmntInfDtIs +++++OrgnlCdtrSchmeld +++++Id +++++++PrvtId +++++++Othr +++++++Id</p> <p>Id</p>	<p>Name Typ Pattern</p> <p>Identification SCLSDDid8 ([A-Za-z0-9][+ \?/ -:\(\)\ \.\ '\ s]){1,35}</p>		Belegung gem. Originalzahlung.	Entry according to original payment.

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	SchmeNm Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++MndtRltdInf ++++++AmdmntInfDtIs +++++++OrgnlCdtrSchmeld +++++++Id +++++++PrvtId +++++++Othr +++++++SchmeNm	Name Typ Scheme Name FinancialIdentificationSchemeName2			
1..1	Prtry Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++MndtRltdInf ++++++AmdmntInfDtIs +++++++OrgnlCdtrSchmeld +++++++Id +++++++PrvtId +++++++Othr +++++++SchmeNm +++++++Prtry	Name Typ Proprietary SCLSDDId9		Belegung gem. Originalzahlung. (Schema-Validierung)	Entry according to original payment. (Schema validation)
Anwendbare Codes / Acceptable Codes					
0..1	OrgnIDbtrAcct Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++MndtRltdInf ++++++AmdmntInfDtIs +++++++OrgnIDbtrAcct	Name Typ Original Debtor Account SCLSDDCashAccount8			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Id Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++MndtRltdInf ++++++AmdmntInfDtls +++++++OrgnlDbtrAcct +++++++Id	Name Identification Typ SCLSDDAccountIdentification5Choice			
1..1	IBAN Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++MndtRltdInf ++++++AmdmntInfDtls +++++++OrgnlDbtrAcct +++++++Id +++++++IBAN	Name IBAN Typ IBANIdentifier Pattern [a-zA-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}			
1..1	Othr Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++MndtRltdInf ++++++AmdmntInfDtls +++++++OrgnlDbtrAcct +++++++Id +++++++Othr	Name Other Typ SCLSDDOrgnlDbtrAcctOther2			
1..1	Id Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++MndtRltdInf ++++++AmdmntInfDtls +++++++OrgnlDbtrAcct	Name Identification Typ Max34Text Length 1 .. 34 Pattern \S+.* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	<p>+++++Id +++++Othr +++++Id</p> <p>OrgnIDbtrAgt</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++MndtRltdInf +++++AmdmntInfDtls +++++OrgnIDbtrAgt</p>	<p>Name Typ</p> <p>Original Debtor Agent SCLSDDOrgnIDbtrAgt</p>			
1..1	<p>FinInstnId</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++MndtRltdInf +++++AmdmntInfDtls +++++OrgnIDbtrAgt +++++FinInstnId</p>	<p>Name Typ</p> <p>Financial Institution Identification SCLSDDOrgnIDbtrAgt1</p>			
1..1	<p>BIC</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++MndtRltdInf +++++AmdmntInfDtls +++++OrgnIDbtrAgt +++++FinInstnId +++++BIC</p>	<p>Name Typ Pattern</p> <p>BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}</p>			
1..1	<p>Othr</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef</p>	<p>Name Typ</p> <p>Other SCLSDDOrgnIDbtrAgtOther2</p>			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++++MndtRltdInf ++++AmdmntInfDtls ++++OrgnlDbtrAgt ++++FinInstnId ++++Othr				
1..1	Id Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlTxRef ++++MndtRltdInf ++++AmdmntInfDtls ++++OrgnlDbtrAgt ++++FinInstnId ++++Othr ++++Id	Name Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	ElctrncSgntr Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlTxRef ++++MndtRltdInf ++++ElctrncSgntr	Name Electronic Signature Typ Max1025Text Length 1 .. 1025 Pattern \S+.* WhiteSpace collapse		Belegung gem. Originalzahlung.	Entry according to original payment.
0..1	Rmtlnf Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlTxRef ++++Rmtlnf	Name Remittance Information Typ SCLSDDRemittanceInformation5		Verwendungszweck	Purpose of payment
1..1	Ustrd Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlTxRef ++++Rmtlnf	Name Unstructured Typ Max140Text Length 1 .. 140 Pattern \S+.* WhiteSpace collapse		Unstrukturierter Verwendungszweck. Belegung gem. Originalzahlung.	Unstructured payment information Entry according to original payment.

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	+++++Ustrd Strd Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++RmtInf +++++Strd	Name Typ Structured SCLSDDStructuredRemittanceInformation7		Strukturierter Verwendungszweck	Structured payment information
0..1	UltmtDbtr Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtDbtr	Name Typ Ultimate Debtor SCLSDDPartyIdentification32		Abweichender Zahler. Alle Sub-Elemente aus der Originalzahlung werden unterstützt.	Ultimate debtor All sub-elements from the original payment are supported.
0..1	Nm Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtDbtr +++++Nm	Name Typ Length Pattern WhiteSpace Name Max70Text 1 .. 70 \\S+.* collapse			
0..1	Id Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtDbtr +++++Id	Name Typ Identification SCLSDDParty6Choice			
1..1	Orgld Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef	Name Typ Organisation Identification SCLSDDOrganisationIdentification41			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	+++++UltmtDbtr +++++Id +++++Orgld BICOrBEI Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtDbtr +++++Id +++++Orgld +++++BICOrBEI	Name BIC Or BEI Typ AnyBICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}			
1..1	Othr Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtDbtr +++++Id +++++Orgld +++++Othr	Name Other Typ SCLSDDGenericOrganisationIdentification1			
1..1	Id Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtDbtr +++++Id +++++Orgld +++++Othr +++++Id	Name Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	SchmeNm Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf	Name Scheme Name Typ SCLSDDOrganisationIdentificationSchemeName1Choice			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++++OrgnITxRef +++++UltmtDbtr +++++ld +++++Orgld +++++Othr +++++SchmeNm				
1..1	Cd Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtDbtr +++++ld +++++Orgld +++++Othr +++++SchmeNm +++++Cd	Name Code Typ SCLSDDEternalOrganisationIdentification1 Code Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtDbtr +++++ld +++++Orgld +++++Othr +++++SchmeNm +++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtDbtr +++++ld +++++Orgld +++++Othr +++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	PrvtId Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtDbtr ++++++Id +++++++PrvtId	Name Typ Private Identification SCLSDDPersonIdentification5			
1..1	DtAndPlcOfBirth Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtDbtr ++++++Id +++++++PrvtId +++++++DtAndPlcOfBirth	Name Typ Date And Place Of Birth DateAndPlaceOfBirth			
1..1	BirthDt Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtDbtr ++++++Id +++++++PrvtId +++++++DtAndPlcOfBirth +++++++BirthDt	Name Typ Pattern Birth Date ISODate [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}			
0..1	PrvcOfBirth Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtDbtr ++++++Id	Name Typ Length Pattern WhiteSpace Province Of Birth Max35Text 1 .. 35 \\S+.* collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	<p>+++++PrvtId +++++DtAndPlcOfBirth +++++PrvcOfBirth</p> <p>CityOfBirth</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtDbtr +++++Id +++++PrvtId +++++DtAndPlcOfBirth +++++CityOfBirth</p>	<p>Name City Of Birth Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse</p>			
1..1	<p>CtryOfBirth</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtDbtr +++++Id +++++PrvtId +++++DtAndPlcOfBirth +++++CtryOfBirth</p>	<p>Name Country Of Birth Typ CountryCode Pattern [A-Z]{2,2}</p>			
1..1	<p>Othr</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtDbtr +++++Id +++++PrvtId +++++Othr</p>	<p>Name Other Typ SCLSDDGenericPersonIdentification1</p>			
1..1	<p>Id</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg</p>	<p>Name Identification Typ Max35Text Length 1 .. 35 Pattern \S+.*</p>			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+++TxInf ++++OrgnITxRef +++++UltmtDbtr ++++++Id +++++++PrvtId +++++++Othr +++++++Id	WhiteSpace collapse			
0..1	SchmeNm Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtDbtr ++++++Id +++++++PrvtId +++++++Othr +++++++SchmeNm	Name Scheme Name Typ SCLSDDPersonIdentificationSchemeName1 Choice			
1..1	Cd Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtDbtr ++++++Id +++++++PrvtId +++++++Othr +++++++SchmeNm +++++++Cd	Name Code Typ SCLSDDExternalPersonIdentification1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtDbtr ++++++Id +++++++PrvtId +++++++Othr	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	+++++++SchmeNm +++++++Prtry Issr Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef ++++UltmtDbtr +++++ld +++++Prvtld +++++Othr +++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	Dbtr Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef ++++Dbtr	Name Debtor Typ SCLSDDPartyIdentification35		Zahler. Alle Sub-Elemente aus der Originalzahlung werden unterstützt.	Debtor. All sub-elements from the original payment are supported.
1..1	Nm Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef ++++Dbtr +++++Nm	Name Name Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse		Name des Zahlers oder Ersatzinformationen gemäß Originalnachricht	Debtor Name or additional informations according tehe original payment.
0..1	PstlAdr Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++Dbtr +++++PstlAdr	Name Postal Address Typ SCLSDDPostalAddress1		Anschrift des Zahlers	Address of debtor
0..1	Ctry Document	Name Country Typ CountryCode Pattern [A-Z]{2,2}			

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++Dbtr ++++++PstlAdr +++++++Ctry				
0..2	AdrLine Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++Dbtr ++++++PstlAdr +++++++AdrLine	Name Address Line Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse			
0..1	Id Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++Dbtr ++++++Id	Name Identification Typ SCLSDDParty6Choice			
1..1	Orgld Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++Dbtr ++++++Id +++++++Orgld	Name Organisation Identification Typ SCLSDDOrganisationIdentification41			
1..1	BICorBEI Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef	Name BIC Or BEI Typ AnyBICIdentifier Pattern [A-Z]{6,6}[A-Z-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+++++Dbtr +++++Id +++++Orgld +++++BICOrBEI				
1..1	Othr Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlTxRef +++++Dbtr +++++Id +++++Orgld +++++Othr	Name Typ	Other SCLSDDGenericOrganisationIdentification1		
1..1	Id Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlTxRef +++++Dbtr +++++Id +++++Orgld +++++Othr +++++Id	Name Typ Length Pattern WhiteSpace	Identification Max35Text 1 .. 35 \\S+.* collapse		
0..1	SchmeNm Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlTxRef +++++Dbtr +++++Id +++++Orgld +++++Othr +++++SchmeNm	Name Typ	Scheme Name SCLSDDOrganisationIdentificationSchemeName1Choice		
1..1	Cd Document +FIToFIPmtCxlReq	Name Typ Length	Code SCLSDDExternalOrganisationIdentification1 Code 1 .. 4		

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++Undrlyg +++TxInf ++++OrgnITxRef +++++Dbtr ++++++ld ++++++Orgld ++++++Othr ++++++SchmeNm ++++++Cd	Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++Dbtr ++++++ld ++++++Orgld ++++++Othr ++++++SchmeNm ++++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++Dbtr ++++++ld ++++++Orgld ++++++Othr ++++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	Prvtld Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++Dbtr ++++++ld	Name Private Identification Typ SCLSDDPersonIdentification5			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	<p>+++++PrvtId</p> <p>DtAndPlcOfBirth</p> <p>Document</p> <p>+FIToFIPmtCxlReq</p> <p>++Undrlyg</p> <p>+++TxInf</p> <p>++++OrgnlTxRef</p> <p>+++++Dbtr</p> <p>+++++Id</p> <p>+++++PrvtId</p> <p>+++++DtAndPlcOfBirth</p>	<p>Name Date And Place Of Birth</p> <p>Typ DateAndPlaceOfBirth</p>			
1..1	<p>BirthDt</p> <p>Document</p> <p>+FIToFIPmtCxlReq</p> <p>++Undrlyg</p> <p>+++TxInf</p> <p>++++OrgnlTxRef</p> <p>+++++Dbtr</p> <p>+++++Id</p> <p>+++++PrvtId</p> <p>+++++DtAndPlcOfBirth</p> <p>+++++BirthDt</p>	<p>Name Birth Date</p> <p>Typ ISODate</p> <p>Pattern [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}</p>			
0..1	<p>PrvcOfBirth</p> <p>Document</p> <p>+FIToFIPmtCxlReq</p> <p>++Undrlyg</p> <p>+++TxInf</p> <p>++++OrgnlTxRef</p> <p>+++++Dbtr</p> <p>+++++Id</p> <p>+++++PrvtId</p> <p>+++++DtAndPlcOfBirth</p> <p>+++++PrvcOfBirth</p>	<p>Name Province Of Birth</p> <p>Typ Max35Text</p> <p>Length 1 .. 35</p> <p>Pattern \S+.*</p> <p>WhiteSpace collapse</p>			
1..1	<p>CityOfBirth</p> <p>Document</p> <p>+FIToFIPmtCxlReq</p> <p>++Undrlyg</p> <p>+++TxInf</p> <p>++++OrgnlTxRef</p>	<p>Name City Of Birth</p> <p>Typ Max35Text</p> <p>Length 1 .. 35</p> <p>Pattern \S+.*</p> <p>WhiteSpace collapse</p>			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+++++Dbtr +++++Id +++++Prvtld +++++DtAndPlcOfBirth +++++CityOfBirth				
1..1	CtryOfBirth Document +FIToFIPmtCxlReq ++Undrlyg +++Txlnf ++++OrgnITxRef +++++Dbtr +++++Id +++++Prvtld +++++DtAndPlcOfBirth +++++CtryOfBirth	Name Country Of Birth Typ CountryCode Pattern [A-Z]{2,2}			
1..1	Othr Document +FIToFIPmtCxlReq ++Undrlyg +++Txlnf ++++OrgnITxRef +++++Dbtr +++++Id +++++Prvtld +++++Othr	Name Other Typ SCLSDDGenericPersonIdentification1			
1..1	Id Document +FIToFIPmtCxlReq ++Undrlyg +++Txlnf ++++OrgnITxRef +++++Dbtr +++++Id +++++Prvtld +++++Othr +++++Id	Name Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	SchmeNm Document	Name Scheme Name Typ SCLSDDPersonIdentificationSchemeName1 Choice			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++Dbtr +++++Id +++++PrvtId +++++Othr +++++SchmeNm				
1..1	Cd Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++Dbtr +++++Id +++++PrvtId +++++Othr +++++SchmeNm +++++Cd	Name Code Typ SCLSDDExternalPersonIdentification1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++Dbtr +++++Id +++++PrvtId +++++Othr +++++SchmeNm +++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++Dbtr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+++++Id +++++PrvtId +++++Othr +++++Issr				
1..1	DbtrAcct Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef ++++DbtrAcct	Name Typ Debtor Account SCLSDDCashAccount16		Konto des Zahlers	Account of debtor.
1..1	Id Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef ++++DbtrAcct +++++Id	Name Typ Identification SCLSDDAccountIdentification4Choice			
1..1	IBAN Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++DbtrAcct +++++Id +++++IBAN	Name Typ Pattern IBAN IBAN2007Identifier [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}		Belegung gem. Originalzahlung.	Entry according to original payment
1..1	DbtrAgt Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++DbtrAgt	Name Typ Debtor Agent SCLSDDBranchAndFinancialInstitutionIdentification4		Zahlungsdienstleister des Zahlers	Credit institution of debtor
1..1	FinInstnId Document +FIToFIPmtCxlReq	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification7			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++Undrlyg +++TxInf ++++OrgnITxRef ++++DbtrAgt +++++FinInstnld				
1..1	BIC Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++DbtrAgt +++++FinInstnld +++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}		BIC des Zahlungsdienstleisters des Zahlungsempfängers gemäß der Originalnachricht. Gültigkeit des BIC anhand des SCL-Directory. Fehlercode: XT27	BIC of the Beneficiary Bank according to original payment. Validity check of BIC against SCL-Directory. Error code: XT27
1..1	CdtrAgt Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++CdtrAgt	Name Typ Creditor Agent SCLSDDBranchAndFinancialInstitutionIdentification4		Zahlungsdienstleister des Zahlungsempfängers	Credit institution of creditor
1..1	FinInstnld Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++CdtrAgt +++++FinInstnld	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification7			
1..1	BIC Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++CdtrAgt +++++FinInstnld +++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}		Belgung gem. Originalzahlung Der Original Creditor Agent BIC ist Bestandteil der Doppelseinreichungskontrolle auf Einzelsatzebene. Fehlercode: AM05 Gültigkeit des BIC anhand des SCL-Directory. Fehlercode: XT27	Entry according to original payment The original creditor agent BIC is part of the duplication check at single record level. Error code: AM05 Validity of BIC using SCL-Directory. Error code: XT27

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
				Die Originaltransaktion (pacs.003) muss im SEPA Clearer verarbeitet worden sein. Fehlercode XT75	The original transaction (pacs.003) must have been processed in the SEPA-Clearer. Error code: XT75
1..1	Cdtr Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlTxRef +++++Cdtr	Name Creditor Typ SCLSDDPartyIdentification34		Zahlungsempfänger. Alle Sub-Elemente aus der Originalzahlung werden unterstützt.	Creditor. All sub-elements from the original payment are supported.
1..1	Nm Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlTxRef +++++Cdtr +++++Nm	Name Name Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse			
0..1	PstlAdr Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlTxRef +++++Cdtr +++++PstlAdr	Name Postal Address Typ SCLSDDPostalAddress1		Anschrift des Zahlungsempfängers	Address of debtor
0..1	Ctry Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlTxRef +++++Cdtr +++++PstlAdr +++++Ctry	Name Country Typ CountryCode Pattern [A-Z]{2,2}			
0..2	AdrLine	Name Address Line Typ Max70Text			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++Cdtr ++++++PstlAdr +++++++AdrLine	Length 1 .. 70 Pattern \S+.* WhiteSpace collapse			
1..1	CdtrAcct Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++CdtrAcct	Name Creditor Account Typ SCLSDDCashAccount16		Konto des Zahlungsempfängers	Account of debtor.
1..1	Id Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++CdtrAcct +++++Id	Name Identification Typ SCLSDDAccountIdentification4Choice			
1..1	IBAN Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++CdtrAcct +++++Id +++++++IBAN	Name IBAN Typ IBAN2007Identifier Pattern [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}		Belegung gem. Originalzahlung.	Entry according to original payment
0..1	UltmtCdtr Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtCdtr	Name Ultimate Creditor Typ SCLSDDPartyIdentification32		Abweichender Zahlungsempfänger. Alle Sub-Elemente aus der Originalzahlung werden unterstützt.	Ultimate Creditor. All sub-elements from the original payment are supported.

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	Nm Document +FIToFIPmtCxlReq ++Undrlyg +++Txlnf ++++OrgnITxRef +++++UltmtCdtr ++++++Nm	Name Name Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse			
0..1	Id Document +FIToFIPmtCxlReq ++Undrlyg +++Txlnf ++++OrgnITxRef +++++UltmtCdtr ++++++Id	Name Identification Typ SCLSDDParty6Choice			
1..1	OrgId Document +FIToFIPmtCxlReq ++Undrlyg +++Txlnf ++++OrgnITxRef +++++UltmtCdtr ++++++Id +++++++OrgId	Name Organisation Identification Typ SCLSDDOrganisationIdentification41			
1..1	BICOrBEI Document +FIToFIPmtCxlReq ++Undrlyg +++Txlnf ++++OrgnITxRef +++++UltmtCdtr ++++++Id +++++++OrgId +++++++BICOrBEI	Name BIC Or BEI Typ AnyBICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}			
1..1	Othr Document +FIToFIPmtCxlReq	Name Other Typ SCLSDDGenericOrganisationIdentification1			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtCdtr ++++++ld ++++++Orgld ++++++Othr				
1..1	Id Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtCdtr ++++++ld ++++++Orgld ++++++Othr ++++++ld	Name Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	SchmeNm Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtCdtr ++++++ld ++++++Orgld ++++++Othr ++++++SchmeNm	Name Scheme Name Typ SCLSDDErganisationIdentificationSchemeName1Choice			
1..1	Cd Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtCdtr ++++++ld ++++++Orgld ++++++Othr ++++++SchmeNm ++++++Cd	Name Code Typ SCLSDDErganisationIdentification1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Prtry Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtCctr +++++Id +++++Orgld +++++Othr +++++SchmeNm +++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtCctr +++++Id +++++Orgld +++++Othr +++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	PrvtId Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtCctr +++++Id +++++PrvtId	Name Private Identification Typ SCLSDDPersonIdentification5			
1..1	DtAndPlcOfBirth Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef	Name Date And Place Of Birth Typ DateAndPlaceOfBirth			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+++++UltmtCctr +++++Id +++++Prvtld +++++DtAndPlcOfBirth				
1..1	BirthDt Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlTxRef +++++UltmtCctr +++++Id +++++Prvtld +++++DtAndPlcOfBirth +++++BirthDt	Name Birth Date Typ ISODate Pattern [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}			
0..1	PrvcOfBirth Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlTxRef +++++UltmtCctr +++++Id +++++Prvtld +++++DtAndPlcOfBirth +++++PrvcOfBirth	Name Province Of Birth Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	CityOfBirth Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnlTxRef +++++UltmtCctr +++++Id +++++Prvtld +++++DtAndPlcOfBirth +++++CityOfBirth	Name City Of Birth Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	CtryOfBirth Document	Name Country Of Birth Typ CountryCode Pattern [A-Z]{2,2}			

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtCdtr ++++++Id +++++++Prvtld +++++++DtAndPlcOfBirth +++++++CtryOfBirth				
1..1	Othr Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtCdtr ++++++Id +++++++Prvtld +++++++Othr	Name Typ	Other SCLSDDGenericPersonIdentification1		
1..1	Id Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtCdtr ++++++Id +++++++Prvtld +++++++Othr +++++++Id	Name Typ Length Pattern WhiteSpace	Identification Max35Text 1 .. 35 \\S+.* collapse		
0..1	SchmeNm Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtCdtr ++++++Id +++++++Prvtld +++++++Othr	Name Typ	Scheme Name SCLSDDPersonIdentificationSchemeName1 Choice		

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	<p>+++++++SchmeNm</p> <p>Cd</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtCdtr +++++Id +++++PrvtId +++++Othr +++++SchmeNm +++++Cd</p>	<p>Name Code Typ SCLSDDEternalPersonIdentification1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse</p>			
1..1	<p>Prtry</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtCdtr +++++Id +++++PrvtId +++++Othr +++++SchmeNm +++++Prtry</p>	<p>Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse</p>			
0..1	<p>Issr</p> <p>Document +FIToFIPmtCxlReq ++Undrlyg +++TxInf ++++OrgnITxRef +++++UltmtCdtr +++++Id +++++PrvtId +++++Othr +++++Issr</p>	<p>Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse</p>			

Nachricht

SEPA Direct Debit – Interbank Direct Debit Return/Refund of a Collection (DS-05)

Verwendung der Interbank Direct Debit Return/Refund of a Collection (pacs.004.001.02SDD)

Die Nachricht wird verwendet, um Rückgaben von Lastschriften zwischen Zahlungsdienstleistern zu transportieren. Anhand der Belegung des Feldes ‚Return Originator‘ kann abgeleitet werden, ob es sich um einen Refund oder einen Return handelt. Wenn im ‚Return Originator‘ ein ‚Name‘ angegeben wurde, handelt es sich um einen Refund, wenn ein ‚BIC‘ angegeben wurde, handelt es sich um einen Return.

Die Nachricht berücksichtigt **nur** einzelne Rückgaben.

Hinweise:

- Attribut R1 wird vom ‚Message Name‘ ‚pacs.004.001‘ und der ‚Original Message Name Identification‘ ‚pacs.003.001‘ impliziert
- Nachrichtenelemente unter der ‚Original Transaction Reference‘ Sequenz basieren auf DS-04 Attributen.

ISO Nachrichtenstruktur

Eine Return/Refund-Nachricht beinhaltet:

- einen einzelnen Group Header.
- eine oder mehrere „Transaction Information“-Sequenzen, von der jede eine Rückgabe enthält, wie in DS-05 definiert.

Group Header

Der Group Header enthält Informationen, die für die Verarbeitung der gesamten Nachricht benötigt werden.

Use of Interbank Return Direct Debit Return/Refund of a Collection (pacs.004.001.02)

This message is used to transport the direct debit return/refund instruction between payment service providers. It is possible to deduce whether the transaction is being used as a refund or a return by referring to the entry in the 'Return Originator' field. If the 'Return Originator' contains a 'Name', this means that the message is being used as a Refund. If it contains a BIC, this means the message is being used as a return.

The message caters for single return/refund instructions **only**.

Notes:

- Attribute R1 is implied by the 'Message Name', 'pacs.004.001', and the 'Original Message Name Identification' set to 'pacs.003.001'.
- Message elements under the 'Original Transaction Reference' sequence are based on DS-04 attributes.

ISO message structure

A Return/Refund message contains:

- a single group header
- one or more 'transaction information' sequences, each of which contains the transaction data of an individual underlying direct debit being returned/refunded, as defined in DS-05.

Group header

The group header contains information required to process the entire message.

Nachrichtenstruktur / Message structure

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document	Typ Document			
1..1	Document PmtRtr	Typ PaymentReturnV02			
1..1	Document +PmtRtr GrpHdr	Name Typ Group Header SCLSDDGroupHeader6		Enthält allgemeine Informationen der Verarbeitung, die auf jede einzelne Zahlung zutreffen.	The group header contains general processing information which applies to the whole payment.
1..1	Document +PmtRtr ++GrpHdr MsgId	Name Typ Pattern Message Identification SCLSDDId7 ([A-Za-z0-9][+ \? / - \(\) \., !]){1,35}		Referenz-Nr. des Bulks Bestandteil der Doppeleinreichungskontrolle. Fehlercode: B14 Die ersten 8 bzw. 11 Stellen der MsgId müssen im IDF mit dem BIC des Instructing Agent übereinstimmen. Der Rest des Feldes ist frei verfügbar. Fehlercode: B98	Bulk reference number. <MsgId> is part of the duplication check at bulk level Error code: B14 The first 8 or 11 characters of MsgId must match the BIC of the instructing agent in the IDF. The rest of the field can be freely defined. Error code: B98
1..1	Document +PmtRtr ++GrpHdr +++CreDtTm CreDtTm	Name Typ Pattern Creation Date Time ISODatetime [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}[T][0-9]{2,2};[0-9]{2,2};[0-9]{2,2}\[S]*		Erstellungsdatum und -zeit des Bulks	Bulk creation date and time.
1..1	Document +PmtRtr ++GrpHdr +++NbOfTx NbOfTx	Name Typ Pattern Number Of Transactions Max15NumericText [0-9]{1,15}		Gesamtanzahl der Einzeltransaktionen im Bulk Darf nicht größer sein als 100.000 (maximaler Parameter der Datensätze im Bulk). Fehlercode: B02 Gesamtanzahl der Datensätze muss der tatsächlichen Anzahl der Einzeldatensätze im Bulk entsprechen. Fehlercode: B03	Total number of single transactions in the bulk. Must not exceed 100,000 (maximum parameter of data records in the bulk). Error code: B02 Total number of data records must be equal to the actual number of individual data records in the bulk. Error code: B03

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	TtIRtrdIntrBkSttlmAmt Document +PmtRtr ++GrpHdr +++TtIRtrdIntrBkSttlmAmt	Name Total Returned Interbank Settlement Amount Typ SCLSDDCurrencyAndAmount_Total FractionDigits 2 TotalDigits 18 Inclusive 0.01 .. 99999999999999.99 Pattern [0-9]{0,15}(\.[0-9]{0,2}){0,1}	Mandatory Usage Rule: Only 'EUR' is allowed. Usage Rule: Amount must be 0.01 or more and 99999999999999.99 or less. Format Rule: The fractional part has a maximum of two digits.	Gesamtsumme der Einzeltransaktionen im Bulk Bis zu 15 Zeichen sind im ganzzahligen Wertebereich erlaubt. Weiterhin sind maximal bis zwei Nachkommastellen erlaubt. (Schema- Validierung) Währungskennzeichen ist immer "EUR". (Schema-Validierung) Die angegebene Gesamtsumme muss der Summe der Einzel- transaktionen (ReturnedInterbank Settlement Amount) des Bulks entsprechen. Fehlercode: B05 Betragsangabe muss mindestens den Wert 0.01 oder mehr enthalten und darf den Wert 99999999999999.99 nicht übersteigen. (Schema-Validierung)	Total number of single transactions in the bulk. Integer value of up to 15 characters allowed. Maximum number of decimal places allowed remains two. (Schema validation) Currency designation is always 'EUR'. (Schema validation) The total amount given must equal the sum of the single transactions (Returned Interbank Settlement Amount) in the bulk Error code: B05 Amount must be at least 0.01 but no more than 99999999999999.99 (Schema validation)

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	IntrBkSttlmDt Document +PmtRtr ++GrpHdr +++IntrBkSttlmDt	Name Typ Pattern Interbank Settlement Date ISODate [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}	Mandatory AT-R4 Settlement Date for Return	Abrechnungsdatum des Returns. Geschäftstag an dem die Zahlungen der Datei im SEPA- Clearer verarbeitet werden sollen. Bei Einlieferungen bis 10:00 Uhr (Core) bzw. 11:00 Uhr (B2B) muss hier der aktuelle Geschäftstag des SEPA-Clearers angegeben werden. Bei Einlieferungen nach 15:00 Uhr (Core) bzw. 13:00 Uhr (B2B) muss hier der nächste Geschäftstag des SEPA-Clearers angegeben werden. Fehlercode: B15 "IntrBkSttlmDt" ist Bestandteil der Doppeleinreichungskontrolle auf Bulk- und Transaktionsebene.	Settlement date of the return. Business day for processing the transactions in the SEPA-Clearer For submission not later than 10.00 (Core) respectively 11.00 (B2B) the current operating day of the SEPA-Clearer must be given. For submissions after 15.00 (Core) respectively 13.00 (B2B) the next operating day of the SEPA-Clearer must be given. Error code: B15 "IntrBkSttlmDt" is part of theduplication check at bulk and single transaction level.
1..1	SttlmInf Document +PmtRtr ++GrpHdr +++SttlmInf	Name Typ Settlement Information SCLSDDSettlementInformation1			
1..1	SttlmMtd Document +PmtRtr ++GrpHdr +++SttlmInf ++++SttlmMtd	Name Typ Settlement Method SCLSDDSettlementMethod1Code	Usage Rule: Only CLRG, INGA and INDA are allowed.	Information über den Settlement Mechanismus. Nur der Code "CLRG" ist zulässig. (Schema-Validierung)	Information on the settlement mechanism. Only the code 'CLRG' is allowed. (Schema validation)
Anwendbare Codes / Acceptable Codes					
CLRG					
1..1	ClrSys Document +PmtRtr ++GrpHdr +++SttlmInf ++++ClrSys	Name Typ Clearing System SCLSDDClearingSystemIdentification1Choice			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Prtry Document +PmtRtr ++GrpHdr +++Stlmlnfnf ++++ClrSys +++++Prtry	Name Proprietary Typ Max35Text_Prtry Length 1 .. 35 Pattern \S+.* WhiteSpace collapse		Kennzeichen für das Clearing System. Für den SEPA-Clearer ist nur der Wert "SCL" zulässig. (Schema-Validierung)	Code for the clearing system. For the SEPA-Clearer, only the entry 'SCL' is allowed. (Schema validation)
Anwendbare Codes / Acceptable Codes					
0..1	InstgAgt Document +PmtRtr ++GrpHdr +++InstgAgt	Name Instructing Agent Typ SCLSDDBranchAndFinancialInstitutionIdentification3	Usage Rule: Only BIC is allowed.	Nur bei Einlieferungen in den SEPA-Clearer zu belegen. Hier ist der BIC des SCL-Teilnehmers einzustellen, der zu dem technischen Unterkonto/Sub-Account in T2 gehört. das für die Durchführung der geldlichen Verrechnung herangezogen wird. Bestandteil der Doppeleinreichungskontrolle auf Bulkebene.	Only to be used for submissions to the SEPA-Clearer. Allocation of the BIC of the SCL participant which is linked with the T2 sub-account assigned for settlement with the SEPA-Clearer. Part of duplication check at bulk level. Error code: AM05
1..1	FinInstnld Document +PmtRtr ++GrpHdr +++InstgAgt ++++FinInstnld	Name Financial Institution Identification Typ SCLSDDFinancialInstitutionIdentification5Choice			
1..1	BIC Document +PmtRtr ++GrpHdr +++InstgAgt ++++FinInstnld +++++BIC	Name BIC Typ BICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}		BIC muss im Input Debit File (IDF) enthalten und einreichungsberechtigt sein. Fehlercode: B10 Prüfung gegen den BIC im File Header (Sending Institution) auf Einreichungsberechtigung des Kommunikationspartners. Fehlercode: B10	BIC must be contained in Input Debit File (IDF). Error code: B10 Communication partner's authorisation to submit verified against the BIC in the file header (Sending Institution). Error code: B10

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	InstdAgt Document +PmtRtr ++GrpHdr +++InstdAgt	Name Typ Instructed Agent SCLSDDBranchAndFinancialInstitutionIdentification3	Usage Rule: Only BIC is allowed.	Nur bei Auslieferungen aus dem SEPA-Clearer zu belegen. Hier ist der BIC des SCL-Teilnehmers einzustellen, der zu dem technischen Unterkonto/Sub-Account in T2-gehört, das für die Durchführung der geldlichen Verrechnung herangezogen wird.	Only to be used for deliveries from the SEPA-Clearer. Allocation of the BIC of the SCL participant which is linked with the T2 sub-account assigned for settlement with the SEPA-Clearer.
1..1	FinInstnId Document +PmtRtr ++GrpHdr +++InstdAgt ++++FinInstnId	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Choice			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	BIC Document +PmtRtr ++GrpHdr +++InstdAgt ++++FinInstnId +++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}		BIC darf nur im Settled Debit File (SDF) enthalten sein. Fehlercode: B11	BIC may only present in the Settled Debit File(SDF). Fehlercode: B11
1..n	TxInf Document +PmtRtr ++TxInf	Name Typ Transaction Information SCLSDDPaymentTransactionInformation2	Mandatory	Maximal 100.000 Datensätze im Bulk	Maximum of 100,000 data records in the bulk.
1..1	RtrId Document +PmtRtr ++TxInf +++RtrId	Name Typ Pattern Return Identification SCLSDdId7 ([A-Za-z0-9][+ ? / - : \(\) \., !]){1,35}	Mandatory AT-R5 Specific Reference of the Bank Initiating the Return/ Refund	Referenznummer der Transaktion, die von der initiierten Bank des Returns vergeben wird. Return ID ist Bestandteil der Doppeleinreichungskontrolle auf Einzelsatzebene. Fehlercode: AM05	Reference number of the transaction given by the bank initiating the return. Return Id is part of the duplication check at single record level. Error code: AM05
1..1	OrgnlGrpInf Document +PmtRtr ++TxInf +++OrgnlGrpInf	Name Typ Original Group Information SCLSDdOriginalGroupInformation3	Usage Rule: Element 'Original Group Information' must be present either here or under '+Original Group Information'	Information aus dem ursprünglichen Bulk	Information from the original bulk in which the original message was enclosed.
1..1	OrgnlMsgId Document +PmtRtr ++TxInf +++OrgnlGrpInf ++++OrgnlMsgId	Name Typ Pattern Original Message Identification SCLSDdId7 ([A-Za-z0-9][+ ? / - : \(\) \., !]){1,35}		Dateireferenz (MsgId) des ursprünglichen Pacs.003-Bulks. Bei Auslieferung des SCL, die aus Einlieferungen anderer CSM resultieren kann hier ggf. der Wert "UNMATCHED" stehen.	Reference (<MsgId>) of original pac.003 bulk. In the case of deliveries from the SCL which result from submissions from another CSM, the entry 'UNMATCHED' is allowed where necessary
1..1	OrgnlMsgNmId Document +PmtRtr ++TxInf +++OrgnlGrpInf ++++OrgnlMsgNmId	Name Typ Pattern Original Message Name Identification SCLSDdOrgnlMsgNmId pac.\.003[A-Za-z0-9\.] {0,27} PACS\.\.003[A-Za-z0-9\.] {0,27}	Usage Rule: Only pac.003.001.02 is allowed.	Nachrichtentyp des ursprünglichen Bulk Belegung mit "pac.003" oder "PACS.003", jeweils ggf. zzgl. weiterer Zeichen gem. Schema-Validierung zulässig.	Name of the rejected original message. Usage rule: may be completed with "pac.003" or "PACS.003", where necessary with additional further characters in accordance with schema validation

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	OrgnlInstrId Document +PmtRtr ++TxInf +++OrgnlInstrId	Name Original Instruction Identification Typ SCLSDDId7 Pattern ([A-Za-z0-9][+ ? / - : (\\) \., '])(1,35)	Usage Rule: Mandatory if provided in the original instruction.	Die "Original Instruction ID" des zugrundeliegenden pac.003. Wird hier nur angegeben, wenn bereits in der ursprünglichen Lastschrift belegt.	The 'original instruction ID' of the underlying pac.003. Is only given here if it already existed in the original direct debit.
1..1	OrgnlEndToEndId Document +PmtRtr ++TxInf +++OrgnlEndToEndId	Name Original End To End Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse	Mandatory AT-10 Creditor's reference to the collection	Ursprüngliche Referenz des Zahlungsempfängers, End-to-End-Id der ursprünglichen Lastschrift.	The original creditor reference, End to End Id of the original direct debit.
1..1	OrgnlTxId Document +PmtRtr ++TxInf +++OrgnlTxId	Name Original Transaction Identification Typ SCLSDDId7 Pattern ([A-Za-z0-9][+ ? / - : (\\) \., '])(1,35)	Mandatory AT-43 Creditor bank's reference of the Collection Usage Rule: Must contain a reference that is meaningful to the Creditor's Bank and is unique over time.	Ursprüngliche Referenz der ersten Inkassostelle (Referenz der Auftraggeberbank). Die Transaction ID (TxId) des ursprünglichen pac.003-Bulk (keine Prüfung durch den SCL). Ggf. Fehlercode XT74 bzw. XT75 bei Weiterleitung der Zahlung an andere CSM	Original reference of the creditor bank. Transaction Id (TxId) of the original message. (not checked by the SEPA-Clearer) Where applicable error code XT74 or XT75, if payment is forwarded to another CSM..
1..1	OrgnlIntrBkSttlmAmt Document +PmtRtr ++TxInf +++OrgnlIntrBkSttlmAmt	Name Original Interbank Settlement Amount Typ SCLSDDCurrencyAndAmount_Tx FractionDigits 2 TotalDigits 18 Inclusive 0.01 .. 999999999.99 Pattern [0-9]{0,15}(\\.)(([0-9]{0,2})){0,1}	Mandatory AT-06 Amount of the Collection in euro Usage Rule: Amount must be 0.01 or more and 999999999.99 or less. Format Rule: The fractional part has a maximum of two digits.	Originalbetrag der ursprünglichen Lastschrift. Nur die Währungsbezeichnung "EUR" ist erlaubt. (Schema-Validierung) Maximal zwei Nachkommastellen gemäß der Konvention für EUR-Währung sind erlaubt. (Schema-Validierung) Betrag muss mindestens 0.01 betragen und darf den Wert 999999999.99 nicht übersteigen. (Schema-Validierung)	Original amount of original direct debit. Only 'EUR' is permitted as the currency designation. (Schema validation) A maximum of two decimal places is permitted (Schema validation) Amount must be at least 0.01 and must not exceed 999999999.99. (Schema validation)
1..1	RtrdIntrBkSttlmAmt Document +PmtRtr ++TxInf +++RtrdIntrBkSttlmAmt	Name Returned Interbank Settlement Amount Typ SCLSDDCurrencyAndAmount_Tx FractionDigits 2 TotalDigits 18 Inclusive 0.01 .. 999999999.99 Pattern [0-9]{0,15}(\\.)(([0-9]{0,2})){0,1}	Usage Rule: Only 'EUR' is allowed. Amount must be 0.01 or more and 999999999.99 or less.	Rückgabebetrag der Lastschrift. Nur die Währungsbezeichnung "EUR" ist erlaubt. (Schema-Validierung)	Return amount of the direct debit. Only 'EUR' is permitted as the currency designation. (Schema validation)

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
			Element is equal to the sum of 'Original Interbank Settlement Amount', 'Compensation Amount' and 'Amount' in 'Charges Information'. Format Rule: The fractional part has a maximum of two digits.	Maximal zwei Nachkommastellen gemäß der Konvention für EUR-Währung sind erlaubt. (Schema-Validierung) Betrag muss mindestens 0.01 betragen und darf den Wert 999999999.99 nicht übersteigen. (Schema-Validierung) Nutzbar für CORE- und B2B-Lastschriften. Dabei wird nur die rechnerische Richtigkeit der Addition <OrgnlIntrBkSttlmAmt> + <CompstnAmt> + <ChrgsInf/Amt> = <RtrdIntrBkSttlmAmt> geprüft, wenn <CompstnAmt> und/oder <ChrgsInf> gefüllt ist. Fehlercode: XT78	A maximum of two decimal places is permitted. (Schema validation) Amount must be at least 0.01 and must not exceed 999999999.99. (Schema validation) Can be used for CORE- and B2B-Direct Debits. Only the correctness of the sum (OrgnlIntrBkSttlm Amt) + <CompstnAmt> = <RtrdIntrBkSttlmAmt> is checked if <CompstnAmt> and/or <ChrgsInf> is/are completed. Error code: XT78
0..1	RtrdInstdAmt Document +PmtRtr ++TxInf +++RtrdInstdAmt	Name Returned Instructed Amount Typ SCLSDDCurrencyAndAmount_Tx FractionDigits 2 TotalDigits 18 Inclusive 0.01 .. 999999999.99 Pattern [0-9]{0,15}(\. [0-9]{0,2}){0,1}	Usage Rule: Only allowed in the case an Interchange Fee is included, i.e., 'Amount' under 'Charges Information' is used. Only 'EUR' is allowed. Amount must be 0.01 or more and 999999999.99 orless. Format Rule: The fractional part has a maximum of two digits.	Wird der Elementblock "Charges Information" genutzt, muss auf Grund einer ISO-Anforderung zusätzlich das Element "Returned Instructed Amount" belegt sein. Fehlercode: XT13 Falls belegt, obwohl "Amount" in "Charges Information" nicht belegt ist. Fehlercode: XT13 Betrag muss mindestens 0.01 betragen und darf den Wert 999999999.99 nicht übersteigen. (Schema-Validierung) Nur die Währungsbezeichnung "EUR" ist erlaubt. (Schema-Validierung)	If the element block "Charges Information" is used, the element "Returned Instructed Amount" must also be completed in compliance with an ISO requirement. Error code: XT13 Should this be completed, although "Amount" in "Charges Information" is not completed: error code: XT13 Amount must be at least 0.01 and must not exceed 999999999.99. (Schema validation) Only 'EUR' is permitted as the currency designation. (Schema validation)

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	CompstnAmt Document +PmtRtr ++TxInf +++CompstnAmt	Name Compensation Amount Typ SCLSDDCurrencyAndAmount_Tx FractionDigits 2 TotalDigits 18 Inclusive 0.01 .. 999999999.99 Pattern [0-9]{0,15}(\.[0-9]{0,2}){0,1}	CORE: AT-R6 Refund compensation recovered by the Debtor bank from the Creditor bank Usage Rule: 'Compensation Amount' only applies to refunds, which is indicated by the presence of 'Name' in 'Return Originator'. Only 'EUR' is allowed. Amount must be 0.01 or more and 999999999.99 or less. Format Rule: The fractional part has a maximum of two digits. B2B: Not to be used	Optionaler Zinsausgleich, der bei der Rückgabe der SEPA-Lastschrift durch die Zahlstelle zu Lasten der ersten Inkassostelle vereinnahmt wird. Verwendung nur im Core-Lastschriftverfahren zulässig; es findet keine Validierung durch den SCL statt. Compensation Amount ist nur in Refunds zulässig, d.h. <RtrRsnInf><Orgtr><Nm> muss belegt sein. Fehlercode: XT78. Nur die Währungsbezeichnung "EUR" ist erlaubt. (Schema-Validierung) Maximal zwei Nachkommastellen gemäß der Konvention für EUR-Währung sind erlaubt. (Schema-Validierung) Betrag muss mindestens 0.01 betragen und darf den Wert 999999999.99 nicht übersteigen. (Schema-Validierung).	Optional refund compensation recovered by the Debtor bank from the Creditor bank. Can be used only in Core Direct Debit; no validation by the SCL. Compensation Amount' only applies to refunds, which is indicated by the presence of <RtrRsnInf><Orgtr><Nm> Error code: XT78 Only 'EUR' is permitted as the currency designation. (Schema validation) A maximum of two decimal places is permitted (Schema validation) Amount must be at least 0.01 and must not exceed 999999999.99. (Schema validation)
0..1	ChrgBr Document +PmtRtr ++TxInf +++ChrgBr	Name Charge Bearer Typ SCLSDDChargeBearerType1Code	Usage Rule: Only 'SLEV' is allowed.	Gebührenkennzeichen Nur der Wert "SLEV" ist erlaubt (Schema-Validierung).	Charge bearer symbol. Only the code "SLEV" is allowed (Schema validation).
Anwendbare Codes / Acceptable Codes					
0..1	ChrgsInf Document +PmtRtr ++TxInf +++ChrgsInf	Name Charges Information Typ SCLSDDChargesInformation1	Usage Rule: Only one occurrence is allowed.	Wird der Elementblock "Charges Information" genutzt, muss auf Grund einer ISO-Anforderung zusätzlich das Element "Returned Instructed Amount" belegt sein. Fehlercode: XT13	If the element block "Charges Information" is used, the element "Returned Instructed Amount" must also be completed in compliance with an ISO requirement. Error code: XT13

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Amt Document +PmtRtr ++TxInf +++ChrgsInf ++++Amt	Name Amount Typ SCLSDDCurrencyAndAmount_2 FractionDigits 2 TotalDigits 18 Inclusive 0.01 .. 99999999.99 Pattern [0-9]{0,15}(\. [0-9]{0,2}){0,1}	AT-R8 Amount of the Interchange Fee Usage Rule: Only 'EUR' is allowed. Amount must be 0.01 or more and 99999999.99 or less. Format Rule: The fractional part has a maximum of two digits.	Nur zulässig, wenn bilateral zwischen Debtor Bank und Creditor Bank vereinbart. Nur die Währungsbezeichnung "EUR" ist erlaubt. (Schema-Validierung) Maximal zwei Nachkommastellen gemäß der Konvention für EUR-Währung sind erlaubt. (Schema-Validierung) Betragsangabe muss mindestens den Wert 0.01 oder mehr enthalten und darf den Wert 99999999.99 nicht übersteigen (Schema-Validierung).	Only permissible if bilaterally agreed between Debtor Bank and Creditor Bank. Currency designation is always 'EUR'. (Schema validation) A maximum of two decimal places is permitted (Schema validation) Amount must be at least 0.01 but no more than 99999999999999.99 (Schema validation)
1..1	Pty Document +PmtRtr ++TxInf +++ChrgsInf ++++Pty	Name Party Typ SCLSDDBranchAndFinancialInstitutionIdentification3			
1..1	FinInstnId Document +PmtRtr ++TxInf +++ChrgsInf ++++Pty +++++FinInstnId	Name Financial Institution Identification Typ SCLSDDFinancialInstitutionIdentification5Choice	AT-13 BIC of the Debtor Bank		
1..1	BIC Document +PmtRtr ++TxInf +++ChrgsInf ++++Pty +++++FinInstnId ++++++BIC	Name BIC Typ BICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	InstgAgt Document +PmtRtr ++TxInf +++InstgAgt	Name Typ Instructing Agent SCLSDDBranchAndFinancialInstitutionIdentification3	Usage Rule: Only BIC is allowed.	Ursprünglicher Einreicher der das Bulk, in dem die R-Transaktion enthalten war, in den SCL eingeliefert hat Nur bei Auslieferung der BBK an den SCL-Teilnehmer (Bank) belegt. Hier steht bei Zahlungen die über STEP2 an den SCL geleitet werden der BIC des direkten STEP2-Teilnehmers bzw. bei Zahlungen die innerhalb des SEPA-Clearers abgewickelt werden der BIC des SCL-Teilnehmers, der den Return/Refund in den SCL eingereicht hat.	Original submitter in the SCL of the bulk which contained the R-transaction. Only used in deliveries from the BBk to the SCL participant. In payments that have been submitted by STEP2, to the SCL the BIC of the direct STEP2 participant is displayed here.
1..1	FinInstnId Document +PmtRtr ++TxInf +++InstgAgt ++++FinInstnId	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Choice			
1..1	BIC Document +PmtRtr ++TxInf +++InstgAgt ++++FinInstnId +++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}		Belegung nur im Settled Debit File (SDF) erlaubt, darf im Input Debit File (IDF) des Teilnehmers an den SCL nicht enthalten sein. Fehlercode: XT13	Only permitted in the Settled Debit File (SDF), may not be contained in the Input Debit File (IDF) submitted by SCL participant. Error code: XT13
1..1	RtrRsnInf Document +PmtRtr ++TxInf +++RtrRsnInf	Name Typ Return Reason Information SCLSDDReturnReasonInformation1	Mandatory Usage Rule: Only one Occurrence of 'Return Reason Information' is allowed.		

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Orgtr Document +PmtRtr ++TxInf +++RtrRsnInf ++++Orgtr	Name Typ Originator SCLDDId5	Mandatory AT-R2 Identification of the type of party initiating the r-message Usage Rule: <u>CORE:</u> Limited to BIC to identify the bank originating the return orto 'Name' to identify the Debtor in the case of refunds. 'Name' is limited to 70 characters in length. <u>B2B:</u> Limited to BIC to identify the bank originating the return.	Angabe der Partei, die die Nachricht pac.004 initiiert hat. Es darf entweder nur der BIC oder der Name (nur für Nicht- Finanzinstitute) angegeben werden. (Schema-Validierung) Wenn der "Name" belegt wurde handelt es sich um einen Refund. Wenn der "BIC" belegt wurde, handelt es sich um einen Return. Im B2B-Verfahren ist nur die Belegung des "BIC" zulässig (d. h. Return). Fehlercode: AG02	Initiation of the R-transaction Only the BIC or the name (solely for non-financial institutions) may be given. (Schema validation) If 'Name' is completed we are dealing with a refund. If 'BIC' is completed we are dealing with a return. Under the B2B scheme it is only permitted to enter the "BIC" (ie a return). Error code: AG02

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Nm Document +PmtRtr ++TxInf +++RtrRsnInf ++++Orgtr +++++Nm	Name Name Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse		Im B2B-Verfahren ist der Name des Return Originators nicht zugelassen. Fehlercode: AG02	Under the B2B scheme, it is not permitted to enter the name of the return originator. Error code: AG02
1..1	Id Document +PmtRtr ++TxInf +++RtrRsnInf ++++Orgtr +++++Id	Name Identification Typ SCLSDDParty3Choice			
1..1	OrgId Document +PmtRtr ++TxInf +++RtrRsnInf ++++Orgtr +++++Id +++++OrgId	Name Organisation Identification Typ SCLSDDOrganisationIdentification2			
1..1	BICorBEI Document +PmtRtr ++TxInf +++RtrRsnInf ++++Orgtr +++++Id +++++OrgId +++++BICorBEI	Name BIC or BEI Typ BICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Rsn Document +PmtRtr ++TxInf +++RtrRsnInf ++++Rsn	Name Typ Reason SCLSDDReturnReason1Choice	Mandatory AT-R3 Reason Code for Non-Acceptance	Rückgabegrund des Returns/ Refunds.	Reason for return/refund.
1..1	Cd Document +PmtRtr ++TxInf +++RtrRsnInf ++++Rsn +++++Cd	Name Typ Code SCLSDDTransactionRejectReason2Code	See Message Element Specifications below.	<p>Alle zulässigen Return/Refund- Rückgabecodes gemäß EPC IG's. (Schema-Validierung)</p> <p>Für Refund-Zahlungen sind nur die Codes MD01 und MD06 zulässig. Fehlercode: XT76</p> <p>Für Return-Zahlungen ist der Code MD06 nicht zulässig. Fehlercode XT13</p> <p>Der Code AC13 darf nur im B2B- Service genutzt werden. Fehlercode: XT33</p> <p>Der Return-Code MD06 darf im B2B-Service nicht genutzt werden. Fehlercode XT33</p>	<p>All acceptable return/refund codes according to the EPC's IGs (schema validation).</p> <p>For refund payments, only the codes 'MD01' and 'MD06' are allowed. Error code: XT76</p> <p>The Code 'MD06' can not be used for return payments. Error code: XT13</p> <p>The Code 'AC13' is only allowed to be used in the SEPA B2B Direct Debit Scheme. Error code: XT33</p> <p>The code MD06 can not be used in the B2B-Service Error code: XT13</p>
Anwendbare Codes / Acceptable Codes					
AC01 AC04 AC06 AC13 AG01 AG02 AM04 AM05 BE05					

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
		Anwendbare Codes / Acceptable Codes			
		MD01			
		MD06			
		MD07			
		MS02			
		MS03			
		RC01			
		RR01			
		RR02			
		RR03			
		RR04			
		SL01			
1..1	OrgnlTxRef Document +PmtRtr ++TxInf +++OrgnlTxRef	Name Typ Original Transaction Reference SCLSDDOriginalTransactionReference1	Mandatory An exact copy of all attributes of the received DS-04 which is being returned Usage Rule: The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction .	Kopie der zurückgegebenen Originalnachricht.	Informations of returned original message.
1..1	IntrBkSttlmDt Document +PmtRtr ++TxInf +++OrgnlTxRef ++++IntrBkSttlmDt	Name Typ Pattern Interbank Settlement Date ISODate [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}	AT-26 Settlement Date of the Collection	Verarbeitungstag der Original-Lastschrift. Bei Weiterleitung der Zahlung an ein anderes CSM ggf. Fehlercode XT74. Dieses Datum der Original-Lastschrift muss kleiner oder gleich Datum des <IntrBkSttlmDt> im <GrpHdr> sein. Fehlercode: DT01	Settlement date of the original direct debit. Where applicable, error code XT74, if payment is forwarded via another CSM. The date of the original direct debit must be the same or before the date of <IntrBkSttlmDt> in <GrpHdr>. Error code: DT01

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	ReqdColltnDt Document +PmtRtr ++TxInf +++OrgnlTxRef ++++ReqdColltnDt	Name Typ Pattern Requested Collection Date ISODate [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}	AT-11 Due date of the Collection	Fälligkeitsdatum des Einzugs aus der ursprünglichen Lastschrift.	Due date of the collection of the original direct debit.
1..1	CdtrSchmeld Document +PmtRtr ++TxInf +++OrgnlTxRef ++++CdtrSchmeld	Name Typ Creditor Scheme Identification SCLSDDCdtrSchmeld	AT-02 Identifier of the Creditor	Identifikation des Zahlungsempfängers aus der Originalnachricht.	Identifier of the creditor from the original message.
1..1	Id Document +PmtRtr ++TxInf +++OrgnlTxRef ++++CdtrSchmeld +++++Id	Name Typ Identification SCLSDDPriateIdentification2			
1..1	PrvtId Document +PmtRtr ++TxInf +++OrgnlTxRef ++++CdtrSchmeld +++++Id ++++++PrvtId	Name Typ Private Identification SCLSDDPrtly2			
1..1	Othr Document +PmtRtr ++TxInf +++OrgnlTxRef ++++CdtrSchmeld +++++Id ++++++PrvtId +++++++Othr	Name Typ Other SCLSDDid10			
1..1	Id Document +PmtRtr	Name Typ Pattern Identification SCLSDDid8 ([A-Za-z0-9][+ ~ / \- : () \.\ ' \s]){1,35}			

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++TxInf +++OrgnlTxRef ++++CdtrSchmeld ++++++Id ++++++PrvtId ++++++Othr ++++++Id				
1..1	SchmeNm Document +PmtRtr ++TxInf +++OrgnlTxRef ++++CdtrSchmeld ++++++Id ++++++PrvtId ++++++Othr ++++++SchmeNm	Name Typ	Scheme Name FinancialIdentificationSchemeName2		
1..1	Prtry Document +PmtRtr ++TxInf +++OrgnlTxRef ++++CdtrSchmeld ++++++Id ++++++PrvtId ++++++Othr ++++++SchmeNm ++++++Prtry	Name Typ	Proprietary SCLSDDId9		
Anwendbare Codes / Acceptable Codes					
SEPA					
0..1	SttlmInf Document +PmtRtr ++TxInf +++OrgnlTxRef ++++SttlmInf	Name Typ	Settlement Information SCLSDDSettlementInformation3		
1..1	SttlmMtd Document +PmtRtr	Name Typ	Settlement Method SCLSDDSettlementMethod1Code	Information über den Settlement Mechanismus.	Information on the settlement mechanism.

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++TxInf +++OrgnlTxRef ++++SttlmInf +++++SttlmMtd			Nur der Code "CLRG" ist zulässig. (Schema-Validierung)	Only the code "CLRG" is allowed. (Schema validation)
Anwendbare Codes / Acceptable Codes					
CLRG					
0..1	ClrSys Document +PmtRtr ++TxInf +++OrgnlTxRef ++++SttlmInf +++++ClrSys	Name Clearing System Typ SCLSDDClearingSystemIdentification1Choice			
1..1	Prtry Document +PmtRtr ++TxInf +++OrgnlTxRef ++++SttlmInf +++++ClrSys +++++Prtry	Name Proprietary Typ Max35Text_Prtry Length 1 .. 35 Pattern \S+.* WhiteSpace collapse		Kennzeichen für das Clearing System. Für den SEPA-Clearer ist nur der Wert "SCL" zulässig. (Schema-Validierung)	Code for the clearing system. For the SEPA-Clearer, only the code "SCL" is allowed. (Schema validation)
Anwendbare Codes / Acceptable Codes					
SCL					
1..1	PmtTplnf Document +PmtRtr ++TxInf +++OrgnlTxRef ++++PmtTplnf	Name Payment Type Information Typ SCLSDDPaymentTypeInfo6	AT-20 Identification code of the Scheme AT-20 Identification code of the B2B Scheme. AT-21 Transaction / Sequence Type AT-59 Category purpose of the Collection		
1..1	SvcLvl Document +PmtRtr ++TxInf +++OrgnlTxRef ++++PmtTplnf +++++SvcLvl	Name Service Level Typ SCLSDDServiceLevel2Choice			
1..1	Cd Document	Name Code Typ SCLSDDServiceLevel1Code		Konstante "SEPA" (Schema-Validierung)	Constant 'SEPA' (Schema validation)

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+PmtRtr ++TxInf +++OrgnlTxRef ++++PmtTpInf +++++SvcLvl +++++Cd				
Anwendbare Codes / Acceptable Codes					
SEPA					
1..1	LclInstrm Document +PmtRtr ++TxInf +++OrgnlTxRef ++++PmtTpInf +++++LclInstrm	Name Local Instrument Typ SCLSDDLocalInstrument1Choice			
1..1	Cd Document +PmtRtr ++TxInf +++OrgnlTxRef ++++PmtTpInf +++++LclInstrm +++++Cd	Name Code Typ ExternalLocalInstrument1Code Length 1 .. 35		Belegung gem. Originalzahlung. Es dürfen nur die Werte "CORE" oder "B2B" enthalten sein (Schema-Validierung). In einem COR-File dürfen nur CORE-Bulks und in einem B2B-File nur B2B-Bulks enthalten sein. Fehlercode: XT43 Eine gemischte Einreichung von B2B- und CORE-Lastschriften in einem Bulk ist nicht zulässig. Fehlercode: XT43	Entry according to original payment. Only the codes 'CORE' or 'B2B' may be entered. (Schema validation) In a COR file only CORE bulks are allowed. In a B2B file only B2B bulks are allowed. Error code: XT43 Mixed submission of B2B and CORE Direct Debits in one bulk is not allowed. Error code: XT43
Anwendbare Codes / Acceptable Codes					
B2B					
CORE					
1..1	SeqTp Document +PmtRtr ++TxInf +++OrgnlTxRef ++++PmtTpInf +++++SeqTp	Name Sequence Type Typ SCLSDDSequenceType1Code		Lastschrift-Sequenztyp (Schema-Validierung)	Direct debit sequence type (Schema validation)

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
		Anwendbare Codes / Acceptable Codes			
		FNAL FRST OOFF RCUR			
0..1	CtgyPurp Document +PmtRtr ++TxInf +++OrgnlTxRef ++++PmtTplnf +++++CtgyPurp	Name Category Purpose Typ CategoryPurpose1Choice		Verschlüsselter Verwendungszweck	Purpose of the transaction
1..1	Cd Document +PmtRtr ++TxInf +++OrgnlTxRef ++++PmtTplnf +++++CtgyPurp +++++Cd	Name Code Typ ExternalCategoryPurpose1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +PmtRtr ++TxInf +++OrgnlTxRef ++++PmtTplnf +++++CtgyPurp +++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	MndtRltdInf Document +PmtRtr ++TxInf +++OrgnlTxRef ++++MndtRltdInf	Name Mandate Related Information Typ SCLSDDMandateRelatedInformation1	AT-01 Unique Mandate reference AT-16 Placeholder for the electronic signature data, if applicable AT- 17 The type of Mandate (paper or e-mandate). AT-18 Identifier of the original Creditor who	Eindeutige Mandatsreferenz. Platzhalter für die elektronische Signatur, falls vorhanden. Identifikator des originalen Zahlungsempfängers, der das Mandat herausgegeben hat. Eindeutige Referenz des Mandats, die vom originalen zahlungsempfänger (Gläubiger)	Unique mandate reference. Placeholder for electronic signature, if available. Identifier of original creditor who issued the mandate. Unique mandate reference as given by the original creditor when the mandate was issued. Reason for changing mandate. Date when

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
			issued the Mandate AT-19 Unique mandate reference as given by the original creditor who issued the mandate AT-24 Reason for Amendment of the Mandate AT-25 Signing date of the Mandate AT-60 Reference of the validation made by the Debtor Bank (if present in DS-03)	beim Ausstellen des Mandats vergeben wurde. Ursache für Änderung des Mandats. Unterschriftsdatum des Mandats.	mandate was signed..
1..1	MndtId Document +PmtRtr ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++MndtId	Name Typ Pattern Mandate Identification SCLSDDId8 ([A-Za-z0-9][+ ? / - : (\\) \., ' \s]){1,35})	Eindeutige Mandatsreferenz	Unique mandate reference
1..1	DtOfSgntr Document +PmtRtr ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++DtOfSgntr	Name Typ Pattern Date Of Signature ISODate [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}		Unterschriftsdatum des Mandats	Date when mandate was signed
0..1	AmdmntInd Document +PmtRtr ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInd	Name Typ Amendment Indicator TrueFalseIndicator		Änderungsindikator des Mandats aus der Originalnachricht, falls vorhanden. Muss "true" oder "false" sein. (Schema-Validierung)	Change indicator of the mandate from the original message, if available. Must be "true" or "false". (Schema validation)
0..1	AmdmntInfDtls Document +PmtRtr ++TxInf +++OrgnlTxRef	Name Typ Amendment Information Details SCLSDDAmendmentInformationDetails1			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	++++MndtRItIdInf ++++AmdmntInfDtIs OrgnlMndtId Document +PmtRtr ++TxInf +++OrgnlTxRef ++++MndtRItIdInf +++++AmdmntInfDtIs ++++++OrgnlMndtId	Name Typ Pattern Original Mandate Identification SCLSDDId8 ([A-Za-z0-9][+ \? \- \: \(\) \.\ ' \s]){1,35}		Eindeutige Referenz des Mandats, die vom originären Zahlungsempfänger (Gläubiger) beim Ausstellen des Mandats vergeben wurde	Unique mandate reference as given by the original creditor when the mandate was issued.
0..1	OrgnlCctrSchmeld Document +PmtRtr ++TxInf +++OrgnlTxRef ++++MndtRItIdInf +++++AmdmntInfDtIs ++++++OrgnlCctrSchmeld	Name Typ Original Creditor Scheme Identification SCLSDDCctrSchmeld1		Identifikator des originären Zahlungsempfängers, der das Mandat herausgegeben hat	Identifier of the original creditor who issued the mandate.
0..1	Nm Document +PmtRtr ++TxInf +++OrgnlTxRef ++++MndtRItIdInf +++++AmdmntInfDtIs ++++++OrgnlCctrSchmeld ++++++Nm	Name Typ Length Pattern WhiteSpace Name Max70Text 1 .. 70 \\S+.* collapse		Name des originären Zahlungsempfängers	Name of original creditor
0..1	Id Document +PmtRtr ++TxInf +++OrgnlTxRef ++++MndtRItIdInf +++++AmdmntInfDtIs ++++++OrgnlCctrSchmeld ++++++Id	Name Typ Identification SCLSDDPrivatIdentification			
1..1	PrvtId Document	Name Typ Private Identification SCLSDDPrty1			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+PmtRtr ++TxInf +++OrgnITxRef ++++MndtRItIdInf +++++AmdmntInfDtIs ++++++OrgnCctrSchmeld +++++++Id +++++++PrvtId				
1..1	Othr Document +PmtRtr ++TxInf +++OrgnITxRef ++++MndtRItIdInf +++++AmdmntInfDtIs ++++++OrgnCctrSchmeld +++++++Id +++++++PrvtId +++++++Othr	Name Typ Other SCLSDDId4			
1..1	Id Document +PmtRtr ++TxInf +++OrgnITxRef ++++MndtRItIdInf +++++AmdmntInfDtIs ++++++OrgnCctrSchmeld +++++++Id +++++++PrvtId +++++++Othr +++++++Id	Name Typ Pattern Identification SCLSDDId8 ([A-Za-z0-9][+ ? / - : (\\) \\. ' \\s]){1,35}		Identifikator des originären Zahlungsempfängers, der das Mandat herausgegeben hat.	Identifier of the original creditor who issued the mandate.
1..1	SchmeNm Document +PmtRtr ++TxInf +++OrgnITxRef	Name Typ Scheme Name FinancialIdentificationSchemeName2			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++++MndtRItIdInf +++++AmdmntInfDtIs +++++++OrgnlCdtrSchmeld +++++++Id +++++++PrvtId +++++++Othr +++++++SchmeNm				
1..1	Prtry Document +PmtRtr ++TxInf +++OrgnlTxRef ++++MndtRItIdInf +++++AmdmntInfDtIs +++++++OrgnlCdtrSchmeld +++++++Id +++++++PrvtId +++++++Othr +++++++SchmeNm +++++++Prtry	Name Typ Proprietary SCLSDDId9		Nur "SEPA" ist zulässig (Schema-Validierung).	Only "SEPA" is allowed. (Schema validation)
Anwendbare Codes / Acceptable Codes					
SEPA					
0..1	OrgnlDbtrAcct Document +PmtRtr ++TxInf +++OrgnlTxRef ++++MndtRItIdInf +++++AmdmntInfDtIs +++++++OrgnlDbtrAcct	Name Typ Original Debtor Account SCLSDDCashAccount8			
1..1	Id Document +PmtRtr ++TxInf +++OrgnlTxRef ++++MndtRItIdInf +++++AmdmntInfDtIs +++++++OrgnlDbtrAcct +++++++Id	Name Typ Identification SCLSDDAccountIdentification4Choice			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	IBAN Document +PmtRtr ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlDbtrAcct +++++++Id ++++++IBAN	Name IBAN Typ IBANIdentifier Pattern [a-zA-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}			
1..1	Othr Document +PmtRtr ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlDbtrAcct +++++++Id ++++++Othr	Name Other Typ SCLSDDOrgnlDbtrAcctOther2			
1..1	Id Document +PmtRtr ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlDbtrAcct +++++++Id ++++++Othr ++++++Id	Name Identification Typ Max34Text Length 1 .. 34 Pattern \S+.* WhiteSpace collapse			
0..1	OrgnlDbtrAgt Document +PmtRtr ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlDbtrAgt	Name Original Debtor Agent Typ SCLSDDOrgnlDbtrAgt			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	FinInstnId Document +PmtRtr ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlDbtrAgt +++++++FinInstnId	Name Typ Financial Institution Identification SCLSDDOrgnlDbtrAgt1			
1..1	BIC Document +PmtRtr ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlDbtrAgt +++++++FinInstnId +++++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}			
1..1	Othr Document +PmtRtr ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlDbtrAgt +++++++FinInstnId +++++++Othr	Name Typ Other SCLSDDOrgnlDbtrAgtOther2			
1..1	Id Document +PmtRtr ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlDbtrAgt +++++++FinInstnId +++++++Othr +++++++Id	Name Typ Length Pattern WhiteSpace Identification Max35Text 1 .. 35 \\S+.* collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	ElctrcnSgnt Document +PmtRtr ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++ElctrcnSgnt	Name Electronic Signature Typ Max1025Text Length 1 .. 1025 Pattern \S+.* WhiteSpace collapse		Platzhalter für elektronische Unterschrift	Placeholder for electronic signature
0..1	Rmtlnf Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Rmtlnf	Name Remittance Information Typ SCLSDDRemittanceInformation1	AT-22 Remittance Information	Strukturierter oder unstrukturierter Verwendungszweck. (Schema-Validierung)	Structured or unstructured remittance information. (Schema validation)
1..1	Ustrd Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Rmtlnf +++++Ustrd	Name Unstructured Typ Max140Text Length 1 .. 140 Pattern \S+.* WhiteSpace collapse			
1..1	Strd Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Rmtlnf +++++Strd	Name Structured Typ SCLSDDStructuredRemittanceInformation6		Im strukturierten Verwendungszweck dürfen max. 140 Zeichen vorkommen. Es zählen nur die Informationen innerhalb der XML-Tags <Strd> und </Strd>. Es werden die in diesem Bereich liegenden Tags inklusive Inhalt gezählt. Fehlercode: XT33 Alle ISO 20022 Feldoptionen sind erlaubt.	Structured remittance information must not exceed 140 characters. Only information within the <Strd> and </Strd> elements is counted. All tags and their contents located in this area are counted. Error code: XT33 All ISO 20022 field options are allowed.

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	CdtrRefInf Document +PmtRtr ++TxInf +++OrgnlTxRef ++++RmtInf +++++Strd ++++++CdtrRefInf	Name Typ Creditor Reference Information SCLSDDCreditorReferenceInformation2			
1..1	Tp Document +PmtRtr ++TxInf +++OrgnlTxRef ++++RmtInf +++++Strd ++++++CdtrRefInf ++++++Tp	Name Typ Type SCLSDDCreditorReferenceType2			
1..1	CdOrPrtry Document +PmtRtr ++TxInf +++OrgnlTxRef ++++RmtInf +++++Strd ++++++CdtrRefInf ++++++Tp ++++++CdOrPrtry	Name Typ Code or Proprietary SCLSDDCreditorReferenceType1Choice			
1..1	Cd Document +PmtRtr ++TxInf +++OrgnlTxRef ++++RmtInf +++++Strd ++++++CdtrRefInf ++++++Tp ++++++CdOrPrtry ++++++Cd	Name Typ Code SCLSDDDocumentType3Code			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
Anwendbare Codes / Acceptable Codes					
SCOR					
0..1	Issr Document +PmtRtr ++TxInf +++OrgnTxRef ++++RmtInf +++++Strd ++++++CdtrRefInf ++++++Tp +++++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	Ref Document +PmtRtr ++TxInf +++OrgnTxRef ++++RmtInf +++++Strd ++++++CdtrRefInf +++++++Ref	Name Reference Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	UltmtDbtr Document +PmtRtr ++TxInf +++OrgnTxRef ++++UltmtDbtr	Name Uitimate Debtor Typ SCLSDDDPartyIdentification10	AT-15 Name of the Debtor Reference Party AT-37 Identification code of the Debtor Reference Party	Abweichender Zahler	Ultimate creditor
0..1	Nm Document +PmtRtr ++TxInf +++OrgnTxRef ++++UltmtDbtr +++++Nm	Name Name Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse		Name des abweichenden Zahlers aus der Originalnachricht	Name of the ultimate creditor

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	Id Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id	Name Typ Identification SCLSDDParty4Choice		Identifikation des abweichenden Zahlers	Identifier of the ultimate creditor
1..1	Orgld Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++Orgld	Name Typ Organisation Identification SCLSDDOrganisationIdentification4			
1..1	BICorBEI Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++Orgld +++++++BICorBEI	Name Typ Pattern BIC or BEI SCLSDDAnyBICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}			
1..1	Othr Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++Orgld +++++++Othr	Name Typ Other SCLSDDGenericOrganisationIdentification1			
1..1	Id Document +PmtRtr	Name Typ Length Pattern Identification Max35Text 1 .. 35 \\S+.*			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++TxInf +++OrgnITxRef ++++UltmtDbtr +++++Id ++++++OrgId ++++++Othr ++++++Id	WhiteSpace collapse			
0..1	SchmeNm Document +PmtRtr ++TxInf +++OrgnITxRef ++++UltmtDbtr +++++Id ++++++OrgId ++++++Othr ++++++SchmeNm	Name Typ Scheme Name SCLSDDOrganisationIdentificationSchemeName1Choice			
1..1	Cd Document +PmtRtr ++TxInf +++OrgnITxRef ++++UltmtDbtr +++++Id ++++++OrgId ++++++Othr ++++++SchmeNm ++++++Cd	Name Typ Length Pattern WhiteSpace Code SCLSDDExternalOrganisationIdentification1Code 1 .. 4 \S+* collapse			
1..1	Prtry Document +PmtRtr ++TxInf +++OrgnITxRef ++++UltmtDbtr +++++Id ++++++OrgId ++++++Othr ++++++SchmeNm ++++++Prtry	Name Typ Length Pattern WhiteSpace Proprietary Max35Text 1 .. 35 \S+* collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	Issr Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++Orgld +++++++Othr ++++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	PrvtId Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId	Name Private Identification Typ SCLSDDPersonIdentification5			
1..1	DtAndPlcOfBirth Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth	Name Date and Place of Birth Typ DateAndPlaceOfBirth			
1..1	BirthDt Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth +++++++BirthDt	Name Birth Date Typ ISODate Pattern [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}			
0..1	PrvcOfBirth	Name Province of Birth Typ Max35Text			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth +++++++PrvcOfBirth	Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	CityOfBirth Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth +++++++CityOfBirth	Name City of Birth Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	CtryOfBirth Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth +++++++CtryOfBirth	Name Country of Birth Typ CountryCode Pattern [A-Z]{2,2}			
1..1	Othr Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++Othr	Name Other Typ SCLSDDGenericPersonIdentification1			
1..1	Id	Name Identification Typ Max35Text			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++Othr +++++++Id	Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	SchmeNm Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm	Name Scheme Name Typ SCLSDDPersonIdentificationSchemeName1 Choice			
1..1	Cd Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm +++++++Cd	Name Code Typ SCLSDDExternalPersonIdentification1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm +++++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	Issr Document +PmtRtr ++TxInf +++OrgnTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++Othr +++++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	Dbtr Document +PmtRtr ++TxInf +++OrgnTxRef ++++Dbtr	Name Debtor Typ SCLSDDPartyIdentification9	AT-14 Name of the Debtor AT-09 Address of the Debtor AT-27 Debtor Identification	Zahler	Debtor
1..1	Nm Document +PmtRtr ++TxInf +++OrgnTxRef ++++Dbtr +++++Nm	Name Name Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse		Name des Zahlers oder Ersatzinformationen aus der Originalnachricht	Name of debtor or additional informations accordig the original payment
0..1	PstlAdr Document +PmtRtr ++TxInf +++OrgnTxRef ++++Dbtr +++++PstlAdr	Name Postal Address Typ SCLSDDPostalAddress1		Adresse des Zahlers	Address of debtor
0..1	Ctry Document +PmtRtr ++TxInf +++OrgnTxRef ++++Dbtr +++++PstlAdr +++++Ctry	Name Country Typ CountryCode Pattern [A-Z]{2,2}		Land des Zahlers	Country of debtor

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..2	AdrLine Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Dbtr +++++PstlAdr ++++++AdrLine	Name Address Line Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse			
0..1	Id Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id	Name Identification Typ SCLSDDParty4Choice	(Identifikation des Zahlungspflichtigen.	Identifier of debtor
1..1	OrgId Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++OrgId	Name Organisation Identification Typ SCLSDDOrganisationIdentification4		Darf nicht gleichzeitig mit Id/Prvtld (siehe unten) angegeben werden. (Schema-Validierung) Alle ISO 20022 Optionen sind erlaubt.	May not be given simultaneously with <Id><Prvtld> (see below). (Schema validation) All ISO 20022 options are allowed
1..1	BICorBEI Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++OrgId +++++++BICorBEI	Name BIC or BEI Typ SCLSDDAnyBICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}			
1..1	Othr Document +PmtRtr ++TxInf +++OrgnlTxRef	Name Other Typ SCLSDDGenericOrganisationIdentification1			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++++Dbtr +++++Id +++++OrgId +++++Othr				
1..1	Id Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id +++++OrgId +++++Othr +++++Id	Name Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	SchmeNm Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id +++++OrgId +++++Othr +++++SchmeNm	Name Scheme Name Typ SCLSDDOrganisationIdentificationSchemeName1Choice			
1..1	Cd Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id +++++OrgId +++++Othr +++++SchmeNm +++++Cd	Name Code Typ SCLSDDExternalOrganisationIdentification1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +PmtRtr ++TxInf	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.*			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+++OrgnlTxRef ++++Dbtr +++++Id +++++Orgld +++++Othr +++++SchmeNm +++++Prtry	WhiteSpace collapse			
0..1	Issr Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id +++++Orgld +++++Othr +++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	Prvtld Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id +++++Prvtld	Name Private Identification Typ SCLSDDPersonIdentification5		Darf nicht gleichzeitig mit Id/Orgld (siehe oben) angegeben werden. (Schema-Validierung) Alle ISO 20022 Optionen sind erlaubt.	May not be given simultaneously with <Id><Orgld> (see below). (Schema validation) All ISO 20022 options are allowed
1..1	DtAndPlcOfBirth Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id +++++Prvtld +++++DtAndPlcOfBirth	Name Date and Place of Birth Typ DateAndPlaceOfBirth			
1..1	BirthDt Document +PmtRtr ++TxInf +++OrgnlTxRef	Name Birth Date Typ ISODate Pattern [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++++Dbtr +++++Id +++++PrvtId +++++DtAndPlcOfBirth +++++BirthDt				
0..1	PrvcOfBirth Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id +++++PrvtId +++++DtAndPlcOfBirth +++++PrvcOfBirth	Name Province of Birth Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	CityOfBirth Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id +++++PrvtId +++++DtAndPlcOfBirth +++++CityOfBirth	Name City of Birth Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	CtryOfBirth Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id +++++PrvtId +++++DtAndPlcOfBirth +++++CtryOfBirth	Name Country of Birth Typ CountryCode Pattern [A-Z]{2,2}			
1..1	Othr Document +PmtRtr ++TxInf	Name Other Typ SCLSDDGenericPersonIdentification1			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+++OrgnlTxRef ++++Dbtr +++++Id ++++++PrvtId +++++++Othr				
1..1	Id Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++PrvtId +++++++Othr +++++++Id	Name Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	SchmeNm Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm	Name Scheme Name Typ SCLSDDPersonIdentificationSchemeName1 Choice			
1..1	Cd Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm +++++++Cd	Name Code Typ SCLSDDExternalPersonIdentification1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +PmtRtr	Name Proprietary Typ Max35Text Length 1 .. 35			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++PrvtId ++++++Othr +++++++SchmeNm +++++++Prtry	Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++PrvtId ++++++Othr +++++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	DbtrAcct Document +PmtRtr ++TxInf +++OrgnlTxRef ++++DbtrAcct	Name Debtor Account Typ SCLSDDCashAccount7	AT-07 Account Number of (IBAN) of the Debtor	Kontonummer des Zahlungspflichtigen.	Kontonummer des Zahlungspflichtigen.
1..1	Id Document +PmtRtr ++TxInf +++OrgnlTxRef ++++DbtrAcct +++++Id	Name Identification Typ SCLSDDAccountIdentification3Choice			
1..1	IBAN Document +PmtRtr ++TxInf +++OrgnlTxRef ++++DbtrAcct +++++Id ++++++IBAN	Name IBAN Typ IBANIdentifier Pattern [a-zA-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}		IBAN des Zahlers	IBAN des Zahlers

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	DbtrAgt Document +PmtRtr ++TxInf +++OrgnlTxRef ++++DbtrAgt	Name Typ Debtor Agent SCLSDDBranchAndFinancialInstitutionIdentification3	AT-13 BIC of the Debtor Bank	BIC des Zahlungsdienstleisters des Zahlers	BIC of debtor agent
1..1	FinInstnld Document +PmtRtr ++TxInf +++OrgnlTxRef ++++DbtrAgt +++++FinInstnld	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Choice			
1..1	BIC Document +PmtRtr ++TxInf +++OrgnlTxRef ++++DbtrAgt +++++FinInstnld ++++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}		Debtor Agent BIC ist Bestandteil der Doppeleinreichungskontrolle auf Einzelsatzebene Fehlercode: AM05 Prüfung nur bei Weiterleitung der Zahlung vom SEPA-Clearer an STEP2: BIC muss ein über die Bundesbank registrierter Reachable BIC des entsprechenden SDD Service der EBA CLEARING sein. Fehlercode: PY01	Debtor agent BIC is included in the duplication check at single record level. Error code: AM05 Check only if the direct debit is forwarded from the SEPA-Clearer to STEP2: BIC must belong to a registered reachable BIC of the respective STEP2 SDD Service via the Deutsche Bundesbank. Error code: PY01
1..1	CdtrAgt Document +PmtRtr ++TxInf +++OrgnlTxRef ++++CdtrAgt	Name Typ Creditor Agent SCLSDDBranchAndFinancialInstitutionIdentification3	AT-12 BIC of the Creditor Bank	BIC des Zahlungsdienstleisters des Zahlungsempfängers	BIC of the Creditor Bank
1..1	FinInstnld Document +PmtRtr ++TxInf +++OrgnlTxRef ++++CdtrAgt +++++FinInstnld	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Choice			

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	BIC Document +PmtRtr ++TxInf +++OrgnlTxRef ++++CdtrAgt +++++FinInstnld ++++++BIC	Name BIC Typ BICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}		Gültigkeit des BIC anhand des SCL-Directorys. Fehlercode: XT27 Prüfung nur bei Weiterleitung der Zahlung vom SEPA-Clearer an STEP2: BIC muss ein registrierter direkter Teilnehmer oder Reachable BIC am entsprechenden STEP2 SDD Service sein. Fehlercode: PY01	Validity of BIC using SEPA BIC Directory. Error code: XT27 Check only if the direct debit is forwarded from the SEPA-Clearer to STEP2: BIC must belong to a registered reachable BIC of the respective STEP2 SDD Service via the Deutsche Bundesbank .. Error code: PY01
1..1	Cdtr Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Cdtr	Name Creditor Typ SCLSDDId2	AT-03 Name of the Creditor AT-05 Address of the Creditor	Zahlungsempfänger	Creditor
1..1	Nm Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Cdtr +++++Nm	Name Name Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse		Name des Zahlungsempfängers.	Name of creditor.
0..1	PstlAdr Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Cdtr +++++PstlAdr	Name Postal Address Typ SCLSDDPostalAddress1		Adresse des Zahlungsempfängers.	Address of creditor
0..1	Ctry Document	Name Country Typ CountryCode		Land des Zahlungsempfängers.	Country of creditor

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+PmtRtr ++TxInf +++OrgnlTxRef ++++Cdtr +++++PstlAdr +++++Ctry	Pattern [A-Z]{2,2}			
0..2	AdrLine Document +PmtRtr ++TxInf +++OrgnlTxRef ++++Cdtr +++++PstlAdr +++++AdrLine	Name Typ Length Pattern WhiteSpace Address Line Max70Text 1 .. 70 \S+.* collapse			
1..1	CdtrAcct Document +PmtRtr ++TxInf +++OrgnlTxRef ++++CdtrAcct	Name Typ Creditor Account SCLSDDCashAccount7	AT-04 Account number (IBAN) of the Creditor	Kontonummer des Zahlungsempfängers.	Account number of creditor
1..1	Id Document +PmtRtr ++TxInf +++OrgnlTxRef ++++CdtrAcct ++++Id	Name Typ Identification SCLSDDAccountIdentification3Choice			
1..1	IBAN Document +PmtRtr ++TxInf +++OrgnlTxRef ++++CdtrAcct ++++Id +++++IBAN	Name Typ Pattern IBAN IBANIdentifier [a-zA-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}		IBAN des Zahlungsempfängers.	IBAN of creditor.
0..1	UltmtCdtr Document +PmtRtr	Name Typ Ultimate Creditor SCLSDDPartyIdentification10	AT-38 Name of the Creditor Reference Party AT-39 Identification code of the Creditor Reference Party	Abweichender Zahlungsempfänger	Ultimate creditor

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	Nm Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Nm	Name Name Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse		Name des abweichenden Zahlungsempfängers	Name of the ultimate creditor
0..1	Id Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id	Name Identification Typ SCLSDDParty4Choice			
1..1	OrgId Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++OrgId	Name Oranisation Identification Typ SCLSDDOrganisationIdentification4			
1..1	BICorBEI Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++OrgId ++++++BICorBEI	Name BIC or BEI Typ SCLSDDAnyBICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}			
1..1	Othr Document +PmtRtr ++TxInf	Name Other Typ SCLSDDGenericOrganisationIdentification1			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++Orgld +++++++Othr				
1..1	Id Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++Orgld +++++++Othr +++++++Id	Name Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	SchmeNm Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++Orgld +++++++Othr +++++++SchmeNm	Name Scheme Name Typ SCLSDDOrganisationIdentificationSchemeName1Choice			
1..1	Cd Document +PmtRtr ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++Orgld +++++++Othr +++++++SchmeNm +++++++Cd	Name Code Typ SCLSDDExternalOrganisationIdentification1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +PmtRtr	Name Proprietary Typ Max35Text Length 1 .. 35			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++TxInf +++OrgnTxRef ++++UltmtCdtr +++++Id ++++++OrgId ++++++Othr +++++++SchmeNm +++++++Prtry	Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +PmtRtr ++TxInf +++OrgnTxRef ++++UltmtCdtr +++++Id ++++++OrgId ++++++Othr +++++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	PrvtId Document +PmtRtr ++TxInf +++OrgnTxRef ++++UltmtCdtr +++++Id ++++++PrvtId	Name Private Identification Typ SCLSDDPersonIdentification5			
1..1	DtAndPlcOfBirth Document +PmtRtr ++TxInf +++OrgnTxRef ++++UltmtCdtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth	Name Date and Place of Birth Typ DateAndPlaceOfBirth			
1..1	BirthDt Document +PmtRtr ++TxInf	Name Birth Date Typ ISODate Pattern [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+++OrgnlTxRef +++UltmtCdtr +++++Id +++++PrvtId +++++DtAndPlcOfBirth +++++BirthDt				
0..1	PrvcOfBirth Document +PmtRtr ++TxInf +++OrgnlTxRef +++UltmtCdtr +++++Id +++++PrvtId +++++DtAndPlcOfBirth +++++PrvcOfBirth	Name Province of Birth Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	CityOfBirth Document +PmtRtr ++TxInf +++OrgnlTxRef +++UltmtCdtr +++++Id +++++PrvtId +++++DtAndPlcOfBirth +++++CityOfBirth	Name City of Birth Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	CtryOfBirth Document +PmtRtr ++TxInf +++OrgnlTxRef +++UltmtCdtr +++++Id +++++PrvtId +++++DtAndPlcOfBirth +++++CtryOfBirth	Name Country of Birth Typ CountryCode Pattern [A-Z]{2,2}			
1..1	Othr Document +PmtRtr	Name Other Typ SCLSDDGenericPersonIdentification1			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++TxInf +++OrgnTxRef ++++UltmtCdtr +++++Id ++++++PrvtId ++++++Othr				
1..1	Id Document +PmtRtr ++TxInf +++OrgnTxRef ++++UltmtCdtr +++++Id ++++++PrvtId ++++++Othr ++++++Id	Name Typ Length Pattern WhiteSpace	Identification Max35Text 1 .. 35 \S+* collapse		
0..1	SchmeNm Document +PmtRtr ++TxInf +++OrgnTxRef ++++UltmtCdtr +++++Id ++++++PrvtId ++++++Othr ++++++SchmeNm	Name Typ	Scheme Name SCLSDDPersonIdentificationSchemeName1 Choice		
1..1	Cd Document +PmtRtr ++TxInf +++OrgnTxRef ++++UltmtCdtr +++++Id ++++++PrvtId ++++++Othr ++++++SchmeNm ++++++Cd	Name Typ Length Pattern WhiteSpace	Code SCLSDDExternalPersonIdentification1Code 1 .. 4 \S+* collapse		
1..1	Prtry Document	Name Typ Length	Proprietary Max35Text 1 .. 35		

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+PmtRtr ++TxInf +++OrgnITxRef ++++UltmtCdtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm +++++++Prtry	Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +PmtRtr ++TxInf +++OrgnITxRef ++++UltmtCdtr +++++Id ++++++PrvtId +++++++Othr +++++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			

Nachricht

SEPA Direct Debit – Interbank Reversal Instruction for a Collection (DS-07)

Verwendung des Payment Reversal (pacs.007.001.02)

Die Nachricht wird verwendet, um die Rückerstattung einer Lastschrift vom Zahlungsdienstleister des Zahlungsempfängers zum Zahlungsdienstleister des Zahlers zu transportieren.

Diese Nachricht berücksichtigt **nur** die Rückerstattung einzelner Lastschriften. Rückerstattungen auf Bulk-Ebene werden vom SEPA-Clearer **nicht** unterstützt.

Hinweise:

- Attribut R1 in DS-07 wird angezeigt durch den „Message Name“ ‘pacs.007.001’ und „Original Message Name Identification“ ‘pacs.003.001’
- Attribut R2 wird angezeigt durch eine Kombination des „Reversal Originator“ mit dem “Reversal Reason“.
- „Original“-Nachrichtenelemente basieren auf DS-04-Attributen.

ISO Nachrichtenstruktur

Eine Interbank Reversal Instruction Nachricht beinhaltet:

- einen einzelnen Group Header.
- eine einzelne Original Group Header Sequenz
- eine oder mehrere „Transaction Information“-Sequenzen, von denen jede eine Rückerstattung enthält, wie in DS-07 definiert.

Group Header

Der Group Header enthält Informationen, die für die Verarbeitung der gesamten Nachricht benötigt werden.

Use of the Payment Reversal (pacs.007.001.02)

This message is used to transport the Interbank Reversal Instruction for a Collection from the Creditor bank to the Debtor bank. The message caters for single reversal instructions **only**. Bulk-level reversal instructions are **not** supported by the SEPA-Clearer.

Notes:

- Attribute R1 in DS-07 is indicated by the 'Message Name', 'pacs.007.001', and the 'Original Message Name Identification', set to 'pacs.003.001'.
- Attribute R2 is indicated by the combination of the Reversal 'originator' with the Reversal 'reason'.
- 'Original' message elements are based on DS-04 attributes.

ISO message structure

A Interbank Reversal Instruction message contains:

- a single Group Header
- a single Original Group Information sequence
- one or more 'Transaction Information' sequences, each of which contains the transaction date of an individual underlying direct debit to be reversed, as defined in DS-07.

Group header

The group header contains information required to process the entire message.

Nachrichtenstruktur / Message structure

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document Document	Typ Document			
1..1	FIToFIPmtRvsl Document +FIToFIPmtRvsl	Typ FIToFIPaymentReversalV02			
1..1	GrpHdr Document +FIToFIPmtRvsl ++GrpHdr	Name Typ Group Header SCLSDDGroupHeader9		Enthält allgemeine Informationen der Verarbeitung, die auf jede einzelne Zahlung zutreffen.	The group header contains general processing information which applies to the whole message.
1..1	MsgId Document +FIToFIPmtRvsl ++GrpHdr +++MsgId	Name Typ Pattern Message Identification SCLSDDId7 ([A-Za-z0-9][+ \? / - :\(\) \.\ , ']){1,35}		Referenz-Nr. des Bulks MsgId ist Bestandteil der Doppeleinreichungskontrolle auf Bulkebene (über 15 Kalendertage eindeutige Referenz). Fehlercode: B14 Die ersten 8 bzw. 11 Stellen der MsgId müssen im IDF mit dem BIC des Instructing Agent übereinstimmen. Der Rest des Feldes ist frei verfügbar. Fehlercode: B98	Bulk reference number. <MsgId> is part of duplication check at bulk level (unique reference over 15 calendar days). Error code: B14 The first 8 or 11 characters of <MsgId> must match the BIC of the instructing agent in the IDF. The rest of the field can be freely defined. Error code: B98
1..1	CreDtTm Document +FIToFIPmtRvsl ++GrpHdr +++CreDtTm	Name Typ Pattern Creation Date and Time ISODateTime [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}[T][0-9]{2,2}: [0-9]{2,2}:[0-9]{2,2}\S*		Erstellungsdatum und -zeit des Bulks	Bulk creation date and time.
1..1	NbOfTxs Document +FIToFIPmtRvsl ++GrpHdr +++NbOfTxs	Name Typ Pattern Number Of Transactions Max15NumericText [0-9]{1,15}		Gesamtanzahl der Einzeltransaktionen im Bulk. Darf bei Einlieferung in den SCL nicht "Null" sein, da Reversal auf Bulk-Ebene nicht unterstützt wird (Schema-Validierung).	Total number of single transactions in the bulk. May not be 'zero' at point of submission to SCL as reversal is not supported at bulk level (Schema validation).

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
				<p>Darf nicht größer sein als 100.000 (maximaler Parameter der Datensätze im Bulk). Fehlercode: B02</p> <p>Gesamtanzahl der Datensätze muss der tatsächlichen Anzahl der Einzeldatensätze im Bulk entsprechen. Fehlercode: B03</p>	<p>Must not exceed 100,000 (maximum parameter of data records in the bulk). Error code: B02</p> <p>Total number of data records must be equal to the actual number of individual data records in the bulk. Error code: B03</p>
1..1	<p>GrpRvsl</p> <p>Document +FIToFIPmtRvsl ++GrpHdr +++GrpRvsl</p>	<p>Name Group Reversal Typ restriction (xs:string)</p>	<p>Mandatory Usage Rule: Only "false" is allowed.</p>	<p>Kennzeichnung, ob es sich um ein Bulk-Reversal oder um Reversal einzelner Zahlung(en) handelt.</p> <p>Reversal auf Bulk-Ebene wird nicht unterstützt. Bei Einlieferung in den SCL daher nur Belegung mit "false" zulässig. (Schema-Validierung)</p>	<p>Shows whether we are dealing with a bulk reversal or the reversal of individual payments.</p> <p>Reversal at bulk level is not supported. Therefore, at time of submission to the SCL may only be completed with 'FALSE'. (Schema validation)</p>
Anwendbare Codes / Acceptable Codes					
		false			
1..1	<p>TtIRvsdIntrBkSttlmAmt</p> <p>Document +FIToFIPmtRvsl ++GrpHdr +++TtIRvsdIntrBkSttlmAmt</p>	<p>Name Total Reversed Interbank Settlement Amount Typ SCLSDDCurrencyAndAmount_Total FractionDigits 2 TotalDigits 18 Inclusive 0.01 .. 99999999999999.99 Pattern [0-9]{0,15}(\.([0-9]{0,2}))?{0,1}</p>	<p>Mandatory AT-44 Amount of the reversal in Euro Usage Rule: Only 'EUR' is allowed. Amount must be 0.01 or more and 99999999999999.99 or less. Format Rule: The fractional part has a maximum of two digits.</p>	<p>Gesamtsumme der Einzeltransaktionen (Reversals) im Bulk</p> <p>Bis zu 15 Zeichen sind im ganzzahligen Wertebereich erlaubt. Weiterhin maximal bis zwei Nachkommastellen erlaubt. (Schema-Validierung)</p> <p>Währungskennzeichen ist immer "EUR". (Schema-Validierung)</p> <p>Die angegebene Gesamtsumme muss der Summe aus den Einzeltransaktionen des Bulks entsprechen. Fehlercode: B05</p>	<p>Total number of single transactions (reversals) in the bulk.</p> <p>Integer value of up to 15 characters is allowed. Maximum number of decimal places allowed remains two. (Schema validation)</p> <p>Currency symbol is always 'EUR'. (Schema validation)</p> <p>The total amount given must equal the sum of the single transactions in the bulk. Error code: B05</p>

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
				Betragsangabe muss mindestens den Wert 0.01 oder mehr enthalten und darf den Wert 9999999999999999.99 nicht übersteigen. (Schema-Validierung)	Amount must be at least 0.01 and no more than 9999999999999999.99. (Schema validation)
1..1	IntrBkSttlmDt Document +FIToFIPmtRvsl ++GrpHdr +++IntrBkSttlmDt	Name Typ Pattern Interbank Settlement Date ISODate [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}	Mandatory AT-R4- Settlement Date for the reversal instruction	Abrechnungsdatum des Reversals. Geschäftstag an dem die Reversals des Bulks im SEPA-Clearer verarbeitet werden sollen. Bei Einlieferung bis 10:00 Uhr (Core) bzw. 11:00 Uhr (B2B) muss hier der aktuelle Geschäftstag des SEPA-Clearers angegeben werden. Bei Einlieferungen nach 15:00 Uhr (Core) bzw. 13:00 Uhr (B2B) muss hier der nächste Geschäftstag des SEPA-Clearers angegeben werden. Fehlercode: B15 <IntrBkSttlmDt> ist Bestandteil der Doppeleinreichungskontrolle auf Datei- (eindeutige Referenz über 15 Kalendertage) und Einzelsatzebene.	Settlement date for reversal. Business day for processing of the reversal in the SEPA-Clearer. For submission not later than 10.00 (Core) respectively 11.00 (B2B) the current operating day of the SEPA-Clearer must be given. For submissions after 15.00 (Core) respectively 13.00 (B2B) the next operating day of the SEPA-Clearer must be given. Error code: B15 <IntrBkSttlmDt> is part of duplication check at bulk level (unique reference over 15 calendar days) and single record level.
1..1	SttlmInf Document +FIToFIPmtRvsl ++GrpHdr +++SttlmInf	Name Typ Settlement Information SCLSDDSettlementInformation1			
1..1	SttlmMtd Document +FIToFIPmtRvsl ++GrpHdr +++SttlmInf ++++SttlmMtd	Name Typ Settlement Method SCLSDDSettlementMethod1Code	Only CLRG, INGA and INDA are allowed.	Information über den Settlement Mechanismus. Nur der Code "CLRG" ist zulässig. (Schema-Validierung)	Information on the settlement mechanism. Only the code 'CLRG' is allowed. (Schema validation)

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
Anwendbare Codes / Acceptable Codes					
CLRG					
1..1	ClrSys Document +FIToFIPmtRvsl ++GrpHdr +++Stlmlnf ++++ClrSys	Name Clearing System Typ SCLSDDClearingSystemIdentification1Choice			
1..1	Prtry Document +FIToFIPmtRvsl ++GrpHdr +++Stlmlnf ++++ClrSys ++++Prtry	Name Proprietary Typ Max35Text_Prtry Length 1 .. 35 Pattern \S+.* WhiteSpace collapse		Kennzeichen für das Clearing System. Für den SEPA-Clearer ist nur der Wert "SCL" zu verwenden. (Schema-Validierung)	Code for the clearing system. For the SEPA-Clearer, only the code 'SCL' may be used. (Schema validation)
Anwendbare Codes / Acceptable Codes					
SCL					
0..1	InstgAgt Document +FIToFIPmtRvsl ++GrpHdr +++InstgAgt	Name Instructing Agent Typ SCLSDDBranchAndFinancialInstitutionIdentification3	Usage Rule: Only BIC is allowed.	Nur bei Einlieferungen in den SEPA-Clearer zu belegen. Hier ist der BIC des SCL-Teilnehmers einzustellen, der zu dem technischen Unterkonto/Sub-Account in T2 gehört, das für die Durchführung der geldlichen Verrechnung herangezogen wird. Bestandteil der Doppelseinreichungskontrolle (geschäftstäglich eindeutige Referenz).	Only to be used for submissions to the SEPA-Clearer. Allocation of the BIC of the SCL participant which is linked with the T2 sub-account assigned for settlement with the SEPA-Clearer. Part of duplication check (unique reference per business day).
1..1	FinInstnld Document +FIToFIPmtRvsl ++GrpHdr +++InstgAgt ++++FinInstnld	Name Financial Institution Identification Typ SCLSDDFinancialInstitutionIdentification5Choice			
1..1	BIC Document +FIToFIPmtRvsl	Name BIC Typ BICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3})		BIC muss im Input Debit File (IDF) enthalten und einreichungsberechtigt sein. Fehlercode: B10	BIC must be contained in the input debit file (IDF). Error code: B10

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	++GrpHdr +++InstgAgt ++++FinInstnId ++++BIC	{0,1}		Prüfung gegen den BIC im File Header (Sending Institution) auf Einreichungsberechtigung des Kommunikationspartners. Fehlercode: B10	Communication partner's authorisation to submit verified against the BIC in the file header (Sending Institution). Error code: B10
0..1	InstdAgt Document +FIToFIPmtRvsl ++GrpHdr +++InstdAgt	Name Typ Instructed Agent SCLSDDBranchAndFinancialInstitutionIdentification3	Usage Rule: Only BIC is allowed.	Nur bei Auslieferungen aus dem SEPA-Clearer belegt. Hier ist der BIC des SCL-Teilnehmers eingestellt, der zu dem technischen Unterkonto/Sub-Account in T2 gehört, das für die Durchführung der geldlichen Verrechnung herangezogen wird.	Only used for deliveries from the SEPA-Clearer. Allocation of the BIC of the SCL participant which is linked with the T2 sub-account assigned for settlement with the SEPA-Clearer.
1..1	FinInstnId Document +FIToFIPmtRvsl ++GrpHdr +++InstdAgt ++++FinInstnId	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Choice			
1..1	BIC Document +FIToFIPmtRvsl ++GrpHdr +++InstdAgt ++++FinInstnId ++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}		BIC darf nur im Settled Debit File (SDF) enthalten sein. Fehlercode: B11	BIC may only be contained in the settled debit file (SDF). Error code: B11
1..1	OrgnGrpInf Document +FIToFIPmtRvsl ++OrgnGrpInf	Name Typ Original Group Information SCLSDDOriginalGroupInformation5		Enthält allgemeine Informationen des Original Group Headers, die auf alle Zahlungen zutreffen. Reversal auf Bulk-Ebene wird nicht unterstützt.	Contains general information from the original group header which is relevant for all payments. Reversal at bulk level is not supported.
1..1	OrgnMsgId Document +FIToFIPmtRvsl ++OrgnGrpInf +++OrgnMsgId	Name Typ Pattern Original Message Identification SCLSDDId7 ([A-Za-z0-9][+ ~ / \\- : (\\) \\. , '])(1,35}		Referenz-Nr. des ursprünglichen Bulks. Bei Auslieferung des SCL, die aus Einlieferungen anderer CSM resultieren kann hier ggf. der Wert "UNMATCHED" stehen.	Reference (<MsgId>) of original bulk. In the case of deliveries from the SCL which result from submissions from another CSM, the entry 'UNMATCHED' is allowed where necessary

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	OrgnlMsgNmId Document +FIToFIPmtRvsl ++OrgnlGrplnf +++OrgnlMsgNmId	Name Typ Pattern Original Message Name Identification SCLSDDOrgnlMsgNmId pac\..003[A-Za-z0-9\.\.]{0,27} PACS\..003[A-Za-z0-9\.\.]{0,27}	Only pac.003.001.02 is allowed.	Name der Originalnachricht. Belegung mit "pac.003" oder "PACS.003" zulässig. (Schema-Validierung)	Message type of the original bulk. May be completed with 'pac.003' or 'PACS.003' (Schema validation).
1..n	TxInf Document +FIToFIPmtRvsl ++TxInf	Name Typ Transaction Information SCLSDDPaymentTransactionInformation5	Mandatory		
1..1	RvslId Document +FIToFIPmtRvsl ++TxInf +++RvslId	Name Typ Pattern Reversal Identification SCLSDDId7 ([A-Za-z0-9][+ \? / - : \(\) \.\. \, '])(1,35)	Mandatory AT-R7 Specific reference of the Creditor Bank for the reversal Usage Rule: Must contain a reference that is meaningful to the Creditor's Bank.	Referenznummer der ersten Inkassostelle für den Reversal. Reversal Id ist Bestandteil der Doppelseinreichungskontrolle auf Einzelsatzebene. Fehlercode: AM05	Reference number of the payment service provider initiating the reversal. Reversal Id is part of the duplication check at single record level. Error code: AM05
0..1	OrgnlInstrId Document +FIToFIPmtRvsl ++TxInf +++OrgnlInstrId	Name Typ Pattern Original Instruction Identification SCLSDDId7 ([A-Za-z0-9][+ \? / - : \(\) \.\. \, '])(1,35)	Usage Rule: Mandatory if provided in the original instruction.	Die "Original Instruction ID" des zugrundeliegenden pac.003. Wird hier nur angegeben, wenn bereits in der ursprünglichen Lastschrift belegt.	Original Instruction ID of the original pac.003. Only be given if the ID was part of the original direct debit.
1..1	OrgnlEndToEndId Document +FIToFIPmtRvsl ++TxInf +++OrgnlEndToEndId	Name Typ Length Pattern WhiteSpace Original End To End Identification Max35Text 1 .. 35 \\S+.* collapse	Mandatory AT-10 Creditor's reference to the direct debit collection	Referenznummer des Zahlungsempfängers der zu stornierenden Original-Lastschrift.	Original reference of the creditor End-to-End-ID of the original direct debit
1..1	OrgnlTxId Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxId	Name Typ Pattern Original Transaction Identification SCLSDDId7 ([A-Za-z0-9][+ \? / - : \(\) \.\. \, '])(1,35)	Mandatory AT-43 Creditor Bank Reference of the collection Usage Rule: Must contain a reference that is meaningful to the Creditor's Bank and is unique over time.	Referenznummer der Bank des Zahlungsempfängers für die zu stornierende Original-Lastschrift. Bei Weiterleitung der Zahlung über andere CSM ggf. Fehlercode: XT75.	Reference of the creditor bank. Transaction ID of the original direct debit. Where applicable, error code XT75, if payment is forwarded to another CSM.
1..1	OrgnlIntrBkSttlmAmt Document	Name Typ FractionDigits Original Interbank Settlement Amount SCLSDDCurrencyAndAmount_Tx 2	AT- 06 Amount of the Collection in euro Usage Rule: Only 'EUR'	Betrag der zu stornierenden Original-Lastschrift.	Original amount of the original direct debit.

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+FIToFIPmtRvsl ++TxInf +++OrgnlIntrBkSttlmAmt	TotalDigits 18 Inclusive 0.01 .. 999999999.99 Pattern [0-9]{0,15}(\.([0-9]{0,2}))?{0,1}	is allowed. Amount must be 0.01 or more and 999999999.99 or less. Format Rule: The fractional part has a maximum of two digits	Bis zu 15 Zeichen sind im ganzzahligen Wertebereich erlaubt. Weiterhin maximal bis zwei Nachkommastellen erlaubt. (Schema-Validierung) Währungskennzeichen ist immer "EUR". (Schema-Validierung) Betragsangabe muss mindestens den Wert 0.01 enthalten und darf den Wert 999999999.99 nicht übersteigen. (Schema-Validierung)	Integer value of up to 15 characters is allowed. Maximum number of decimal places allowed is two. (Schema validation) Currency symbol is always 'EUR'. (Schema validation) Amount must be at least 0.01 and no more than 999999999.99. (Schema validation)
1..1	RvsdIntrBkSttlmAmt Document +FIToFIPmtRvsl ++TxInf +++RvsdIntrBkSttlmAmt	Name Reversed Interbank Settlement Amount Typ SCLSDDCurrencyAndAmount_Tx FractionDigits 2 TotalDigits 18 Inclusive 0.01 .. 999999999.99 Pattern [0-9]{0,15}(\.([0-9]{0,2}))?{0,1}	AT-44 Amount of the reversal in euro Usage Rule: 'Reversed Interbank Settlement Amount must be the same as the Amount of the Collection (AT-06) plus any Charges. Only 'EUR' is allowed. Amount must be 0.01 or more and 999999999.99 or less. Format Rule: The fractional part has a maximum of two digits.	Betrag des Reversals. Die rechnerische Richtigkeit der Addition <OrgnlIntrBkSttlmAmt> + <ChrgsInf/Amt> = <RvsdIntrBkSttlmAmt> wird geprüft, wenn <ChrgsInf> gefüllt ist. Fehlercode: XT78 Bis zu 15 Zeichen sind im ganzzahligen Wertebereich erlaubt. Weiterhin maximal bis zwei Nachkommastellen erlaubt. (Schema-Validierung) Währungskennzeichen ist immer "EUR". (Schema-Validierung) Betragsangabe muss mindestens den Wert 0.01 enthalten und darf den Wert 999999999.99 nicht übersteigen. (Schema-Validierung)	Amount of the reversal. The correctness of the sum <OrgnlIntrBkSttlmAmt> + <ChrgsInf/Amt> = <RvsdIntrBkSttlmAmt> is checked, if <ChrgsInf> is completed. Error code: XT78 Integer value of up to 15 characters is allowed. Maximum number of decimal places allowed remains two. (Schema validation) Only EUR is allowed (Schema validation) Amount must be at least 0.01 and no more than 999999999.99. (Schema validation)
0..1	RvsdInstdAmt	Name Reversed Instructed Amount Typ SCLSDDCurrencyAndAmount_Tx	Usage Rule: Only allowed in the case an	Wird der Elementblock "Charges Information" genutzt, muss auf	If the element block "Charges Information" is used, the element

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFIPmtRvsl ++TxInf +++RvsdInstdAmt	FractionDigits 2 TotalDigits 18 Inclusive 0.01 .. 999999999.99 Pattern [0-9]{0,15}(\. [0-9]{0,2}){0,1}	Interchange Fee is included, i.e., 'Amount' under 'Charges Information' is used. Only 'EUR' is allowed. Amount must be 0.01 or more and 999999999.99 or less. Format Rule: The fractional part has a maximum of two digits.	Grund einer ISO-Anforderung zusätzlich das Element "Reversed Instructed Amount" belegt sein. Fehlercode: XT13 Falls belegt, obwohl "Amount" in "Charges Information" nicht belegt ist. Fehlercode: XT33 Maximal bis zwei Nachkommastellen erlaubt. (Schema-Validierung) Währungskennzeichen ist immer "EUR". (Schema-Validierung) Betragsangabe muss mindestens den Wert 0.01 enthalten und darf den Wert 999999999.99 nicht übersteigen. (Schema-Validierung)	"Reversed Instructed Amount" must also be completed, in compliance with an ISO requirement. Error code: XT13 If completed, although "Amount" in "Charges Information" is not completed: Error code: XT33 The fractional part has a maximum of two digits. (Schema validation) Only EUR is allowed (Schema validation) Amount must be at least 0.01 and no more than 999999999.99. (Schema validation)
0..1	ChrgBr Document +FIToFIPmtRvsl ++TxInf +++ChrgBr	Name Charge Bearer Typ SCLSDDChargeBearerType1Code	Usage Rule: Only 'SLEV' is allowed.	Nur SLEV ist erlaubt. (Schema-Validierung)	Only SLEV is allowed. (Schema validation)
Anwendbare Codes / Acceptable Codes					
0..1	ChrgsInf Document +FIToFIPmtRvsl ++TxInf +++ChrgsInf	Name Charges Information Typ SCLSDDChargesInformation1	Usage Rule: Only one occurrence is allowed.	Wird der Elementblock "Charges Information" genutzt, muss auf Grund einer ISO-Anforderung zusätzlich das Element "Reversed Instructed Amount" belegt sein. Fehlercode: XT13	If the element block "Charges Information" is used, the element "Reversed Instructed Amount" must also be completed, in compliance with an ISO requirement. Error code: XT13
1..1	Amt Document	Name Amount Typ SCLSDDCurrencyAndAmount_Tx FractionDigits 2	AT-R8 Amount of the Interchange Fee Usage Rule: Only 'EUR'	Maximal zwei Nachkommastellen erlaubt. (Schema-Validierung)	The fractional part has a maximum of two digits. (Schema validation)

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+FIToFIPmtRvsl ++TxInf +++ChrgsInf ++++Amt	TotalDigits 18 Inclusive 0.01 .. 999999999.99 Pattern [0-9]{0,15}(\.([0-9]{0,2}))?{0,1}	is allowed. Amount must be 0.01 or more and 999999999.99 or less. Format Rule: The fractional part has a maximum of two digits.	Währungskennzeichen ist immer "EUR". (Schema-Validierung) Betragsangabe muss mindestens den Wert 0.01 enthalten und darf den Wert 999999999.99 nicht übersteigen. (Schema-Validierung)	Only EUR is allowed (Schema validation) Amount must be at least 0.01 and no more than 999999999.99. (Schema validation)
1..1	Pty Document +FIToFIPmtRvsl ++TxInf +++ChrgsInf ++++Pty	Name Party Typ SCLSDDBranchAndFinancialInstitutionIdentification3			
1..1	FinInstnId Document +FIToFIPmtRvsl ++TxInf +++ChrgsInf ++++Pty +++++FinInstnId	Name Financial Institution Identification Typ SCLSDDFinancialInstitutionIdentification5Character	AT-13 BIC of the Debtor Bank Usage Rule: Only BIC is allowed.		
1..1	BIC Document +FIToFIPmtRvsl ++TxInf +++ChrgsInf ++++Pty +++++FinInstnId ++++++BIC	Name BIC Typ BICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}			
0..1	InstgAgt Document +FIToFIPmtRvsl ++TxInf +++InstgAgt	Name Instructing Agent Typ SCLSDDBranchAndFinancialInstitutionIdentification3	Usage Rule: Only BIC is allowed.	Ursprünglicher Einreicher der das Bulk, in dem die R-Transaktion enthalten war, in den SCL eingeliefert hat Nur bei Auslieferung der BBK an den SCL-Teilnehmer (Bank) belegt. Hier steht bei Zahlungen die über die STEP2 an den SCL geleitet werden der BIC des direkten	Original submitter in the SCL of the bulk which contained the R-transaction. Only used in deliveries from the BBk to the SCL participant. In payments that have been submitted by STEP2, the BIC of the direct STEP2 participant is

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
				STEP2-Teilnehmers bzw. bei Zahlungen die innerhalb des SEPA-Clearers abgewickelt werden der BIC des SCL-Teilnehmers, der den Reversal im SCL eingereicht hat.	displayed here.
1..1	FinInstnId Document +FIToFIPmtRvsl ++TxInf +++InstgAgt ++++FinInstnId	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Ch oice			
1..1	BIC Document +FIToFIPmtRvsl ++TxInf +++InstgAgt ++++FinInstnId +++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}		Belegung nur im Settled Debit File (SDF) erlaubt, darf im Input Debit File (IDF) des Teilnehmers an den SCL nicht enthalten sein. Fehlercode: XT13	Only permitted in the Settled Debit File (SDF), may not be contained in the Input Debit File (IDF) submitted by SCL participant. Error code: XT13
1..1	RvslRsnInf Document +FIToFIPmtRvsl ++TxInf +++RvslRsnInf	Name Typ Reversal Reason Information SCLSDDReversalReasonInformation1	Usage Rule: 'Reversal Reason Information' must be present either in 'Original Group Information' or 'Transaction Information'. 'Reversal Reason Information' is to be used to indicate a reversal reason of the individual transaction. Only one occurrence of 'Reversal Reason Information' is allowed.	Informationen über den Grund des Reversals.	Information on the reason for reversal.
1..1	Orgtr Document +FIToFIPmtRvsl ++TxInf +++RvslRsnInf+ ++++Orgtr	Name Typ Originator SCLSDDId5	AT-R2 Identification of the type of party that initiated the reversal Usage Rule: Mandatory if 'Reversal Reason Information' is used at this level.	Initiator des Reversals	Reversal originator.

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
			'Name' is limited to 70 characters in length. Limited to BIC (for the Creditor Bank) or 'Name' (for the Creditor).		
1..1	Nm Document +FIToFIPmtRvsl ++TxInf +++RvslRsnInf ++++Orgtr +++++Nm	Name Name Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse		Initiator des Reversals (Kunde) Keine gleichzeitige Belegung mit Originator/BIC zulässig. (Schema-Validierung)	Reversal originator (client) Cannot be populated simultaneously with originator/BIC. (Schema validation)
1..1	Id Document +FIToFIPmtRvsl ++TxInf +++RvslRsnInf ++++Orgtr +++++Id	Name Identification Typ SCLSDDParty3Choice		Initiator des Reversals (Zahlungsdienstleister des Kunden)	Reversal originator (client's bank).
1..1	OrgId Document +FIToFIPmtRvsl ++TxInf +++RvslRsnInf ++++Orgtr +++++Id ++++++OrgId	Name Organisation Identification Typ SCLSDDOrganisationIdentification2			
1..1	BICOrBEI Document +FIToFIPmtRvsl ++TxInf +++RvslRsnInf ++++Orgtr +++++Id ++++++OrgId +++++++BICOrBEI	Name BIC or BEI Typ BICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}			
1..1	Rsn Document +FIToFIPmtRvsl ++TxInf	Name Reason Typ SCLSDDReversalReason1Choice	Usage Rule: Mandatory if 'Reversal Reason Information' is used at this level.	Spezifizierung des Grundes für den Reversal.	Reason for reversal

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	+++RvslRsnInf ++++Rsn Cd Document +FIToFIPmtRvsl ++TxInf +++RvslRsnInf ++++Rsn +++++Cd	Name Typ Code SCLSDDTransactionReversalReason2Code	AT-31 Reason Code for Reversal See Message Element Specifications below.	Zulässiger Code: AM05 (Schema-Validierung)	Permissible code: AM05 (Schema validation)
Anwendbare Codes / Acceptable Codes					
AM05					
MS02					
MS03					
1..1	OrgnlTxRef Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef	Name Typ Original Transaction Reference SCLSDDOriginalTransactionReference1	Mandatory An exact copy of all attributes of the received DS-04 being reversed Usage Rule: The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction.	Exakte Kopie der Datenelemente der Lastschrift, die Gegenstand des Reversals ist, d. h. die nachfolgenden Elemente müssen mit den jeweiligen Originalwerten der ursprünglichen Lastschrift belegt werden.	Data of the original message The following data elements must be completed according to the original underlying direct debit.
1..1	IntrBkSttlmDt Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++IntrBkSttlmDt	Name Typ Pattern Interbank Settlement Date ISODate [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}	AT-26 Settlement date of the Collection	Abrechnungsdatum des Einzugs der Originalnachricht. Bei Weiterleitung der Zahlung an andere CSM ggf. Fehlercode: XT74. Dieses Datum der Original-Lastschrift muss kleiner oder gleich Datum des <IntrBkSttlmDt> im <GrpHdr> sein. Fehlercode: DT01	Settlement date of the original direct debit. Where applicable error code XT74, if payment is forwarded via another CSM. The date of the original direct debit must be the same or before the date of <IntrBkSttlmDt> in <GrpHdr>. Error code: DT01

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	ReqdColltnDt Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++ReqdColltnDt	Name Typ Pattern Requested Collection Date ISODate [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}	AT-11 Due date of the Collection	Fälligkeitsdatum des Einzugs	Due date of original direct debit
1..1	CdtrSchmeld Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++CdtrSchmeld	Name Typ Creditor Scheme Identification SCLSDDCdtrSchmeld	AT-02 Identifier of the Creditor	Identifikator des Zahlungsempfängers.	Identifier of the creditor from the original direct debit
1..1	Id Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++CdtrSchmeld +++++Id	Name Typ Identification SCLSDDPriatelidentification2			
1..1	PrvtId Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++CdtrSchmeld +++++Id ++++++PrvtId	Name Typ Private Identification SCLSDDPrtly2			
1..1	Othr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++CdtrSchmeld +++++Id ++++++PrvtId +++++++Othr	Name Typ Other SCLSDDid10			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Id Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++CdtrSchmeld +++++Id ++++++PrvtId +++++++Othr +++++++Id	Name Typ Pattern Identification SCLSDDId8 ([A-Za-z0-9][+ \? / \- :\(\)\ \.\ ' \s]){1,35}		Identifikator des Zahlungsempfängers.	Identifier of the creditor
1..1	SchmeNm Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++CdtrSchmeld +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm	Name Typ Scheme Name FinancialIdentificationSchemeName2			
1..1	Prtry Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++CdtrSchmeld +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm +++++++Prtry	Name Typ Proprietary SCLSDDId9			
Anwendbare Codes / Acceptable Codes					
SEPA					
0..1	SttlmInf Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++SttlmInf	Name Typ Settlement Information SCLSDDSettlementInformation3			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	SttlmMtd Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++SttlmInf +++++SttlmMtd	Name Settlement Method Typ SCLSDDSettlementMethod1Code		Nur "CLRG" (Schema-Validierung)	Only 'CLRG' (Schema validation)
Anwendbare Codes / Acceptable Codes					
CLRG					
0..1	ClrSys Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++SttlmInf +++++ClrSys	Name Clearing System Typ SCLSDDClearingSystemIdentification1Choice			
1..1	Prtry Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++SttlmInf +++++ClrSys ++++++Prtry	Name Proprietary Typ Max35Text_Prtry Length 1 .. 35 Pattern \S+.* WhiteSpace collapse		Nur "SCL" (Schema-Validierung)	Only 'SCL' (Schema validation)
Anwendbare Codes / Acceptable Codes					
SCL					
1..1	PmtTplnf Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++PmtTplnf	Name Payment Type Information Typ SCLSDDPaymentTypeInformation6	AT-20 Identification code of the Scheme AT-21 Transaction / Sequence Type AT-59 Category purpose of the Collection	Identifikation des Schemas.	Identification code of the schema
1..1	SvcLvl Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++PmtTplnf +++++SvcLvl	Name Service Level Typ SCLSDDSERVICELEVEL2Choice			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Cd Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++PmtTpInf +++++SvcLvl ++++++Cd	Name Code Typ SCLSDDSERVICELEVEL1CODE			
Anwendbare Codes / Acceptable Codes					
SEPA					
1..1	LclInstrm Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++PmtTpInf +++++LclInstrm	Name Local Instrument Typ SCLSDDLCLINSTRUMENT1CHOICE			
1..1	Cd Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++PmtTpInf +++++LclInstrm ++++++Cd	Name Code Typ ExternalLocalInstrument1Code Length 1 .. 35		Belegung gem. Originalzahlung. Es dürfen nur die Werte "CORE" oder "B2B" enthalten sein (Schema-Validierung). In einem COR-File dürfen nur CORE-Bulks und in einem B2B-File nur B2B-Bulks enthalten sein. Fehlercode: XT43 Eine gemischte Einreichung von B2B- und CORE-Lastschriften in einem Bulk ist nicht zulässig. Fehlercode: XT43	Entry according to original payment. Only the codes 'CORE' or 'B2B' may be entered. (Schema validation) In a COR-File only CORE bulks are allowed. In a B2B file only B2B bulks are allowed. Error code: XT43 Mixed submission of B2B and CORE Direct Debits in one bulk is not allowed. Error code: XT43
Anwendbare Codes / Acceptable Codes					
B2B					
CORE					
1..1	SeqTp Document	Name Sequence Type Typ SCLSDDSEQUENCETYPE1CODE		Lastschrift-Typ (Schema-Validierung)	Sequence Type of the direct debit (Schema validation)

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++PmtTpInf +++++SeqTp				
Anwendbare Codes / Acceptable Codes					
		FNAL FRST OOFF RCUR			
0..1	CtgyPurp Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++PmtTpInf +++++CtgyPurp	Name Category Purpose Typ CategoryPurpose1Choice		"Verwendungskategorie" der Lastschrift	Purpose of the collection
1..1	Cd Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++PmtTpInf +++++CtgyPurp +++++Cd	Name Code Typ ExternalCategoryPurpose1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++PmtTpInf +++++CtgyPurp +++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	MndtRltdInf Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf	Name Mandate Related Information Typ SCLSDDMandateRelatedInformation1	AT-01 Unique Mandate Reference AT-16 Placeholder for the electronic signature data, if applicable AT-17 The type of Mandate (paper or e-Mandate).		

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
			AT-18 Identifier of the original Creditor who issued the Mandate AT-19 Unique mandate reference as given by the original creditor who issued the mandate AT-24 Reason for Amendment of the Mandate AT-25 Signing date of the Mandate AT-60 Reference of the validation made by the Debtor Bank (if present in DS-03)		
1..1	MndtId Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++MndtId	Name Typ Pattern Mandate Identification SCLSDDId8 ([A-Za-z0-9][+ \? / - : () \. ' \"s]){1,35}		Eindeutige Mandatsreferenz. (Nur Schema-Validierung).	Unique mandate reference. (Schema validation only).
1..1	DtOfSgnt Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++DtOfSgnt	Name Typ Pattern Date Of Signature ISODate [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}		Datum der Unterzeichnung des Mandats.	Date when mandate was signed.
0..1	AmdmntInd Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInd	Name Typ Amendment Indicator TrueFalseIndicator		Grund für die Änderung des Mandats, falls vorhanden, muss Inhalt "true" oder "false" sein. (Schema-Validierung) Falls Feld nicht belegt ist, wird von der Standardeinstellung "false" ausgegangen	Reason for amendment of the mandate. If completed must be 'TRUE' or 'FALSE'. (Schema validation) If the field is not completed, 'FALSE' is assumed to be the default setting
0..1	AmdmntInfDtls Document	Name Typ Amendment Information Details SCLSDDAmendmentInformationDetails1		Belegung gemäß Originaltransaktion.	Entry according to original payment

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs				
0..1	OrgnlMndtId Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlMndtId	Name Original Mandate Identification Typ SCLSDDId8 Pattern ([A-Za-z0-9][+ ? / - : (\\) \., ' \s]){1,35}		Eindeutige Mandatsreferenz wie durch den ursprünglichen Gläubiger vergeben, der das Mandat herausgab.	Unique mandate reference as given by the original creditor who issued the mandate.
0..1	OrgnlCdtrSchmeld Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlCdtrSchmeld	Name Original Creditor Scheme Identification Typ SCLSDDCdtrSchmeld1		Identifikator des ursprünglichen Zahlungsempfängers, der das Mandat herausgegeben hat.	Identifier of the original creditor who issued the mandate.
0..1	Nm Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlCdtrSchmeld ++++++Nm	Name Name Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse		Name des ursprünglichen Zahlungsempfängers.	Name of the original creditor.
0..1	Id Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlCdtrSchmeld ++++++Id	Name Identification Typ SCLSDDPrivateIdentification			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	PrvtId Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlCctrSchmeld +++++++Id +++++++PrvtId	Name Typ Private Identification SCLSDDPrty1			
1..1	Othr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlCctrSchmeld +++++++Id +++++++PrvtId +++++++Othr	Name Typ Other SCLSDDId4			
1..1	Id Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlCctrSchmeld +++++++Id +++++++PrvtId +++++++Othr +++++++Id	Name Typ Pattern Identification SCLSDDId8 ([A-Za-z0-9][+ \? / - : \(\) \^ _ ! \s]){1,35}		Identifikator des ursprünglichen Zahlungsempfängers, der das Mandat herausgegeben hat.	Identifier of the original creditor who issued the mandate.
1..1	SchmeNm Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf	Name Typ Scheme Name FinancialIdentificationSchemeName2			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+++++AmdmntInfDtIs +++++OrgnCctrSchmeld +++++Id +++++PrvtId +++++Othr +++++SchmeNm				
1..1	Prtry Document +FIToFIPmtRvsl ++TxInf +++OrgnITxRef ++++MndtRltdInf +++++AmdmntInfDtIs +++++OrgnCctrSchmeld +++++Id +++++PrvtId +++++Othr +++++SchmeNm +++++Prtry	Name Typ Proprietary SCLSDDId9		Nur "SEPA" ist zulässig (Schema-Validierung).	Only the code 'SEPA' is allowed. (Schema validation)
Anwendbare Codes / Acceptable Codes					
SEPA					
0..1	OrgnIDbtrAcct Document +FIToFIPmtRvsl ++TxInf +++OrgnITxRef ++++MndtRltdInf +++++AmdmntInfDtIs +++++OrgnIDbtrAcct	Name Typ Original Debtor Account SCLSDDCashAccount8			
1..1	Id Document +FIToFIPmtRvsl ++TxInf +++OrgnITxRef ++++MndtRltdInf +++++AmdmntInfDtIs +++++OrgnIDbtrAcct +++++Id	Name Typ Identification SCLSDDAccountIdentification4Choice			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	IBAN Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlDbtrAcct +++++++Id ++++++IBAN	Name IBAN Typ IBANIdentifier Pattern [a-zA-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}			
1..1	Othr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlDbtrAcct +++++++Id ++++++Othr	Name Other Typ SCLSDDOrgnlDbtrAcctOther2			
1..1	Id Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlDbtrAcct +++++++Id ++++++Othr ++++++Id	Name Identification Typ Max34Text Length 1 .. 34 Pattern \S+.* WhiteSpace collapse			
0..1	OrgnlDbtrAgt Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlDbtrAgt	Name Original Debtor Agent Typ SCLSDDOrgnlDbtrAgt			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	FinInstnId Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlDbtrAgt +++++++FinInstnId	Name Typ Financial Institution Identification SCLSDDOrgnlDbtrAgt1			
1..1	BIC Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlDbtrAgt +++++++FinInstnId +++++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}			
1..1	Othr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlDbtrAgt +++++++FinInstnId +++++++Othr	Name Typ Other SCLSDDOrgnlDbtrAgtOther2			
1..1	Id Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++AmdmntInfDtIs ++++++OrgnlDbtrAgt +++++++FinInstnId +++++++Othr +++++++Id	Name Typ Length Pattern WhiteSpace Identification Max35Text 1 .. 35 \\S+.* collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	ElctrcnSgnt Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++MndtRltdInf +++++ElctrcnSgnt	Name Electronic Signature Typ Max1025Text Length 1 .. 1025 Pattern \S+.* WhiteSpace collapse		Platzhalter Elektronische Unterschrift falls vorhanden	Placeholder for electronic signature.
0..1	RmtInf Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++RmtInf	Name Remittance Information Typ SCLSDDRemittanceInformation1	AT-22 Remittance information	Verwendungszweckangaben des Zahlungsempfängers in strukturierter oder unstrukturierter Form. (Schema-Validierung)	Structured or unstructured remittance information (Schema validation)
1..1	Ustrd Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++RmtInf +++++Ustrd	Name Unstructured Typ Max140Text Length 1 .. 140 Pattern \S+.* WhiteSpace collapse			
1..1	Strd Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++RmtInf +++++Strd	Name Structured Typ SCLSDDStructuredRemittanceInformation6		Im strukturierten Verwendungszweck dürfen max. 140x vorkommen. Es zählen nur die Informationen innerhalb des Elements <Strd>. Die Elemente inklusive Inhalte innerhalb des tags <Strd> werden mitgezählt. Fehlercode: XT33 Alle ISO 20022 Feldoptionen sind erlaubt.	Structured remittance information must not exceed 140 characters. Only information within the <Strd> element is counted. The elements including the contents within the tag <Strd> are also counted. Error code: XT33 All ISO 20022 field options are allowed.
0..1	CdtrRefInf Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++RmtInf +++++Strd +++++CdtrRefInf	Name Creditor Reference Information Typ SCLSDDCreditorReferenceInformation2			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Tp Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++RmtInf +++++Strd ++++++CdtrRefInf +++++++Tp	Name Type Typ SCLSDDCreditorReferenceType2			
1..1	CdOrPrtry Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++RmtInf +++++Strd ++++++CdtrRefInf +++++++Tp +++++++CdOrPrtry	Name Code or Proprietary Typ SCLSDDCreditorReferenceType1Choice			
1..1	Cd Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++RmtInf +++++Strd ++++++CdtrRefInf +++++++Tp +++++++CdOrPrtry +++++++Cd	Name Code Typ SCLSDDDocumentType3Code			
Anwendbare Codes / Acceptable Codes					
0..1	Issr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++RmtInf +++++Strd	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	<p>+++++CdtrRefInf +++++Tp +++++Issr</p> <p>Ref</p> <p>Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++RmtInf +++++Strd +++++CdtrRefInf +++++Ref</p>	<p>Name Reference Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse</p>			
0..1	<p>UltmtDbtr</p> <p>Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr</p>	<p>Name Ultimate Debtor Typ SCLSDDDPartyIdentification10</p>	<p>AT-15 Name of the Debtor Reference Party AT-37 Identification code of the Debtor Reference Party</p>	<p>Abweichender Zahler</p>	<p>Ultimate debtor</p>
0..1	<p>Nm</p> <p>Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr ++++Nm</p>	<p>Name Name Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse</p>		<p>Name des abweichenden Zahlers</p>	<p>Name of ultimate debtor</p>
0..1	<p>Id</p> <p>Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr ++++Id</p>	<p>Name Identification Typ SCLSDDDParty4Choice</p>		<p>Identifikation des abweichenden Zahlers</p>	<p>Identifier of ultimate debtor</p>
1..1	<p>Orgld</p> <p>Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr ++++Id +++++Orgld</p>	<p>Name Organisation Identification Typ SCLSDDOrganisationIdentification4</p>			

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	BICOrBEI Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++Orgld +++++++BICOrBEI	Name BIC or BEI Typ SCLSDDAnyBICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}			
1..1	Othr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++Orgld +++++++Othr	Name Other Typ SCLSDDGenericOrganisationIdentification1			
1..1	Id Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++Orgld +++++++Othr +++++++Id	Name Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	SchmeNm Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++Orgld +++++++Othr +++++++SchmeNm	Name Scheme Name Typ SCLSDDOrganisationIdentificationSchemeName1Choice			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Cd Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++Orgld +++++++Othr +++++++SchmeNm +++++++Cd	Name Code Typ SCLSDDExternalOrganisationIdentification1 Length Code 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++Orgld +++++++Othr +++++++SchmeNm +++++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++Orgld +++++++Othr +++++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	Prvtld Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++Prvtld	Name Private Identification Typ SCLSDDPersonIdentification5			

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	DtAndPlcOfBirth Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth	Name Date and Place of Birth Typ DateAndPlaceOfBirth			
1..1	BirthDt Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth +++++++BirthDt	Name Birth Date Typ ISODate Pattern [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}			
0..1	PrvcOfBirth Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth +++++++PrvcOfBirth	Name Province of Birth Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	CityOfBirth Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth +++++++CityOfBirth	Name City of Birth Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	CtryOfBirth Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth +++++++CtryOfBirth	Name Country of Birth Typ CountryCode Pattern [A-Z]{2,2}			
1..1	Othr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++Othr	Name Other Typ SCLSDDGenericPersonIdentification1			
1..1	Id Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++Othr +++++++Id	Name Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	SchmeNm Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm	Name Scheme Name Typ SCLSDDPersonIdentificationSchemeName1 Choice			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Cd Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm +++++++Cd	Name Code Typ SCLSDDExternalPersonIdentification1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm +++++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtDbtr +++++Id ++++++PrvtId +++++++Othr +++++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	Dbtr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr	Name Debtor Typ SCLSDDDPartyIdentification9	AT-14 Name of the Debtor AT-09 Address of the Debtor AT-27 Debtor Identification code	Zahler	Debtor

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Nm Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++Nm	Name Name Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse		Name des Zahlers oder Ersatzinformationen aus der Originalnachricht	Name of the Debtor or additional informations according the original payment
0..1	PstlAdr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++PstlAdr	Name Adresse des Zahlers Typ SCLSDDPPostalAddress1			
0..1	Ctry Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++PstlAdr +++++Ctry	Name Country Typ CountryCode Pattern [A-Z]{2,2}			
0..2	AdrLine Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++PstlAdr +++++AdrLine	Name Address Line Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse		"Address Line" darf nur zweimal vorkommen. (Schema-Validierung)	Maximum of two occurrences of 'address line' allowed. (Schema validation)
0..1	Id Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id	Name Identification Typ SCLSDDPParty4Choice		Identifikation des Zahlers	Identifier of debtor

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Orgld Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++Orgld	Name Typ Organisation Identification SCLSDDOrganisationIdentification4		Entweder "Organisation Identification" oder "Private Identification" ist vorhanden. (Schema-Validierung) Alle ISO 20022 Feldoptionen sind erlaubt.	May not be given simultaneously with <Id><PrvtId> (see below). (Schema validation) All ISO 20022 field options are allowed.
1..1	BICorBEI Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++Orgld +++++++BICorBEI	Name Typ Pattern BIC or BEI SCLSDDAnyBICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}			
1..1	Othr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++Orgld +++++++Othr	Name Typ Other SCLSDDGenericOrganisationIdentification1			
1..1	Id Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++Orgld +++++++Othr +++++++Id	Name Typ Length Pattern WhiteSpace Identification Max35Text 1 .. 35 \\S+.* collapse			
0..1	SchmeNm Document	Name Typ Scheme Name SCLSDDOrganisationIdentificationSchemeName1Choice			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+FIToFIPmtRvsl ++TxInf +++OrgnITxRef ++++Dbtr +++++Id ++++++Orgld +++++++Othr +++++++SchmeNm				
1..1	Cd Document +FIToFIPmtRvsl ++TxInf +++OrgnITxRef ++++Dbtr +++++Id ++++++Orgld +++++++Othr +++++++SchmeNm +++++++Cd	Name Code Typ SCLSDDExternalOrganisationIdentification1 Code Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +FIToFIPmtRvsl ++TxInf +++OrgnITxRef ++++Dbtr +++++Id ++++++Orgld +++++++Othr +++++++SchmeNm +++++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +FIToFIPmtRvsl ++TxInf +++OrgnITxRef ++++Dbtr +++++Id ++++++Orgld +++++++Othr +++++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	PrvtId Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++PrvtId	Name Typ Private Identification SCLSDDPersonIdentification5		Darf nicht gleichzeitig mit Id/Orgld (siehe oben) angegeben werden. (Schema-Validierung) Alle ISO 20022 Optionen sind erlaubt.	May not be given simultaneously with <Id><Orgld > (see below). (Schema validation) All ISO 20022 field options are allowed.
1..1	DtAndPlcOfBirth Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth	Name Typ Date and Place of Birth DateAndPlaceOfBirth			
1..1	BirthDt Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth +++++++BirthDt	Name Typ Pattern Birth Date ISODate [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}			
0..1	PrvcOfBirth Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth +++++++PrvcOfBirth	Name Typ Length Pattern WhiteSpace Province of Birth Max35Text 1 .. 35 \\S+.* collapse			
1..1	CityOfBirth	Name Typ City of Birth Max35Text			

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth +++++++CityOfBirth	Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	CtryOfBirth Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++PrvtId +++++++DtAndPlcOfBirth +++++++CtryOfBirth	Name Country of Birth Typ CountryCode Pattern [A-Z]{2,2}			
1..1	Othr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++PrvtId +++++++Othr	Name Other Typ SCLSDDGenericPersonIdentification1			
1..1	Id Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++PrvtId +++++++Othr +++++++Id	Name Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	SchmeNm	Name Scheme Name Typ SCLSDDPersonIdentificationSchemeName1			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm	Choice			
1..1	Cd Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm +++++++Cd	Name Code Typ SCLSDDEExternalPersonIdentification1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm +++++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Dbtr +++++Id ++++++PrvtId +++++++Othr +++++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	DbtrAcct Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++DbtrAcct	Name DebtorAccount Typ SCLSDDCashAccount7	AT -07 Account number (IBAN) of the Debtor	IBAN des Zahlungspflichtigen.	Account number of the debtor
1..1	Id Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++DbtrAcct +++++Id	Name Identification Typ SCLSDDAccountIdentification3Choice			
1..1	IBAN Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++DbtrAcct +++++Id ++++++IBAN	Name IBAN Typ IBANIdentifier Pattern [a-zA-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}		IBAN des Zahlers	IBAN of the debtor
1..1	DbtrAgt Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++DbtrAgt	Name Debtor Agent Typ SCLSDDBranchAndFinancialInstitutionIdentification3	AT-13 BIC of Debtor Bank	BIC des Zahlungsdienstleister des Zahlers	BIC of Debtor Bank
1..1	FinInstnId Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++DbtrAgt +++++FinInstnId	Name Financial Institution Identification Typ SCLSDDFinancialInstitutionIdentification5Choice			
1..1	BIC Document	Name BIC Typ BICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3})		Debtor Agent BIC aus der Originaltransaktion.	Debtor Agent BIC from the original instruction

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++DbtrAgt +++++FinInstnld ++++++BIC	{0,1}		Gültigkeit des BIC anhand des SCL-Directories. Fehlercode: XT27 Prüfung nur bei Weiterleitung der Transaktion vom SEPA-Clearer an STEP2: BIC muss ein registrierter direkter oder Reachable BIC am entsprechenden STEP2 SDD Service sein. Fehlercode: PY01	Validity of BIC according to SCL Directory. Error code: XT27 Check only if the direct debit is forwarded from the SEPA-Clearer to STEP2: BIC must belong to a registered reachable BIC of the respective STEP2 SDD Service via the Deutsche Bundesbank. Error code: PY01
1..1	CdtrAgt Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++CdtrAgt	Name Typ Creditor Agent SCLSDDBranchAndFinancialInstitutionIdentification3	AT-12 BIC of the Creditor bank	BIC des Zahlungsdienstleisters des Zahlungsempfängers	BIC of the Creditor bank
1..1	FinInstnld Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++CdtrAgt +++++FinInstnld	Name Typ Financial Institution Identification SCLSDDFinancialInstitutionIdentification5Choice			
1..1	BIC Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++CdtrAgt +++++FinInstnld ++++++BIC	Name Typ Pattern BIC BICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}		Creditor Agent BIC ist Bestandteil der Doppeleinreichungskontrolle auf Einzelsatzebene. Fehlercode: AM05 Gültigkeit des BIC anhand des SCL-Directories. Fehlercode: XT27 Prüfung nur bei Weiterleitung der Transaktion vom SEPA-Clearer an STEP2: BIC muss ein über die Bundesbank registrierter Reachable BIC am entsprechenden STEP2 SDD Service sein. Fehlercode: PY01	Creditor agent BIC is included in the duplication check at single record level Error code: AM05 Validity of BIC according to SCL-Directory. Error code: XT27 Check only if the direct debit is forwarded from the SEPA-Clearer to STEP2: BIC must belong to a registered reachable BIC of the respective STEP2 SDD Service via the Deutsche Bundesbank. Error code: PY01

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	Cdtr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Cdtr	Name Creditor Typ SCLSDDId2	AT-03 Name of the Creditor AT-05 Address of the Creditor	Zahlungsempfänger	Creditor
1..1	Nm Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Cdtr ++++Nm	Name Name Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse		Name des Zahlungsempfängers.	Name of the creditor.
0..1	PstlAdr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Cdtr ++++PstlAdr	Name Postal Address Typ SCLSDDPostalAddress1		Adresse des Zahlungsempfängers.	Address of the creditor.
0..1	Ctry Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Cdtr ++++PstlAdr ++++Ctry	Name Country Typ CountryCode Pattern [A-Z]{2,2}			
0..2	AdrLine Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++Cdtr ++++PstlAdr ++++AdrLine	Name Adress Line Typ Max70Text Length 1 .. 70 Pattern \S+.* WhiteSpace collapse		"Address Line" darf nur zweimal vorkommen. (Schema-Validierung)	Maximum of two occurrences of 'address line' allowed. (Schema validation)

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	CdtrAcct Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++CdtrAcct	Name Typ Creditor Account SCLSDDCashAccount7	AT-04 Account number (IBAN) of the Creditor	IBAN des Zahlungsempfängers.	Account number of the creditor
1..1	Id Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++CdtrAcct +++++Id	Name Typ Identification SCLSDDAccountIdentification3Choice			
1..1	IBAN Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++CdtrAcct +++++Id ++++++IBAN	Name Typ Pattern IBAN IBANIdentifier [a-zA-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}		IBAN des Zahlungsempfängers.	IBAN of the creditor
0..1	UltmtCdtr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr	Name Typ Ultimate Creditor SCLSDDPartyIdentification10	AT-38 Name of the Creditor Reference Party AT-39 Identification code of the Creditor Reference Party	Abweichender Zahlungsempfänger	Ultimate creditor
0..1	Nm Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Nm	Name Typ Length Pattern WhiteSpace Name Max70Text 1 .. 70 \\S+.* collapse		Name des abweichenden Zahlungsempfängers	Name of ultimate creditor
0..1	Id Document	Name Typ Identification SCLSDDParty4Choice			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
	+FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id				
1..1	Orgld Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++Orgld	Name Typ Organisation Identification SCLSDDOrganisationIdentification4			
1..1	BICorBEI Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++Orgld +++++++BICorBEI	Name Typ Pattern BIC or BEI SCLSDDAnyBICIdentifier [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}) {0,1}			
1..1	Othr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++Orgld +++++++Othr	Name Typ Other SCLSDDGenericOrganisationIdentification1			
1..1	Id Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++Orgld +++++++Othr +++++++++Id	Name Typ Length Pattern WhiteSpace Identification Max35Text 1 .. 35 \\S+.* collapse			

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	SchmeNm Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++Orgld +++++++Othr +++++++SchmeNm	Name Typ Scheme Name SCLSDDOrganisationIdentificationSchemeName1Choice			
1..1	Cd Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++Orgld +++++++Othr +++++++SchmeNm +++++++Cd	Name Typ Code SCLSDDExternalOrganisationIdentification1Code Length Pattern WhiteSpace 1 .. 4 \S+.* collapse			
1..1	Prtry Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++Orgld +++++++Othr +++++++SchmeNm +++++++Prtry	Name Typ Length Pattern WhiteSpace Proprietary Max35Text 1 .. 35 \S+.* collapse			
0..1	Issr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++Orgld	Name Typ Length Pattern WhiteSpace Issuer Max35Text 1 .. 35 \S+.* collapse			

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	+++++Othr +++++Issr PrvtId Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id +++++PrvtId	Name Typ Private Identification SCLSDDPersonIdentification5			
1..1	DtAndPlcOfBirth Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id +++++PrvtId +++++DtAndPlcOfBirth	Name Typ Daten and Place of Birth DateAndPlaceOfBirth			
1..1	BirthDt Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id +++++PrvtId +++++DtAndPlcOfBirth +++++BirthDt	Name Typ Pattern Birth Date ISODate [0-9]{4,4}\-[0-9]{2,2}\-[0-9]{2,2}			
0..1	PrvcOfBirth Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id +++++PrvtId +++++DtAndPlcOfBirth +++++PrvcOfBirth	Name Typ Length Pattern WhiteSpace Province of Birth Max35Text 1 .. 35 \\S+.* collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
1..1	CityOfBirth Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++Prvtld +++++++DtAndPlcOfBirth +++++++CityOfBirth	Name City of Birth Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
1..1	CtryOfBirth Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++Prvtld +++++++DtAndPlcOfBirth +++++++CtryOfBirth	Name Country of Birth Typ CountryCode Pattern [A-Z]{2,2}			
1..1	Othr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++Prvtld +++++++Othr	Name Other Typ SCLSDDGenericPersonIdentification1			
1..1	Id Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++Prvtld +++++++Othr +++++++Id	Name Identification Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			

Status	Element/Attribute	Format	EPC Referenzen (falls vorhanden)	Inhalte und Prüfung SEPA-Clearer	Contents and Checks
0..1	SchmeNm Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm	Name Scheme Name Typ SCLSDDPersonIdentificationSchemeName1 Choice			
1..1	Cd Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm +++++++Cd	Name Code Typ SCLSDDExternalPersonIdentification1Code Length 1 .. 4 Pattern \S+.* WhiteSpace collapse			
1..1	Prtry Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++PrvtId +++++++Othr +++++++SchmeNm +++++++Prtry	Name Proprietary Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			
0..1	Issr Document +FIToFIPmtRvsl ++TxInf +++OrgnlTxRef ++++UltmtCdtr +++++Id ++++++PrvtId +++++++Othr +++++++Issr	Name Issuer Typ Max35Text Length 1 .. 35 Pattern \S+.* WhiteSpace collapse			

Fett/Bold = Element/Element, Kursiv/Italic = Attribut/Attribute, Grau/Grey = Gruppe/Group